

Package ‘SticsRFiles’

February 23, 2024

Title Read and Modify 'STICS' Input/Output Files

Version 1.2.0

Date 2024-02-23

Description Manipulating input and output files of the 'STICS' crop model. Files are either 'JavaSTICS' XML files or text files used by the model 'fortran' executable. Most basic functionalities are reading or writing parameter names and values in both XML or text input files, and getting data from output files. Advanced functionalities include XML files generation from XML templates and/or spreadsheets, or text files generation from XML files by using 'xslt' transformation.

License LGPL (>= 3)

URL <https://github.com/SticsRPacks/SticsRFiles>,
<https://doi.org/10.5281/zenodo.4443206>

BugReports <https://github.com/SticsRPacks/SticsRFiles/issues>

Depends R (>= 3.6.0)

Imports cli, crayon, curl, data.table, dplyr (>= 1.0.0), lifecycle, lubridate, methods, rlang, rstudioapi, stringr, tibble, tidyr, tools, utils, XML, xml2, xslt

Suggests covr, formatR, knitr, learnr, readxl, rmarkdown, spelling, testthat

VignetteBuilder knitr

ByteCompile true

Encoding UTF-8

Language en-US

RoxygenNote 7.3.1

Collate 'add_node_to_doc.R' 'add_stics_nodes.R' 'all_in_par.R'
'all_out_var.R' 'attributes_list2matrix.R'
'check_choice_param.R' 'check_java_path.R'
'check_java_workspace.R' 'check_output_files.R'
'check_param_names.R' 'col_names_to_var.R'

'compute_doy_cumul.R' 'convert_xml2txt.R'
 'convert_xml2txt_int.R' 'download_data.R' 'download_usm_xl.R'
 'exist_param_xml.R' 'exists_javastics_pref.R' 'exists_param.R'
 'expand_stics_names.R' 'extract.R' 'global.R' 'file_document.R'
 'find_names.R' 'force_param_values.R' 'gen_climate.R'
 'gen_ini_doc.R' 'gen_ini_xml.R' 'gen_new_travail.R' 'gen_obs.R'
 'gen_paramsti.R' 'gen_sol_xsl_file.R' 'gen_sols_xml.R'
 'gen_sta_doc.R' 'gen_sta_xml.R' 'gen_tec_doc.R' 'gen_tec_xml.R'
 'gen_usms_sols_doc.R' 'gen_usms_xml.R' 'gen_usms_xml2txt.R'
 'gen_varmod.R' 'get_climate_txt.R' 'get_file.R'
 'get_file_int.R' 'get_formalisms_xml.R' 'get_java_workspace.R'
 'get_lai_forcing.R' 'get_name_value_file_value.R' 'get_obs.R'
 'get_option_choice_param_values.R' 'get_options_choices.R'
 'get_options_names.R' 'get_param_bounds.R'
 'get_param_bounds_xml.R' 'get_param_desc.R'
 'get_param_formalisms.R' 'get_param_info_xml.R'
 'get_param_names.R' 'get_param_names_xml.R'
 'get_param_number.R' 'get_param_txt.R' 'get_param_type.R'
 'get_param_value.R' 'get_param_xml.R' 'get_params_dict.R'
 'get_params_from_doc.R' 'get_params_from_doc_attr.R'
 'get_params_from_doc_node.R' 'get_params_from_table.R'
 'get_plant_name.R' 'get_plants_nb.R' 'get_report_results.R'
 'get_sim.R' 'get_soils_list.R' 'get_stics_versions_compat.R'
 'get_used_param.R' 'get_usms_files.R' 'get_usms_list.R'
 'get_values_by_param.R' 'get_varmod.R' 'get_xml_base_doc.R'
 'get_xml_base_node.R' 'get_xml_doc_example.R'
 'get_xml_files_param_df.R' 'get_xml_stics_version.R'
 'init_javastics_pref.R' 'is_os_name.R' 'is_stics_doc.R'
 'is_stics_xml.R' 'javastics_cmd_util.R' 'javastics_path.R'
 'manage_stics_versions.R' 'merge_nodesets.R'
 'read_params_table.R' 'remove_node_from_doc.R'
 'remove_parent_from_doc.R' 'replace_string_in_file.R'
 'replace_txt_param_value.R' 'set_codeoptim.R'
 'set_file_executable.R' 'set_java_workspace.R'
 'set_param_txt.R' 'set_param_value.R' 'set_param_xml.R'
 'set_sols_param_xml.R' 'set_usms_param_xml.R' 'static_help.R'
 'stics_environment.R' 'stics_examples_utils.R'
 'upgrade_ini_xml.R' 'upgrade_param_gen_xml.R'
 'upgrade_param_newform_xml.R' 'upgrade_plt_xml.R'
 'upgrade_sols_xml.R' 'upgrade_sta_xml.R' 'upgrade_tec_xml.R'
 'upgrade_usms_xml.R' 'upgrade_workspace_xml.R'
 'var_to_col_names.R' 'xml_document.R' 'xml_files_functions.R'
 'zzz.R'

NeedsCompilation no

Author Patrice Lecharpentier [aut, cre]

(<<https://orcid.org/0000-0002-4044-4322>>),

Remi Vezy [aut] (<<https://orcid.org/0000-0002-0808-1461>>),

Samuel Buis [aut] (<<https://orcid.org/0000-0002-8676-5447>>),

Michel Giner [aut] (<<https://orcid.org/0000-0002-9310-2377>>),
 Thomas Robine [ctb],
 Amine Barkaoui [ctb],
 Patrick Chabrier [ctb],
 Julie Constantin [rev],
 Dominique Ripoche [rev],
 Marie Launay [rev],
 Alain Mollier [rev],
 Christine Le Bas [rev],
 Joel Leonard [rev]

Maintainer Patrice Lecharpentier <patrice.lecharpentier@inrae.fr>

Repository CRAN

Date/Publication 2024-02-23 14:40:02 UTC

R topics documented:

convert_xml2txt	4
download_data	5
download_usm_csv	6
download_usm_xl	7
force_param_values	8
gen_ini_xml	9
gen_obs	10
gen_sols_xml	12
gen_sta_xml	13
gen_tec_xml	15
gen_usms_xml	16
gen_usms_xml2txt	18
gen_varmod	19
get_climate_txt	21
get_examples_path	22
get_lai_forcing	23
get_obs	23
get_param_info	25
get_param_txt	26
get_param_xml	30
get_plants_nb	31
get_report_results	32
get_sim	33
get_soils_list	35
get_stics_versions_compat	36
get_usms_files	36
get_usms_list	38
get_varmod	39
get_var_info	40
is_mac	41
is_stics_param	41

is_stics_var	42
is_unix	43
is_windows	43
read_params_table	44
set_param_txt	45
set_param_xml	48
upgrade_ini_xml	50
upgrade_param_gen_xml	51
upgrade_param_newform_xml	52
upgrade_plt_xml	54
upgrade_sols_xml	55
upgrade_sta_xml	56
upgrade_tec_xml	57
upgrade_usms_xml	58
upgrade_workspace_xml	59
[.cropr_simulation	61

Index	62
--------------	-----------

convert_xml2txt	<i>Transforming a STICS xml file into a text file</i>
-----------------	---

Description

The input file according to his type (ini,plant,tec,station,soil,par) is converted to a text file readable by the STICS model (ficini.txt, ficplt1.txt,...)

Usage

```
convert_xml2txt(
  file,
  plant_id = 1,
  out_dir = NULL,
  save_as = NULL,
  stics_version = "latest",
  xml_file = lifecycle::deprecated(),
  plt_num = lifecycle::deprecated(),
  out_file = lifecycle::deprecated()
)
```

Arguments

file	Path (including name) of the xml file to convert
plant_id	The plant identifier (main crop: 1 ; associated crop: 2)
out_dir	Path of the directory where to generate the file. Optional, set to the path of the input xml file by default
save_as	Name of the output file (optional, default: fixed name for STICS)

stics_version the STICS files version to use (optional, default to latest).
 xml_file **[Deprecated]** xml_file is no longer supported, use file instead.
 plt_num **[Deprecated]** plt_num is no longer supported, use plant_id instead.
 out_file **[Deprecated]** out_file is no longer supported, use save_as instead.

Value

None

Examples

```

## Not run:
xml_path <- "/path/to/corn_plt.xml"
javastics_path <- "/path/to/JavaSTICS/folder"
convert_xml2txt(file = xml_path, javastics = javastics_path)

## End(Not run)

```

download_data	<i>Download example USMs</i>
---------------	------------------------------

Description

Download locally the example data from the [data repository](#) in the SticsRPacks organisation.

Usage

```

download_data(
  out_dir = tempdir(),
  example_dirs = NULL,
  stics_version = "latest",
  dir = lifecycle::deprecated(),
  version_name = lifecycle::deprecated()
)

```

Arguments

out_dir Path of the directory where to download the data
 example_dirs List of use case directories names (optional)
 stics_version Name of the STICS version. Optional, by default the latest version returned by `get_stics_versions_compat()` is used.
 dir **[Deprecated]** dir is no longer supported, use out_dir instead.
 version_name **[Deprecated]** file_path is no longer supported, use file instead.

Value

The path to the folder where data have been downloaded

Examples

```
# Getting data for a given example : study_case_1 and a given STICS version
download_data(example_dirs = "study_case_1", stics_version = "V9.0")
```

download_usm_csv	<i>Downloading a CSV usms data file example into a directory</i>
------------------	--

Description

The file is an example that can be used for generating JavaSTICS usms.xml input file from parameters values stored in a CSV file using the function [gen_usms_xml](#)

Usage

```
download_usm_csv(
  file = NULL,
  out_dir = tempdir(),
  stics_version = "latest",
  overwrite = FALSE,
  verbose = FALSE,
  csv_name = lifecycle::deprecated(),
  version_name = lifecycle::deprecated(),
  dest_dir = lifecycle::deprecated()
)
```

Arguments

file	Name of a csv file (optional, not used for the moment)
out_dir	Directory path where to copy the csv file (default: tempdir())
stics_version	Name of the STICS version. Optional, by default the latest version returned by <code>get_stics_versions_compat()</code> is used.
overwrite	Optional logical, TRUE for overwriting files, FALSE otherwise (default)
verbose	Logical value for displaying information while running
csv_name	[Deprecated] csv_name is no longer supported, use file instead.
version_name	[Deprecated] version_name is no longer supported, use stics_version instead.
dest_dir	[Deprecated] dest_dir is no longer supported, use out_dir instead.

Value

A vector of copied files path.

Examples

```
download_usm_csv()
```

```
download_usm_xl
```

Downloading an Excel usms data file example into a directory

Description

The file is an example that can be used for generating JavaSTICS input files from parameters values stored in Excel spreadsheet format (USMs, Ini, Soils, Tec, Station, ...). Each sheet contains parameters values to insert into XML files, with the help of these functions: [gen_usms_xml](#), [gen_sols_xml](#), [gen_tec_xml](#), [gen_sta_xml](#), [gen_usms_xml](#), [gen_ini_xml](#)

Usage

```
download_usm_xl(
  file = NULL,
  out_dir = tempdir(),
  stics_version = "latest",
  overwrite = FALSE,
  verbose = FALSE,
  xl_name = lifecycle::deprecated(),
  version_name = lifecycle::deprecated(),
  dest_dir = lifecycle::deprecated(),
  ...
)
```

Arguments

file	Name of an Excel file (optional, not used for the moment)
out_dir	Directory path where to copy the Excel file (optional, default: tempdir())
stics_version	Name of the STICS version. Optional, by default the latest version returned by <code>get_stics_versions_compat()</code> is used.
overwrite	Optional logical, TRUE for overwriting files, FALSE otherwise (default)
verbose	Logical value for displaying information while running
xl_name	[Deprecated] xl_name is no longer supported, use file instead.
version_name	[Deprecated] version_name is no longer supported, use stics_version instead.
dest_dir	[Deprecated] dest_dir is no longer supported, use out_dir instead.
...	Additional arguments to be passed

Value

A vector of copied files path.

Examples

```
download_usm_xl()
```

force_param_values	<i>Generates files to force parameters values in STICS simulations</i>
--------------------	--

Description

Generates a param.sti file and sets code optim in new_travail.usm to force parameters values in STICS simulations (this function is typically called before SticsOnR::run_stics())

Usage

```
force_param_values(  
  workspace,  
  values,  
  javastics,  
  param_values = lifecycle::deprecated()  
)
```

Arguments

workspace	Path of the workspace containing the STICS (txt) input files.
values	named vector of parameter values to force. See Details for more information.
javastics	Path of JavaSTICS
param_values	[Deprecated] param_values is no longer supported, use values instead.

Details

This function operates on STICS text input files. Do not use it before calling gen_usms_xml2txt(), otherwise param.sti and new_travail.usm files will be overwritten.

This function has been created to be called before SticsOnR::run_stics(). It can not work with SticsOnR::run_javastics(), that will overwrite param.sti and new_travail.usm files.

values can contain NA. In this case, the corresponding parameter(s) will not be forced (default value(s), i.e. read in STICS input files, will be used). If values==NA or values==NULL, not any parameter will be forced (all default values used).

Value

A logical status TRUE if successful, FALSE otherwise

See Also

SticsOnR::run_stics()

Examples

```
## Not run:
example_txt_dir <- get_examples_path(file_type = "txt")
force_param_values(example_txt_dir,
  setNames(object = c(220, 330), c("stlevamf", "stamflax")),
  javastics = "/path/to/javastics"
)

## End(Not run)
```

gen_ini_xml

Generate STICS ini xml file(s) from a template or an input file

Description

Generate STICS ini xml file(s) from a template or an input file

Usage

```
gen_ini_xml(
  param_df,
  file = NULL,
  out_dir,
  crop_tag = "Crop",
  stics_version = "latest",
  ini_in_file = lifecycle::deprecated(),
  param_table = lifecycle::deprecated(),
  out_path = lifecycle::deprecated()
)
```

Arguments

param_df	A table (df, tibble) containing the values of the parameters to use (see details)
file	Path of an ini xml file to be used as a template. Optional, if not provided, the function will use a standard template depending on the STICS version (see stics_version argument)
out_dir	Path of the directory where to generate the file(s).
crop_tag	identifier for the crop parameters names related to the main crop, or the associated crop if any (example: Crop is used in the param_table example in the details section below)
stics_version	Name of the STICS version. Optional, used if the file argument is not provided. In this case the function uses a standard template associated to the STICS version.
ini_in_file	[Deprecated] ini_in_file is no longer supported, use file instead.
param_table	[Deprecated] param_table is no longer supported, use param_df instead.
out_path	[Deprecated] out_path is no longer supported, use out_dir instead.

Details

Please see `get_stics_versions_compat()` for the full list of STICS versions that can be used for the argument `stics_version`.

`param_df` is a `data.frame` with the following format:

Ini_name	nbplantes	stade0_Crop1	lai0_Crop1	masec0_Crop1
USM_2017_T1_ini.xml	1	snu	0	0
Vill09_ini.xml	1	snu	0	0
Vill10_ini.xml	1	snu	0	0
Vill11_ini.xml	1	snu	0	0
Vill12_ini.xml	1	snu	0	0
Vill13_ini.xml	1	snu	0	0
Vill14_ini.xml	1	snu	0	0
Standard_ini.xml	1	snu	0	0

The first column gives the ini file name (to be generated), all following columns give the parameter value to put in the file, and each line denotes a separate ini file (for e.g. several USMs).

The first column name must contain the keyword `ini` or `Ini` or `INI` as a prefix to be detected (as shown in the table extract above).

If not given (the default, `NULL`), the function returns the template as is.

Value

None

Examples

```
library(readxl)

xl_path <- download_usm_xl(file = "inputs_stics_example.xlsx")

ini_param_df <- read_excel(xl_path, sheet = "Ini")
gen_ini_xml(
  out_dir = tempdir(),
  param_df = ini_param_df[1:2,]
)
```

gen_obs

Generating observation data files from a data.frame

Description

Generating observation data files from a `data.frame`

Usage

```
gen_obs(
  df,
  out_dir,
  usms_list = NULL,
  obs_table = lifecycle::deprecated(),
  out_path = lifecycle::deprecated()
)
```

Arguments

`df` A data frame containing the values of the observations to use (see Details).

`out_dir` Path of the directory where to generate the file(s).

`usms_list` An optional list of usms names to be used for selecting which files to generate from the `obs_table`

`obs_table` **[Deprecated]** `obs_table` is no longer supported, use `df` instead.

`out_path` **[Deprecated]** `out_path` is no longer supported, use `out_dir` instead.

Details

`df` is a data.frame with the following format:

usm_name	ian	mo	jo	jul	densite	lai(n)	masec(n)	azomes
USM_2017_T1_CI	2017	9	6	249	NA	NA	0.31	27.07395
USM_2017_T1_CI	2017	9	20	263	NA	NA	0.60	27.90000
USM_2018_T1	2017	10	20	293	NA	0.1	NA	NA
USM_2018_T1	2018	5	15	482	NA	1.2	NA	NA

- `usm_name` column contains usms names which are used as output .obs files names
- `ian`, `mo`, `jo` and `jul` are mandatory (year, month, day and julian date)
- Other columns one per variable contain observations values or NA

@seealso [get_var_info](#) for getting variable right syntax or searching a variable name.

Value

A return logical status indicating if any error when writing files (FALSE), TRUE when no errors.

Examples

```
x1_path <- download_usm_xl(file = "inputs_stics_example.xlsx")
obs_df <- read_params_table(file = x1_path, sheet_name = "Obs")
gen_obs(df = obs_df, out_dir = "/path/to/dest/dir")
```

gen_sols_xml *Generate STICS sols xml file from a template or an input file*

Description

Generate STICS sols xml file from a template or an input file

Usage

```
gen_sols_xml(
  file,
  param_df,
  template = NULL,
  stics_version = "latest",
  sols_in_file = lifecycle::deprecated(),
  sols_param = lifecycle::deprecated(),
  sols_out_file = lifecycle::deprecated(),
  sols_nb = lifecycle::deprecated()
)
```

Arguments

file	Path (including name) of the sols file to generate.
param_df	A table (df, tibble) containing the values of the parameters to use (see details)
template	Path of a soil xml file to be used as a template. Optional, if not provided, the function will use a standard template depending on the STICS version.
stics_version	Name of the STICS version. Optional, used if the file argument is not provided. In this case the function uses a standard template associated to the STICS version.
sols_in_file	[Deprecated] sols_in_file is no longer supported, use template instead.
sols_param	[Deprecated] sols_param is no longer supported, use param_df instead.
sols_out_file	[Deprecated] sols_out_file is no longer supported, use file instead.
sols_nb	[Deprecated] sols_nb is no longer supported, it is now computed in the function.

Details

Please see `get_stics_versions_compat()` for the full list of STICS versions that can be used for the argument `stics_version`.

`param_df` is a `data.frame` with the following format:

Soil_name	argi	norg	calc	pH	albedo	q0	epc_1
USM_T1	20.35000	0.100	0.52	8.23	0.22	9.630	30
LF1	17.00000	1.900	0.00	6.70	0.22	9.360	30
LF2	17.00000	1.800	0.00	6.70	0.22	9.360	30

LAP	22.00000	2.000	0.00	6.50	0.22	9.760	25
LAS	24.05000	2.500	30.00	8.00	0.22	9.928	30
LA0	30.00675	2.300	0.50	7.50	0.22	10.400	30
LC0	22.38750	2.000	10.00	7.90	0.22	9.792	25
Vill09	25.00000	0.101	0.40	7.90	0.22	10.000	30
Vill10	14.30000	0.099	1.50	8.20	0.22	9.144	30
Vill11	11.80000	0.100	0.00	7.30	0.22	8.944	30
Vill12	14.30000	0.091	0.60	8.30	0.22	9.144	30
Vill13	16.80000	0.088	0.20	7.80	0.22	9.344	30
Vill14	15.10000	0.095	1.30	7.90	0.22	9.208	30

The first column gives the soil name, all following columns give the parameter values to put in the sols.xml file for each soil row.

The first column name must contain the keyword Soil or soil or SOIL as a prefix to be detected (as shown in the table extract above).

If not given (the default, NULL), the function returns the template as is.

Value

None

Examples

```
xl_path <- download_usm_xl(file = "inputs_stics_example.xlsx")

sols_param_df <- read_params_table(file = xl_path, sheet_name = "Soils")
gen_sols_xml(file = file.path(tempdir(), "sols.xml"),
param_df = sols_param_df)
```

gen_sta_xml

Generate STICS sta xml file(s) from a template or an input file

Description

Generate STICS sta xml file(s) from a template or an input file

Usage

```
gen_sta_xml(
  param_df,
  file = NULL,
  out_dir,
  stics_version = "latest",
  param_table = lifecycle::deprecated(),
```

```

  sta_in_file = lifecycle::deprecated(),
  out_path = lifecycle::deprecated()
)

```

Arguments

param_df	A table (df, tibble) containing the values of the parameters to use (see details)
file	Path of a sta xml file to be used as a template. Optional, if not provided, the function will use a standard template depending on the STICS version.
out_dir	Path of the directory where to generate the file(s).
stics_version	Name of the STICS version. Optional, used if the file argument is not provided. In this case the function uses a standard template associated to the STICS version.
param_table	[Deprecated] param_table is no longer supported, use param_df instead.
sta_in_file	[Deprecated] sta_in_file is no longer supported, use file instead.
out_path	[Deprecated] out_path is no longer supported, use out_dir instead.

Details

Please see `get_stics_versions_compat()` for the full list of STICS versions that can be used for the argument `stics_version`.

`param_df` is a data.frame with the following format:

Sta_name	zr	NH3ref	latitude	patm	aclim
climatex_sta.xml	2.5	0	49	1000	20
climatex2_sta.xml	2.8	0	49	1000	20
climatex3_sta.xml	2.2	0	49	1000	20

The first column gives the sta file name (to be generated), all following columns give the parameter value to put in the file, and each line denotes a separate sta file (for e.g. several USMs).

The first column name must contain the keyword `sta` or `Sta` or `STA` as a prefix to be detected (as shown in the table extract above).

If not given (the default, `NULL`), the function returns the template as is.

Value

None

Examples

```

xl_path <- download_usm_xl(file = "inputs_stics_example.xlsx")
sta_param_df <- read_params_table(file = xl_path, sheet_name = "Station")
gen_sta_xml(out_dir = tempdir(), param_df = sta_param_df)

```

gen_tec_xml	<i>Generate STICS tec xml file(s) from a template or an input file</i>
-------------	--

Description

Generate STICS tec xml file(s) from a template or an input file

Usage

```
gen_tec_xml(
  param_df = NULL,
  file = NULL,
  out_dir,
  stics_version = "latest",
  na_values = NA,
  param_table = lifecycle::deprecated(),
  tec_in_file = lifecycle::deprecated(),
  out_path = lifecycle::deprecated()
)
```

Arguments

param_df	A table (df, tibble) containing the values of the parameters to use (see details)
file	Path of a tec xml file to be used as a template. Optional, if not provided, the function will use a standard template depending on the STICS version.
out_dir	Path of the directory where to generate the file(s).
stics_version	Name of the STICS version. Optional, used if the file argument is not provided. In this case the function uses a standard template associated to the STICS version.
na_values	value to use as missing value in param_table (optional, default : NA)
param_table	[Deprecated] param_table is no longer supported, use param_df instead.
tec_in_file	[Deprecated] tec_in_file is no longer supported, use file instead.
out_path	[Deprecated] out_path is no longer supported, use out_dir instead.

Details

Please see `get_stics_versions_compat()` for the full list of STICS versions that can be used for the argument `stics_version`.

`param_df` is a `data.frame` with the following format:

Tec_name	julres_1	coderes_1
USM_2017_T1_CI_tec.xml	NA	1
BIN_CANPC_05_SEC_220-0-0_34K_CANPC05T3_Q_tec.xml	110	1
BIN_AGT_04_IRR_220-0-0_33K_AGT04T2_Q_tec.xml	73	1
AGA_ARB_13_IRR_220-0-0_37K_ARB13_C_tec.xml	82	1

AGA_ARB_13_SEC_220-0-0_37K_ARB13_C_tec.xml	82	1
FRA_ARB_11_SEC_220-0-0_38K_E_tec.xml	70	1
MAG_ARB_09_SEC_220-0-0_38K_E_tec.xml	81	1
MAG_ARV_12_IRR_220-0-0_36K_ARV12_C_tec.xml	100	1
MAG_ARV_12_SEC_220-0-0_36K_ARV12_C_tec.xml	100	1
FRA_ARB_12_SEC_220-0-0_31K_ARB12_C_tec.xml	92	1
FRA_ARB_13_SEC_220-0-0_37K_ARB13_C_tec.xml	82	1

The first column gives the tec file name (to be generated), all following columns give the parameter value to put in the file, and each line denotes a separate tec file (for e.g. several USMs).

The first column name must contain the keyword tec or Tec or TEC as a prefix to be detected (as shown in the table extract above).

If not given (the default, NULL), the function returns the template as is.

Value

None

Examples

```
x1_path <- download_usm_xl(file = "inputs_stics_example.xlsx")
tec_param_df <- read_params_table(file = x1_path, sheet_name = "Tec")
gen_tec_xml(out_dir = tempdir(), param_df = tec_param_df[1:2, ])
```

gen_usms_xml

Generate STICS usms xml file from a template or an input file

Description

Generate STICS usms xml file from a template or an input file

Usage

```
gen_usms_xml(
  file,
  param_df = NULL,
  template = NULL,
  stics_version = "latest",
  usms_out_file = lifecycle::deprecated(),
  usms_nb = lifecycle::deprecated(),
  usms_param = lifecycle::deprecated(),
  usms_in_file = lifecycle::deprecated()
)
```


Arguments

file	Path (including name) of the usms file to generate.
param_df	A table (df, tibble) containing the values of the parameters to use (see details)
template	Path of an USM xml file to be used as a template. Optional, if not provided, the function will use a standard template depending on the STICS version.
stics_version	Name of the STICS version. Optional, used if the file argument is not provided. In this case the function uses a standard template associated to the STICS version.
usms_out_file	[Deprecated] usms_out_file is no longer supported, use file instead.
usms_nb	[Deprecated] usms_nb is no longer supported, use NA instead.
usms_param	[Deprecated] usms_param is no longer supported, use param_df instead.
usms_in_file	[Deprecated] usms_in_file is no longer supported, use template instead.

Details

Please see `get_stics_versions_compat()` for the full list of STICS versions that can be used for the argument `stics_version`.

`param_df` is a `data.frame` with the following format:

usm_name	datedebut	datefin	nomsol
USM_2017_T1_CI	199	263	USM_T1
USM_2018_T1	264	570	USM_T1
BIN_CANPC_05_SEC_220-0-0_34K_CANPC05T3_Q	199	263	LF1
BIN_AGT_04_IRR_220-0-0_33K_AGT04T2_Q	264	570	LF1
AGA_ARB_13_IRR_220-0-0_37K_ARB13_C	199	263	F1
AGA_ARB_13_SEC_220-0-0_37K_ARB13_C	264	570	LF1
FRA_ARB_11_SEC_220-0-0_38K_E	199	263	LF1
MAG_ARB_09_SEC_220-0-0_38K_E	264	570	LF1
MAG_ARV_12_IRR_220-0-0_36K_ARV12_C	199	263	LF1
MAG_ARV_12_SEC_220-0-0_36K_ARV12_C	264	570	LF1
FRA_ARB_12_SEC_220-0-0_31K_ARB12_C	199	263	LF1
FRA_ARB_13_SEC_220-0-0_37K_ARB13_C	264	570	LF1

The first column gives the usm name, all following columns give the parameter values to put in the `usms.xml` file for each usm row.

The first column name must contain the keyword `Usm` or `usm` or `USM` as a prefix to be detected (as shown in the table extract above).

If not given (the default, `NULL`), the function returns the template as is.

Value

an invisible `xml_document` object

Examples

```
xl_path <- download_usm_xl(file = "inputs_stics_example.xlsx")
usms_param_df <- read_params_table(file = xl_path, sheet_name = "USMs")
gen_usms_xml(file = file.path(tempdir(), "usms.xml"),
  param_df = usms_param_df)
```

gen_usms_xml2txt	<i>Generating one or several usms directories from a javastics workspace content</i>
------------------	--

Description

The function creates sets of input files for one or multiple usms from usms data stored in a JavaSTICS workspace. For multiple usms, sets will be generated into individual folders named with usm names. Observations files will be also copied if they are named [usm_name].obs For one usm, files will be generated either in the workspace directory or in a subdirectory.

Usage

```
gen_usms_xml2txt(
  javastics = NULL,
  workspace = NULL,
  out_dir = NULL,
  usm = c(),
  stics_version = "latest",
  verbose = TRUE,
  dir_per_usm_flag = TRUE,
  java_cmd = "java",
  java_converter = FALSE,
  javastics_path = lifecycle::deprecated(),
  workspace_path = lifecycle::deprecated(),
  target_path = lifecycle::deprecated(),
  usms_list = lifecycle::deprecated()
)
```

Arguments

javastics	Path of JavaSTICS. Optional (needed if the JavaSTICS converter is used, java_converter set to TRUE in inputs)
workspace	Path of a JavaSTICS workspace (i.e. containing the STICS XML input files). Optional, if not provided the current workspace stored in JavaSTICS preferences will be used.
out_dir	The path of the directory where to create usms directories (Optional), if not provided the JavaSTICS workspace will be used as root
usm	List of usms to generate (Optional). If not provided, all usms contained in workspace/usms.xml file will be generated.

stics_version	the STICS files version to use (optional, default to latest).
verbose	Logical value for displaying information while running
dir_per_usm_flag	logical, TRUE if one want to create one directory per USM, FALSE if USM files are generated in the target_path (only useful for usms_list of size one)
java_cmd	For unix like systems, the java virtual machine command name or executable path. Usefull only if the JavaSTICS command line is used for generating files. "java" is the default system command, but a full path to a java executable (other than the default one) may be given
java_converter	logical TRUE for using JavaStics command (a JavaSTICS path must be set in the function inputs), FALSE otherwise
javastics_path	[Deprecated] javastics_path is no longer supported, use javastics instead.
workspace_path	[Deprecated] workspace_path is no longer supported, use workspace instead.
target_path	[Deprecated] target_path is no longer supported, use out_dir instead.
usms_list	[Deprecated] usms_list is no longer supported, use usm instead.

Value

A list with named elements: usms_path : created directories paths (for storing STICS input files), files : generated files list (in JavaSTICS workspace origin), copy_status : logical value vector, indicating if all files have been generated for each usm obs_copy_status : logical value vector, indicating if observation files have been successfully copied in usms directories

Examples

```
## Not run:
javastics <- "/path/to/JavaSTICS/folder"
workspace <- "/path/to/workspace"

# For all usms
gen_usms_xml2txt(javastics, workspace)

# For an usms list
usm <- c("usm1", "usm2")
gen_usms_xml2txt(javastics, workspace, usm)

## End(Not run)
```

gen_varmod

Generating a var.mod type file

Description

Generating a daily variable list file from variables names

Usage

```
gen_varmod(
  workspace,
  var,
  append = FALSE,
  file_name = "var.mod",
  stics_version = "latest",
  force = FALSE,
  var_names = lifecycle::deprecated(),
  version = lifecycle::deprecated()
)
```

Arguments

workspace	Path of the directory containing the STICS var.mod file to modify
var	vector of variables names (see details)
append	if TRUE, var data are appended to file_name
file_name	file name to generate (without path, default value: "var.mod")
stics_version	Name of the STICS version (used to check variable names)
force	Force variables writing even if they are not a STICS variable (default: FALSE).
var_names	[Deprecated] var_names is no longer supported, use var instead.
version	[Deprecated] version is no longer supported, use stics_version instead.

Details

Variable names can be found using `get_var_info()`. They are checked before writing. If any variable name does not exist, it will not be written by default, but the function will still write the variables that exist. `force= TRUE` may however be used to write variables that do not exist.

Value

None

Examples

```
gen_varmod(tempdir(), c("lai(n)", "hauteur"))
# Add a variable to the others:
gen_varmod(tempdir(), "masec(n)", append = TRUE)
# NB: var.mod will have "lai(n)", "hauteur" and "masec(n)"
```

get_climate_txt	<i>Read STICS input meteorology file</i>
-----------------	--

Description

Read the meteorology input for STICS ("climat.txt")

Usage

```
get_climate_txt(  
  workspace,  
  file_name = "climat.txt",  
  preserve = TRUE,  
  dirpath = lifecycle::deprecated(),  
  filename = lifecycle::deprecated()  
)
```

Arguments

workspace	Path of the workspace containing the STICS climate file to read
file_name	The meteorology file name (default to climat.txt).
preserve	Logical, TRUE`` for keeping the STICS columns related to date calculation (year, month, da
dirpath	[Deprecated] dirpath is no longer supported, use workspace instead.
filename	[Deprecated] filename is no longer supported, use file_name instead.

Value

A data.frame of the input meteorological variables used as input for the STICS model.

Note

The time-related variables are summarised into one POSIXct column named date.

Examples

```
path <- get_examples_path(file_type = "txt")  
Meteo <- get_climate_txt(path)
```

get_examples_path	<i>Getting examples files path attached to a STICS version for a given file type</i>
-------------------	--

Description

Getting examples files path attached to a STICS version for a given file type

Usage

```
get_examples_path(
  file_type,
  stics_version = "latest",
  overwrite = FALSE,
  version_name = lifecycle::deprecated()
)
```

Arguments

file_type	A file type string among files types or a vector of ("csv", "obs", "sti", "txt", "xml")
stics_version	Name of the STICS version. Optional, by default the latest version returned by get_stics_versions_compat() is used.
overwrite	TRUE for overwriting directory; FALSE otherwise
version_name	[Deprecated] version_name is no longer supported, use stics_version instead.

Value

A directory path for examples files for given file type and STICS version or a vector of (for unknown file types "" is returned as path)

Examples

```
get_examples_path(file_type = "csv")

get_examples_path(file_type = c("csv", "sti"))

get_examples_path(file_type = "csv", stics_version = "V8.5")
```

get_lai_forcing	<i>Getting LAI forcing for each usm</i>
-----------------	---

Description

Is LAI forced for usms in usms.xml

Usage

```
get_lai_forcing(usm_file_path, usms_list = c())
```

Arguments

usm_file_path Path to usms.xml file
usms_list Usm(s) name(s) (optional, see details)

Details

Use get_usms_list() to get the list of the usm names for an usms.xml file.

Value

A named numeric vector with a Boolean value (TRUE = forced) for each usm

Examples

```
# Xml case  
xml_usms <- file.path(get_examples_path(file_type = "xml"), "usms.xml")  
get_lai_forcing(xml_usms)  
get_lai_forcing(xml_usms, "wheat")  
get_lai_forcing(xml_usms, c("wheat", "intercrop_pea_barley"))
```

get_obs	<i>Read STICS observation files (*.obs)</i>
---------	---

Description

Read STICS observation files from a JavaSTICS workspace and store data into a list per usm

Usage

```

get_obs(
  workspace,
  usm = NULL,
  var = NULL,
  dates = NULL,
  usms_file = NULL,
  javastics = NULL,
  verbose = TRUE,
  usm_name = lifecycle::deprecated(),
  var_list = lifecycle::deprecated(),
  dates_list = lifecycle::deprecated(),
  usms_filepath = lifecycle::deprecated(),
  javastics_path = lifecycle::deprecated()
)

```

Arguments

workspace	Vector of path(s) of directory(ies) containing the STICS observation files to read (*.obs file) or path of a single directory containing one sub-folder per USM (named as the USM names), each of them containing the corresponding files to read. In the second case, the argument usm must also be provided.
usm	Vector of USM names. Optional, if not provided, the function returns the results for all USMs.
var	Vector of variable names for which results have to be provided. Optional, all variables considered by default. See get_var_info() to get the list of STICS variables names.
dates	list of dates to filter (POSIX date)
usms_file	Path of a USM xml file. Optional, if provided, the plant names are added in the Plant column (see details).
javastics	Path of JavaSTICS. Optional, should be provided in addition to usms_file to get the plant codes if the plant files used are not in the workspace but in the JavaSTICS distribution (see Details).
verbose	Logical value for displaying or not information while running
usm_name	[Deprecated] usm_name is no longer supported, use usm instead.
var_list	[Deprecated] var_list is no longer supported, use var instead.
dates_list	[Deprecated] dates_list is no longer supported, use dates instead.
usms_filepath	[Deprecated] usms_filepath is no longer supported, use usms_file instead.
javastics_path	[Deprecated] javastics_path is no longer supported, use javastics instead.

Details

The .obs files names must match USMs names, *e.g.* for a usm called "banana", the .obs file should be named banana.obs. For intercrops, the name should be suffixed by "p" for the principal and "a" for the associated plant.

If usm is not specified (or equal to NULL), the function reads the files from all usms in the workspace(s).

If usms_file is provided and if the associated plant file is found, the plant names in the "Plant" column of the generated data.frame are either the plant code (as specified in the plant file) or the name of the plant file, if the plant file is not found.

If usms_file is not specified, the plants are named "plant_1" by default (+ "plant_2" for intercroops).

Value

A list, where each element is a data.frame of observations for the given usm. The list is named after the USM name.

Intercrops are returned in a single data.frame, and are identified using either the "Plant" or "Dominance" columns.

See Details section for more information about the "Plant" column.

Examples

```
path <- file.path(get_examples_path(file_type = "obs"), "mixed")

# Get observations for all usms, but only banana has observations:
Meas <- get_obs(path)

# Get observations only for banana:
Meas_banana <- get_obs(path, "banana")

## Not run:
# Get observations with real plant names when plant
# folder is not in the workspace:
get_obs(path, "banana", javastics = "/path/to/JavaSTICS/folder")

## End(Not run)
```

get_param_info

Finding parameters information using partial search words

Description

Helper function that returns names and descriptions of STICS input parameters from a partial name and/or descriptive keywords.

Usage

```
get_param_info(param = NULL, keyword = NULL, stics_version = "latest")
```

Arguments

param	Vector of parameter names (or partial names). Optional, if not provided, the function returns information for all parameters
keyword	Optional, strings or a vector of to be used for searching in parameters names and definition
stics_version	Name of the STICS version. Optional, can be used to search parameters information relative to a specific STICS version. By default the latest version returned by get_stics_versions_compat() is used.

Details

The function understand [regex](#) as input.

Value

A data.frame with information about parameter(s) with columns name,file,min,max, definition

Examples

```
# Find by parameter name (fuzzy search):
SticsRFiles::get_param_info("alb")
SticsRFiles::get_param_info("alb[e]?")

# Find by keyword (fuzzy search in parameter name and description):
SticsRFiles::get_param_info(keyword = "bdil")

# Find for a particular version:
SticsRFiles::get_param_info("alb", stics_version = "V9.0")
```

get_param_txt

Read STICS input parameters from text files

Description

Read STICS model input parameters from a usm in text format (STICS input) Generally used after calling building a usm with JavaSTICS.

Read a specific STICS model input parameter file. Users would generally use the wrapper get_param_txt() instead.

Usage

```
get_param_txt(  
  workspace,  
  param = NULL,  
  variety = NULL,  
  exact = FALSE,  
  stics_version = "latest",  
  dirpath = lifecycle::deprecated(),  
  ...  
)  
  
get_ini_txt(  
  file = "ficini.txt",  
  stics_version,  
  filepath = lifecycle::deprecated()  
)  
  
get_general_txt(file = "tempopar.sti", filepath = lifecycle::deprecated())  
  
get_tmp_txt(file = "tempoparv6.sti", filepath = lifecycle::deprecated())  
  
get_plant_txt(  
  file = "ficplt1.txt",  
  variety = NULL,  
  filepath = lifecycle::deprecated()  
)  
  
get_tec_txt(  
  file = "fictec1.txt",  
  stics_version = "latest",  
  several_fert = NULL,  
  several_thin = NULL,  
  is_pasture = NULL,  
  filepath = lifecycle::deprecated(),  
  ...  
)  
  
get_soil_txt(  
  file = "param.sol",  
  stics_version,  
  filepath = lifecycle::deprecated()  
)  
  
get_station_txt(file = "station.txt", filepath = lifecycle::deprecated())  
  
get_usm_txt(file = "new_travail.usm", filepath = lifecycle::deprecated())
```

Arguments

workspace	Path of the workspace containing the STICS (txt) input files.
param	Vector of parameter names. Optional, if not provided, the function returns an object with all parameters.
variety	Integer. The plant variety to get the parameter from.
exact	Boolean indicating if the function must return results only for exact match.
stics_version	An optional version name as listed in get_stics_versions_compat() return
dirpath	[Deprecated] dirpath is no longer supported, use workspace instead.
...	Further arguments to pass (for future-proofing only)
file	File path
filepath	[Deprecated] filepath is no longer supported, use file instead.
several_fert	Is there several fertilization in the USM ? See details.
several_thin	Is there several thinning in the USM ? See details.
is_pasture	Is the plant a pasture ? See details.

Details

If the variety is not given and a param is asked, the function will return the values for the variety that is simulated in the USM by checking the variete parameter in the technical file. If param is not provided by the user, the values from all varieties will be returned unless the user ask for a given variety.

several_fert, several_thin and is_pasture are read from the tmp file (tempoparv6.sti). get_param_txt() does it automatically. If you absolutely need to use directly get_tec_txt, please see example.

Value

A list of parameters value(s), or if param = NULL a list of all parameters:

ini	Initialization parameters
general	General parameters
tec	Technical parameters
plant	Plant parameters
soil	Soil parameters
station	Station parameters

A list of parameters, depending on the file/function:

ini	Initialization parameters
general	General parameters
tec	Technical parameters
plant	Plant parameters
soil	Soil parameters
station	Station parameters
tmp	Temporary parameters

Note

Users would generally use `get_param_txt` to identify parameters names and values and pass them to other functions.

The functions are compatible with intercrops. Users generally only use `get_param_txt()`, which is a wrapper for all these functions.

See Also

`gen_varmod()`,
`get_param_txt()`.

Examples

```
path <- get_examples_path(file_type = "txt")

# Getting the interrow distance parameter value
get_param_txt(path, param = "interrang")

# Getting varietal parameters values
# Get the leaf lifespan of the variety used in the usm:
get_param_txt(workspace = path, param = "durvieF")
# Get the leaf lifespan of another variety available in the plant file:
get_param_txt(workspace = path, param = "durvieF", variety = "Furio")
# To get the values for several (or all) varieties, either put all varieties:
varieties <- c("Pactol", "Cherif", "Furio", "Dunia", "Volga", "Cecilia")
get_param_txt(workspace = path, param = "durvieF", variety = varieties)
# Or get it from the output of the function returning all parameters:
get_param_txt(workspace = path)$plant$plant1$durvieF

## Not run:
# Read the initialisation file (ficini.txt):
library(SticsRFiles)
path <- file.path(get_examples_path(file_type = "txt"), "ficini.txt")
get_ini_txt(path)

# Read the tec file directly:

# First, get the parameters from the tmp file:
tmp <- get_tmp_txt(file = file.path(get_examples_path(file_type = "txt"),
                                   "tempoparv6.sti"))
several_fert <- ifelse(tmp$option_engrais_multiple == 1, TRUE, FALSE)
several_thin <- ifelse(tmp$option_thinning == 1, TRUE, FALSE)
is_pasture <- ifelse(tmp$option_pature == 1, TRUE, FALSE)

# Then, get the technical parameters:
get_tec_txt(
  file = file.path(get_examples_path(file_type = "txt"), "fictec1.txt"),
  several_fert = several_fert, several_thin = several_thin,
  is_pasture = is_pasture
)
```

```
## End(Not run)
```

```
get_param_xml          Getting parameter values from xml files
```

Description

Extracting parameter values for a list of xml files and parameters

Usage

```
get_param_xml(
  file,
  param = NULL,
  select = NULL,
  select_value = NULL,
  xml_file = lifecycle::deprecated(),
  param_name = lifecycle::deprecated(),
  value = lifecycle::deprecated(),
  ...
)
```

Arguments

file	Vector of the xml file paths from which parameters values must be extracted
param	Vector of parameter names. Optional, if not provided, the function returns information for all parameters.
select	node name or attribute name to use for selection (optional, default to no selection)
select_value	Vector of values used for select (see examples). Optional, should be provided only if select is provided.
xml_file	[Deprecated] xml_file is no longer supported, use file instead.
param_name	[Deprecated] param_name is no longer supported, use param instead.
value	[Deprecated] value is no longer supported, use select_value instead.
...	Pass further arguments to get_param_value()

Value

A list of parameter values for each xml_file (a list of list)

Examples

```

# Soil file
file <- file.path(get_examples_path(file_type = "xml"), "sols.xml")

# For all soils
get_param_xml(file)
get_param_xml(file, c("argi", "norg"))

# With soil selection
# scalar parameters per soil
get_param_xml(file, c("argi", "norg"),
  select = "sol", select_value = c("solcanne", "solbanane")
)

# Crop management file
file <- file.path(get_examples_path(file_type = "xml"), "file_tec.xml")

# Getting parameters for irrigation (date and quantity)
get_param_xml(file, c("julapI_or_sum_upvt", "amount"))

```

get_plants_nb	<i>Getting plants number per usm for all usms or selected from a usm name vector</i>
---------------	--

Description

Extracting plant number from usms.xml or new_travail.usm file data

Usage

```

get_plants_nb(
  usms_file,
  usms_list = c(),
  usm_file_path = lifecycle::deprecated()
)

```

Arguments

usms_file Path (including name) of a USM xml file or of a new_travail.usm file

usms_list Usm(s) name(s) (optional, see details)

usm_file_path **[Deprecated]** usm_file_path is no longer supported, use usms_file instead.

Details

Use get_usms_list() to get the list of the usm names for an usms.xml file.

Value

A named numeric vector of plants number per usm

Examples

```
# Xml case
xml_usms <- file.path(get_examples_path(file_type = "xml"), "usms.xml")
get_plants_nb(xml_usms)
get_plants_nb(xml_usms, "wheat")
get_plants_nb(xml_usms, c("wheat", "intercrop_pea_barley"))

# Txt case
txt_usm <- file.path(get_examples_path(file_type = "txt"), "new_travail.usm")
get_plants_nb(txt_usm)
```

get_report_results *Extracting data from the STICS report file*

Description

Extracting data from the STICS report file

Usage

```
get_report_results(
  workspace,
  file_name = "mod_rapport.sti",
  usm = NULL,
  var_list = NULL,
  usm_name = lifecycle::deprecated()
)
```

Arguments

workspace	Path of the directory containing the STICS report file to read.
file_name	A report file name among "mod_rapport.sti" (default), "mod_rapportA.sti", "mod_rapportP.sti"
usm	Vector of USM names. Optional, if not provided, the function returns the results for all USMs.
var_list	vector of output variables names to filter (optional, see get_var_info() to get the names of the variables)
usm_name	[Deprecated] usm_name is no longer supported, use usm instead.

Details

The data may be filtered using usm_name vector of usm names and and/or var_list vector of variables names. In the returned data.frame, variables names respect the same syntax as in the get_sim output.

Value

A data.frame

Examples

```
path <- get_examples_path(file_type = "sti")
get_report_results(workspace = path)

get_report_results(workspace = path, usm = c("DurumWheat", "grass"))

get_report_results(workspace = path, var_list = c("masec(n)", "QNplante"))

get_report_results(workspace = path, usm = c("DurumWheat", "grass"))

get_report_results(workspace = path)

get_report_results(workspace = path, file_name = "mod_rapportA.sti")
```

get_sim

Load and format STICS daily output file(s)

Description

Reads and format daily output file(s) (mod_s*.sti) for usm(s) with possible selection on variable names, cumulative DOY and dates

Usage

```
get_sim(
  workspace,
  usm = NULL,
  var = NULL,
  dates = NULL,
  usms_file = NULL,
  javastics = NULL,
  verbose = TRUE,
  usm_name = lifecycle::deprecated(),
  var_list = lifecycle::deprecated(),
  dates_list = lifecycle::deprecated(),
  usms_filepath = lifecycle::deprecated(),
  javastics_path = lifecycle::deprecated()
)
```

Arguments

workspace	Vector of path(s) of directory(ies) containing the STICS output files to read (mod_s*.sti file) or path of a single directory containing one sub-folder per USM (named as the USM names), each of them containing the corresponding STICS output file to read. In the second case, the argument usm must also be provided.
usm	Vector of USM names. Optional, if not provided, the function returns the results for all USMs.
var	Vector of variable names for which results have to be provided. Optional, all variables considered by default. See get_var_info() to get the list of STICS variables names.
dates	list of dates to filter (POSIX date)
usms_file	Path of a USM xml file. Optional, if provided, the plant names are added in the Plant column (see details).
javastics	Path of JavaSTICS Optional, should be provided in addition to usms_file to get the plant codes if the plant files used are not in the workspace but in the JavaSTICS distribution (see Details).
verbose	Logical value for displaying or not information while running
usm_name	[Deprecated] usm_name is no longer supported, use usm instead.
var_list	[Deprecated] var_list is no longer supported, use var instead.
dates_list	[Deprecated] dates_list is no longer supported, use dates instead.
usms_filepath	[Deprecated] usms_filepath is no longer supported, use usms_file instead.
javastics_path	[Deprecated] javastics_path is no longer supported, use javastics instead.

Details

If usm is not specified (or equal to NULL), the function reads the files from all usms in the workspace(s).

If usms_file is provided and if the associated plant file is found, the plant names in the "Plant" column of the generated data.frame are either the plant code (as specified in the plant file) or the name of the plant file, if the plant file is not found.

If usms_file is not specified, the plants are named "plant_1" by default (+ "plant_2" for intercrops).

Value

A list, where each element is a data.frame of simulation results for the given usm. The list is named after the USM name.

Intercrops are returned in a single data.frame, and are identified using either the "Plant" or "Dominance" columns.

See Details section for more information about the "Plant" column.

Examples

```
path <- get_examples_path(file_type = "sti")
sim_data <- get_sim(path, "banana")
```

get_soils_list	<i>Get the soil names for an usms.xml file</i>
----------------	--

Description

Extracts the soil names from a "usms.xml" file, or from a soil file

Usage

```
get_soils_list(  
  file,  
  soil = NULL,  
  file_path = lifecycle::deprecated(),  
  name = lifecycle::deprecated()  
)
```

Arguments

file	Either the path of an usm file or of a soil file.
soil	Vector of soil names (or partial names). Optional, if not provided, the function returns the names of all the soils included in the given file.
file_path	[Deprecated] file_path is no longer supported, use file instead.
name	[Deprecated] name is no longer supported, use soil instead.

Details

The file given as the file_path is either a "usms" file type to get all the soils used in a particular USM, or a soil file type ("sols") to get all soil types available in a soil file.

Value

A vector of soil names

Examples

```
path <- get_examples_path(file_type = "xml")  
  
# Read from a usms file (soils used in a USM):  
soil_list <- get_soils_list(file = file.path(path, "usms.xml"))  
  
# Read from a soil file (all soil types available in a soil file)  
soil_list <- get_soils_list(file = file.path(path, "sols.xml"))  
  
soil_list <- get_soils_list(file = file.path(path, "usms.xml"),  
  soil = c("solcanne", "sole"))
```

`get_stics_versions_compat`*Get the compatible STICS versions*

Description

Get the versions of STICS that are fully compatible with this package.

Usage

```
get_stics_versions_compat(version_index = NULL)
```

Arguments

`version_index` Absolute positive index, or negative relative index from latest version

Value

A named list with the STICS versions compatible with this package (`$versions_list`), and the latest version in use (`$latest_version`) or an existing version selected using `version_index`.

Examples

```
# Getting the complete versions list
get_stics_versions_compat()

# Getting the first version
get_stics_versions_compat(1)

# Getting the previous version of the latest one
get_stics_versions_compat(-1)
```

`get_usms_files`*Getting existing xml files path list per usm from an usms.xml file*

Description

Getting existing xml files path list per usm from an usms.xml file

Usage

```

get_usms_files(
  workspace,
  usms_list = NULL,
  usms_file = "usms.xml",
  file_type = NULL,
  javastics = NULL,
  df_output = FALSE,
  workspace_path = lifecycle::deprecated(),
  file_name = lifecycle::deprecated(),
  javastics_path = lifecycle::deprecated()
)

```

Arguments

workspace	Path of a JavaSTICS workspace (i.e. containing the STICS XML input files)
usms_list	Vector of usms names (Optional)
usms_file	Path (including name) of a USM XML file.
file_type	Vector of file(s) type to get (if not given, all types are returned, see details)
javastics	Path of JavaSTICS Optional, only needed if the plant files are not in the workspace (in this case the plant files used are those included in the JavaSTICS distribution)
df_output	logical if TRUE returning a data.frame, otherwise returning a named list if FALSE (default)
workspace_path	[Deprecated] workspace_path is no longer supported, use workspace instead.
file_name	[Deprecated] file_name is no longer supported, use usms_file instead.
javastics_path	[Deprecated] javastics_path is no longer supported, use javastics instead.

Details

The possible values for file_type are: "fplt", "finit", "fclim1", "fclim2", "fstation", "ftec", "sols", "pargen" and "parnew"

Value

A named list with existing files path in each usm element

See Also

See get_soils_list() to get all soils in a usm file, and get_usms_list() to get the list of usms.

Examples

```

## Not run:

get_usms_files(
  workspace = "/path/to/workspace",
  javastics = "/path/to/JavaSTICS/folder"
)

```

```

)

get_usms_files(
  workspace = "/path/to/workspace",
  javastics = "/path/to/JavaSTICS/folder",
  usm_list = c("usm1", "usm3")
)

get_usms_files(
  workspace = "/path/to/workspace",
  file_type = c("finit", "ftec")
)

## End(Not run)

```

get_usms_list

Getting usms names list for an usms.xml file

Description

Extracting a usm names list from an usms.xml file

Usage

```

get_usms_list(
  file,
  usm = NULL,
  usm_path = lifecycle::deprecated(),
  name = lifecycle::deprecated()
)

```

Arguments

file	Path (including name) of the USM xml file
usm	Vector of USM names (or partial names). Optional, if not provided, the function returns the names of all the USMs included in the given file.
usm_path	[Deprecated] usm_path is no longer supported, use file instead.
name	[Deprecated] name is no longer supported, use usm instead.

Value

A vector of usm names

Examples

```
path <- get_examples_path(file_type = "xml")

usms_list <- get_usms_list(file = file.path(path, "usms.xml"))

usms_list <- get_usms_list(file = file.path(path, "usms.xml"),
  usm = c("usm1", "usm2"))
```

get_varmod

Get desired STICS outputs

Description

Get the STICS output variables (from var.mod file)

Usage

```
get_varmod(workspace, file_name = "var.mod")
```

Arguments

workspace	Path of the directory containing the STICS var.mod file
file_name	file name to read (without path, default value: "var.mod")

Value

The variables that will be returned by STICS

See Also

gen_varmod

Examples

```
get_varmod(get_examples_path(file_type = "txt"))
```

`get_var_info`*Find STICS output variable names and description*

Description

Helper function that returns names and descriptions of STICS output variables from a partial name and/or descriptive keywords.

Usage

```
get_var_info(var = NULL, keyword = NULL, stics_version = "latest")
```

Arguments

<code>var</code>	Vector of variable names (or partial names). Optional, if not provided, the function returns information for all variables.
<code>keyword</code>	Search by keyword instead of variable name (search in the name and description field)
<code>stics_version</code>	Name of the STICS version. Optional, can be used to search parameters information relative to a specific STICS version. By default the latest version returned by <code>get_stics_versions_compat()</code> is used.

Details

The function understand [regex](#) as input.

Value

A `data.frame` with information about variable(s) with columns name, definition, unit, type

Examples

```
# Find by variable name (fuzzy search):
SticsRFiles::get_var_info("lai")

# Find by keyword (fuzzy search in variable name and description):
SticsRFiles::get_var_info(keyword = "lai")

# Find for a particular version:
SticsRFiles::get_var_info("lai", stics_version = "V9.0")
```

is_mac	<i>Evaluating if the OS is a Mac OS type</i>
--------	--

Description

Evaluating if the OS is a Mac OS type

Usage

```
is_mac()
```

Value

TRUE/FALSE

Examples

```
is_mac()
```

is_stics_param	<i>Search if a STICS parameter exist</i>
----------------	--

Description

Tells if one or more parameter names are valid STICS input parameters.

Usage

```
is_stics_param(param, stics_version = "latest")
```

Arguments

param	A vector of parameter names
stics_version	Name of the STICS version. Optional, can be used to search parameters information relative to a specific STICS version. By default the latest version returned by <code>get_stics_versions_compat()</code> is used.

Value

A boolean vector: TRUE if the parameter exist, FALSE otherwise

See Also

`get_param_info()` for interactive use.

Examples

```
is_stics_param(c("adil", "adilmax", "unknown"))
```

is_stics_var	<i>Search if a STICS variable exist</i>
--------------	---

Description

Tells if one or more variable names are valid STICS output variables.

Usage

```
is_stics_var(var, stics_version = "latest")
```

Arguments

var	A vector of variable names
stics_version	Name of the STICS version. Optional, can be used to search parameters information relative to a specific STICS version. By default the latest version returned by <code>get_stics_versions_compat()</code> is used.

Value

A boolean vector: TRUE if the variable exist, FALSE otherwise

See Also

`get_var_info()` for interactive use.

Examples

```
is_stics_var(c("lai(n)", "masec(n)", "unknown"))
```

`is_unix`*Evaluating if the OS is a unix like type*

Description

Evaluating if the OS is a unix like type

Usage

```
is_unix()
```

Value

TRUE/FALSE

Examples

```
is_unix()
```

`is_windows`*Evaluating if the OS is a windows type*

Description

Evaluating if the OS is a windows type

Usage

```
is_windows()
```

Value

TRUE/FALSE

Examples

```
is_windows()
```

read_params_table *Getting parameters data from tables files (Excel sheet, csv)*

Description

Getting parameters data from tables files (Excel sheet, csv)

Usage

```
read_params_table(  
  file,  
  sheet_name = NULL,  
  num_na = "NA",  
  char_na = "",  
  file_path = lifecycle::deprecated()  
)
```

Arguments

file	Excel or csv file path (including name of the file)
sheet_name	Name of an Excel sheet (useless for csv files)
num_na	Replacement value for numerical NA values (default: NA)
char_na	Replacement value for character NA values (default: "")
file_path	[Deprecated] file_path is no longer supported, use file instead.

Details

After data are loaded, numerical and string NA values are replaced respectively with num_na or char_na

Value

A tibble of parameters

Examples

```
usm_xl_file <- download_usm_xl(  
  file = "inputs_stics_example.xlsx",  
  verbose = FALSE  
)  
read_params_table(usm_xl_file, sheet = "USMs")  
usm_csv_file <- download_usm_csv(  
  file = "inputs_stics_example_USMs.csv",  
  verbose = FALSE,  
  stics_version = "V9.2"  
)  
read_params_table(file = usm_csv_file)
```

set_param_txt	<i>Set (replace) STICS input file parameters</i>
---------------	--

Description

Replace or set an input parameter from a pre-existing STICS input file.

Usage

```
set_param_txt(  
    workspace,  
    param,  
    value,  
    append = FALSE,  
    plant_id = NULL,  
    variety = NULL,  
    layer = NULL,  
    stics_version = "latest",  
    dirpath = lifecycle::deprecated(),  
    add = lifecycle::deprecated(),  
    plant = lifecycle::deprecated()  
)
```

```
set_usm_txt(  
    file = "new_travail.usm",  
    param,  
    value,  
    append = FALSE,  
    filepath = lifecycle::deprecated(),  
    add = lifecycle::deprecated()  
)
```

```
set_station_txt(  
    file = "station.txt",  
    param,  
    value,  
    append = FALSE,  
    filepath = lifecycle::deprecated(),  
    add = lifecycle::deprecated()  
)
```

```
set_ini_txt(  
    file = "ficini.txt",  
    param,  
    value,  
    append = FALSE,  
    plant_id = 1,
```

```
    layer = NULL,  
    stics_version = "latest",  
    filepath = lifecycle::deprecated(),  
    add = lifecycle::deprecated()  
  )  
  
set_general_txt(  
  file = "tempopar.sti",  
  param,  
  value,  
  append = FALSE,  
  filepath = lifecycle::deprecated(),  
  add = lifecycle::deprecated()  
)  
  
set_tmp_txt(  
  file = "tempoparv6.sti",  
  param,  
  value,  
  append = FALSE,  
  filepath = lifecycle::deprecated(),  
  add = lifecycle::deprecated()  
)  
  
set_plant_txt(  
  file = "ficplt1.txt",  
  param,  
  value,  
  append = FALSE,  
  variety = NULL,  
  filepath = lifecycle::deprecated(),  
  add = lifecycle::deprecated()  
)  
  
set_tec_txt(  
  file = "fictec1.txt",  
  param,  
  value,  
  append = FALSE,  
  filepath = lifecycle::deprecated(),  
  add = lifecycle::deprecated()  
)  
  
set_soil_txt(  
  file = "param.sol",  
  param,  
  value,  
  layer = NULL,
```

```

    stics_version = "latest",
    filepath = lifecycle::deprecated()
)

```

Arguments

workspace	Path of the workspace containing the STICS (txt) input files.
param	Vector of parameter names.
value	New parameter value
append	Boolean. Append input to existing file
plant_id	The plant identifier (main crop: 1 ; associated crop: 2). Only used for plant, technical or initialisation parameters.
variety	The plant variety to set the parameter value, either the variety name (codevar in the plant file) or the index (variete in the technical file).
layer	The soil layer if any (only concerns soil-related parameters)
stics_version	An optional version name as listed in <code>get_stics_versions_compat()</code> return
dirpath	[Deprecated] dirpath is no longer supported, use workspace instead.
add	[Deprecated] add is no longer supported, use append instead.
plant	[Deprecated] plant is no longer supported, use plant_id instead.
file	Path (including name) of the file to modify
filepath	[Deprecated] filepath is no longer supported, use file instead.

Details

The plant parameter can be either equal to 1, 2 for the associated plant in the case of intercrop, or c(1, 2) for both Principal and associated plants. `get_var_info` is a helper function that returns all possible output variables. If the `variety` is not given and if `param` is a varietal parameter, the function will modify the value of `param` for the simulated variety, as given in the technical file.

Value

None

Note

`gen_varmod` is not used by `set_param_txt`. To replace the output variables required from STICS, please directly call `gen_varmod`.

Examples

```

# Getting example data path
path <- get_examples_path(file_type = "txt")

# Change the value of durvieF for the current variety:
set_param_txt(workspace = path, param = "durvieF", value = 245)

```

```

# Change the value of durvieF for another variety:
set_param_txt(workspace = path, param = "durvieF",
              variety = "Nefer", value = 178)

# If the parameter is found in several files, use the set_*
# functions directly, e.g. cailloux is found in the general file
# ("codecailloux") and the soil file. If we want to change its value
# in the soil file, we use set_soil_txt():
set_soil_txt(file = file.path(path, "param.sol"),
             param = "cailloux", layer = 2, value = 1)

```

set_param_xml

Setting parameter values into xml files

Description

Setting parameter values for a parameter or a vector of and with a parameters values vector

Usage

```

set_param_xml(
  file,
  param,
  values,
  save_as = NULL,
  select = NULL,
  select_value = NULL,
  overwrite = FALSE,
  xml_file = lifecycle::deprecated(),
  out_path = lifecycle::deprecated(),
  param_name = lifecycle::deprecated(),
  param_value = lifecycle::deprecated(),
  value = lifecycle::deprecated(),
  ...
)

```

Arguments

file	Path (including name) of the xml file to modify
param	Vector of parameter names.
values	A vector or a list of parameter(s) values (see details).
save_as	Path (including name) of the xml file to generate. Optional, if NULL file is overwritten.

select	node name or attribute name to use for selection (optional, default to no selection)
select_value	Vector of values used for select (see examples). Optional, should be provided only if select is provided.
overwrite	Logical TRUE for overwriting the output file, FALSE otherwise (default)
xml_file	[Deprecated] xml_file is no longer supported, use file instead.
out_path	[Deprecated] out_path is no longer supported, use save_as instead.
param_name	[Deprecated] param_name is no longer supported, use param instead.
param_value	[Deprecated] param_value is no longer supported, use values instead.
value	[Deprecated] value is no longer supported, use select_value instead.
...	Pass further arguments to set_param_value().

Details

It is possible to give several values for a parameter by passing a vector of values. For example, for two parameters with two values each: `value= list(c(1,2), c(2.3,4.5))`

Value

A logical value TRUE for operation success, FALSE otherwise

Examples

```
ex_path <- get_examples_path(file_type = "xml")

# Soil file

sol_path <- file.path(ex_path, "sols.xml")

# For scalar parameters per soil
# Setting all soils "argi" values to 50
set_param_xml(sol_path, "argi", 50, overwrite = TRUE)
# Getting changed values
# get_param_xml(sol_path, "argi")

# Setting a specific value to "argi" for "solcanne" soil
set_param_xml(file = sol_path, param = "argi", values = 56,
  select = "sol", select_value = "solcanne", overwrite = TRUE
)
# Getting changed values
# get_param_xml(sol_path, "argi",
#   select = "sol", select_value = "solcanne"
#)

# Setting a specific values to 2 parameters "argi" and
# "norg" for "solcanne" soil
set_param_xml(sol_path, c("argi", "norg"), list(100, 150),
```

```

    select = "sol", select_value = "solcanne", overwrite = TRUE
  )
  # Getting changed values
  # get_param_xml(sol_path, c("argi", "norg"),
  #   select = "sol", select_value = "solcanne"
  #)

  # For vector parameters per soil (5 values, one per soil layer)
  set_param_xml(sol_path, c("epc", "HCCF"),
    select = "sol",
    select_value = c("solcanne", "solbanane"),
    param_value = list(c(20:24, 10:14), c(50:54, 40:44)), overwrite = TRUE
  )
  # Getting changed values
  # get_param_xml(sol_path, c("epc", "HCCF"),
  #   select = "sol",
  #   select_value = c("solcanne", "solbanane")
  # )

  # Crop management file

  tec_path <- file.path(ex_path, "file_tec.xml")

  # Modifying irrigations parameters
  set_param_xml(tec_path, c("julapI_or_sum_upvt", "amount"),
    param_value = list(200:215, 20:35), overwrite = TRUE
  )
  # Getting changed values
  # get_param_xml(tec_path, c("julapI_or_sum_upvt", "amount"))

```

 upgrade_ini_xml

Upgrading _ini.xml file(s) to a newer version

Description

Upgrading _ini.xml file(s) to a newer version

Usage

```

upgrade_ini_xml(
  file,
  out_dir,
  param_gen_file,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,

```

```

    overwrite = FALSE,
    ...
)

```

Arguments

file	Path of an initialisation (*_ini.xml) file or a vector of
out_dir	Output directory path of the generated files
param_gen_file	Path of the param_gen.xml file corresponding to the file version
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise
...	Additional input arguments

Details

See `SticsRFiles::get_stics_versions_compat()` for listing versions

Value

None

Examples

```

dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_ini_xml(
  file = file.path(dir_path, "file_ini.xml"),
  out_dir = tempdir(),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)

```

upgrade_param_gen_xml *Upgrading a param_gen.xml file to a newer version*

Description

Upgrading a param_gen.xml file to a newer version

Usage

```

upgrade_param_gen_xml(
  file,
  out_dir,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE
)

```

Arguments

file	Path of a param_gen.xml file
out_dir	Output directory path of the generated file
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise

Details

See get_stics_versions_compat() for listing versions

Value

None

Examples

```

dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_param_gen_xml(
  file = file.path(dir_path, "param_gen.xml"),
  out_dir = tempdir()
)

```

upgrade_param_newform_xml

Upgrading a param_newform.xml file to a newer version

Description

Upgrading a param_newform.xml file to a newer version

Usage

```

upgrade_param_newform_xml(
  file,
  out_dir,
  param_gen_file,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE
)

```

Arguments

<code>file</code>	Path of a param_newform.xml file
<code>out_dir</code>	Output directory path of the generated file
<code>param_gen_file</code>	Path of the param_gen.xml file corresponding to the file version
<code>stics_version</code>	Name of the STICS version (VX.Y format)
<code>target_version</code>	Name of the STICS version to upgrade files to (VX.Y format)
<code>check_version</code>	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
<code>overwrite</code>	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise

Details

See `SticsRFiles::get_stics_versions_compat()` for listing versions

Value

None

Examples

```

dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_param_newform_xml(
  file = file.path(dir_path, "param_newform.xml"),
  out_dir = tempdir(),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)

```

upgrade_plt_xml	<i>Upgrading _plt.xml file(s) to a newer version</i>
-----------------	--

Description

Upgrading _plt.xml file(s) to a newer version

Usage

```

upgrade_plt_xml(
    file,
    out_dir,
    param_newform_file,
    param_gen_file,
    stics_version = "V9.2",
    target_version = "V10.0",
    check_version = TRUE,
    overwrite = FALSE,
    ...
)

```

Arguments

file	Path of an plant (*_plt.xml) file or a vector of
out_dir	Output directory path of the generated files
param_newform_file	Path of the param_newform.xml file corresponding to the file version
param_gen_file	Path of the param_gen.xml file corresponding to the file version
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency between stics_version and the file version, for finally checking if an upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise
...	Additional input arguments

Details

See `get_stics_versions_compat()` for listing versions

Value

None

Examples

```

dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_plt_xml(
  file = file.path(dir_path, "file_plt.xml"),
  out_dir = tempdir(),
  param_newform_file = file.path(dir_path, "param_newform.xml"),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)

```

upgrade_sols_xml	<i>Upgrading a sols.xml file to a newer version</i>
------------------	---

Description

Upgrading a sols.xml file to a newer version

Usage

```

upgrade_sols_xml(
  file,
  out_dir,
  param_gen_file,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE
)

```

Arguments

file	Path of a sols.xml file
out_dir	Output directory path of the generated file
param_gen_file	Path of the param_gen.xml file corresponding to the file version
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise

Details

See `SticsRFiles::get_stics_versions_compat()` for listing versions

Value

None

Examples

```
dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_sols_xml(
  file = file.path(dir_path, "sols.xml" ),
  out_dir = tempdir(),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)
```

upgrade_sta_xml	<i>Upgrading _sta.xml file(s) to a newer version</i>
-----------------	--

Description

Upgrading _sta.xml file(s) to a newer version

Usage

```
upgrade_sta_xml(
  file,
  out_dir,
  param_gen_file,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE,
  ...
)
```

Arguments

file	Path of a station (*_sta.xml) file or a vector of
out_dir	Output directory path of the generated files
param_gen_file	Path of the param_gen.xml file corresponding to the file version
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise
...	Additional input arguments

Details

See `SticsRFiles::get_stics_versions_compat()` for listing versions

Value

None

Examples

```
dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_sta_xml(
  file = file.path(dir_path, "file_sta.xml" ),
  out_dir = tempdir(),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)
```

upgrade_tec_xml	<i>Upgrading _tec.xml file(s) to a newer version</i>
-----------------	--

Description

Upgrading _tec.xml file(s) to a newer version

Usage

```
upgrade_tec_xml(
  file,
  out_dir,
  param_newform_file,
  param_gen_file,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE,
  ...
)
```

Arguments

file	Path of a crop management (*_tec.xml) file or a vector of
out_dir	Output directory path of the generated files
param_newform_file	Path of the param_newform.xml file corresponding to the file version
param_gen_file	Path of the param_gen.xml file corresponding to the file version

stics_version Name of the STICS version (VX.Y format)
 target_version Name of the STICS version to upgrade files to (VX.Y format)
 check_version Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
 overwrite logical (optional), TRUE for overwriting file if it exists, FALSE otherwise
 ... Additional input arguments

Details

See get_stics_versions_compat() for listing versions

Value

None

Examples

```

dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_tec_xml(
  file = file.path(dir_path, "file_tec.xml"),
  out_dir = tempdir(),
  param_newform_file = file.path(dir_path, "param_newform.xml"),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)

```

upgrade_usms_xml

Upgrading a usms.xml file to a newer version

Description

Upgrading a usms.xml file to a newer version

Usage

```

upgrade_usms_xml(
  file,
  out_dir,
  param_gen_file,
  obs_dir = NULL,
  stics_version = "V9.2",
  target_version = "V10.0",
  check_version = TRUE,
  overwrite = FALSE
)

```

Arguments

file	Path of a usms.xml file
out_dir	Output directory path of the generated file
param_gen_file	Path of the param_gen.xml file corresponding to the file version
obs_dir	Directory path of the observation data files
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
check_version	Perform version consistency with in stics_version input with the file version and finally checking if the upgrade is possible allowed to the target_version. If TRUE, param_gen_file is mandatory.
overwrite	logical (optional), TRUE for overwriting file if it exists, FALSE otherwise

Details

See get_stics_versions_compat() for listing versions

Value

None

Examples

```
dir_path <- get_examples_path(file_type = "xml", stics_version = "V9.2")

upgrade_usms_xml(
  file = file.path(dir_path, "usms.xml"),
  out_dir = tempdir(),
  param_gen_file = file.path(dir_path, "param_gen.xml")
)
```

upgrade_workspace_xml *Upgrading XML files of a JavaSTICS workspace directory to a newer STICS version format*

Description

Upgrading XML files of a JavaSTICS workspace directory to a newer STICS version format

Usage

```

upgrade_workspace_xml(
  workspace,
  javastics,
  out_dir,
  stics_version = "V9.2",
  target_version = "V10.0",
  plant = FALSE,
  overwrite = FALSE,
  ...
)

```

Arguments

workspace	Path of a JavaSTICS workspace
javastics	Path of JavaSTICS containing the STICS version corresponding to the version of the files to be converted
out_dir	Output directory of the generated files
stics_version	Name of the STICS version (VX.Y format)
target_version	Name of the STICS version to upgrade files to (VX.Y format)
plant	logical (optional), TRUE for upgrading plant files if a "plant" sub-directory of workspace exists, FALSE otherwise
overwrite	logical (optional), TRUE for overwriting files if they exist, FALSE otherwise
...	Additional input arguments

Details

- See `SticsRFiles::get_stics_versions_compat()` for listing versions
- If general parameters files exist in workspace, they are also upgraded. In that case, residues parameters values are kept and might not be adapted to the target model version.
- Weather data and observations files are fully copied to `out_dir`

Value

None

Examples

```

## Not run:
upgrade_workspace_xml(
  workspace = "/path/to/JavaSTICS/workspace",
  javastics = "/path/to/JavaSTICS/folder",
  out_dir = "/path/to/an/output/directory"
)

## End(Not run)

```

[.cropr_simulation [*method for* cropr_simulation

Description

This method ensure keeping the `cropr_simulation` attribute when subsetting a `cropr_simulation` list.

Usage

```
## S3 method for class 'cropr_simulation'  
x[...]
```

Arguments

<code>x</code>	A <code>cropr_simulation</code> list
<code>...</code>	An index

Value

A subset of a `cropr_simulation`, keeping its attribute

Examples

```
path <- file.path(get_examples_path("sti"), "workspace1")  
sim <- SticsRFiles::get_sim(workspace = path)  
# sim returns a `cropr_simulation` list
```

Index

[.cropr_simulation, 61

convert_xml2txt, 4

download_data, 5

download_usm_csv, 6

download_usm_xml, 7

force_param_values, 8

gen_ini_xml, 7, 9

gen_obs, 10

gen_sols_xml, 7, 12

gen_sta_xml, 7, 13

gen_tec_xml, 7, 15

gen_usms_xml, 6, 7, 16

gen_usms_xml2txt, 18

gen_varmod, 19

get_climate_txt, 21

get_examples_path, 22

get_general_txt (get_param_txt), 26

get_ini_txt (get_param_txt), 26

get_lai_forcing, 23

get_obs, 23

get_param_info, 25

get_param_txt, 26

get_param_xml, 30

get_plant_txt (get_param_txt), 26

get_plants_nb, 31

get_report_results, 32

get_sim, 33

get_soil_txt (get_param_txt), 26

get_soils_list, 35

get_station_txt (get_param_txt), 26

get_stics_versions_compat, 36

get_tec_txt (get_param_txt), 26

get_tmp_txt (get_param_txt), 26

get_usm_txt (get_param_txt), 26

get_usms_files, 36

get_usms_list, 38

get_var_info, 11, 40, 47

get_varmod, 39

is_mac, 41

is_stics_param, 41

is_stics_var, 42

is_unix, 43

is_windows, 43

read_params_table, 44

regex, 26, 40

set_general_txt (set_param_txt), 45

set_ini_txt (set_param_txt), 45

set_param_txt, 45

set_param_xml, 48

set_plant_txt (set_param_txt), 45

set_soil_txt (set_param_txt), 45

set_station_txt (set_param_txt), 45

set_tec_txt (set_param_txt), 45

set_tmp_txt (set_param_txt), 45

set_usm_txt (set_param_txt), 45

upgrade_ini_xml, 50

upgrade_param_gen_xml, 51

upgrade_param_newform_xml, 52

upgrade_plt_xml, 54

upgrade_sols_xml, 55

upgrade_sta_xml, 56

upgrade_tec_xml, 57

upgrade_usms_xml, 58

upgrade_workspace_xml, 59