

Package ‘ggspectra’

September 13, 2024

Type Package

Title Extensions to 'ggplot2' for Radiation Spectra

Version 0.3.13

Date 2024-09-12

Maintainer Pedro J. Aphalo <pedro.aphalo@helsinki.fi>

Description Additional annotations, stats, geoms and scales for plotting ``light'' spectra with 'ggplot2', together with specializations of ggplot() and autoplot() methods for spectral data and waveband definitions stored in objects of classes defined in package 'photobiology'. Part of the 'r4photobiology' suite, Aphalo P. J. (2015) <doi:10.19232/uv4pb.2015.1.14>.

License GPL (>= 2)

LazyLoad TRUE

ByteCompile TRUE

Depends R (>= 4.1.0), photobiology (>= 0.11.2), ggplot2 (>= 3.5.0)

Imports photobiologyWavebands (>= 0.5.2), scales (>= 1.2.0), ggrepel (>= 0.9.2), lubridate (>= 1.9.0), rlang (>= 1.0.2), tibble (>= 3.1.5)

Suggests knitr (>= 1.38), rmarkdown (>= 2.13), magrittr (>= 2.0.3)

URL <https://docs.r4photobiology.info/ggspectra/>,
<https://github.com/aphalo/ggspectra/>

BugReports <https://github.com/aphalo/ggspectra/issues/>

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Pedro J. Aphalo [aut, cre] (<<https://orcid.org/0000-0003-3385-972X>>),
Titta K. Kotilainen [ctb] (<<https://orcid.org/0000-0002-2822-9734>>)

Repository CRAN

Date/Publication 2024-09-13 19:30:02 UTC

Contents

ggspectra-package	3
Afr_label	5
autoplot.calibration_spct	6
autoplot.cps_spct	9
autoplot.filter_spct	13
autoplot.object_spct	17
autoplot.raw_spct	20
autoplot.reflector_spct	24
autoplot.response_spct	27
autoplot.source_spct	31
autoplot.waveband	34
autotitle	37
axis_labels_uk	38
A_label	39
black_or_white	41
color_chart	42
counts_label	43
cps_label	44
exponent2prefix	45
geom_spct	46
ggplot	47
multipliers_label	51
multiplot	52
plot.generic_spct	54
Rfr_label	55
s.e.irrad_label	56
s.e.response_label	57
scale_x_energy_eV_continuous	59
scale_x_frequency_continuous	61
scale_x_wavenumber_continuous	62
scale_x_wl_continuous	63
scale_y_Afr_continuous	64
scale_y_A_continuous	66
scale_y_counts_continuous	68
scale_y_cps_continuous	70
scale_y_multipliers_continuous	71
scale_y_Rfr_continuous	72
scale_y_s.e.irrad_continuous	74
scale_y_s.e.response_continuous	77
scale_y_Tfr_continuous	80
sec_axis_w_number	82
set_annotations_default	85
SI_pl_format	86
SI_tg_format	87
stat_color	88
stat_find_qtys	89

stat_find_wls	92
stat_label_peaks	95
stat_peaks	98
stat_spikes	102
stat_wb_box	105
stat_wb_column	108
stat_wb_contribution	110
stat_wb_hbar	113
stat_wb_irrad	116
stat_wb_label	120
stat_wb_mean	122
stat_wb_relative	125
stat_wb_sirrad	128
stat_wb_total	132
stat_wl_strip	135
stat_wl_summary	137
Tfr_label	140
w_length_label	141
w_number	143

Index**145**

ggspectra-package *ggspectra: Extensions to 'ggplot2' for Radiation Spectra*

Description

Additional annotations, stats, geoms and scales for plotting "light" spectra with 'ggplot2', together with specializations of ggplot() and autoplot() methods for spectral data and waveband definitions stored in objects of classes defined in package 'photobiology'. Part of the 'r4photobiology' suite, Aphalo P. J. (2015) [doi:10.19232/uv4pb.2015.1.14](https://doi.org/10.19232/uv4pb.2015.1.14).

Details

Package 'ggspectra' provides a set of stats, geoms and methods extending packages 'ggplot2' and 'photobiology'. They ease the task of plotting radiation-related spectra and of annotating the resulting plots with labels and summary quantities derived from the spectral data.

Plot methods automate in many respects the plotting of spectral data. 'ggplot2' compatible statistics make the addition of labels or plotting of subject-area specific summaries possible as well as the addition of labels and wavelength-based colour to plots easy. Available summaries are most of those relevant to photobiology. However, many of the functions in the package are more generally useful for plotting UV, VIS and NIR spectra of light emission, transmittance, reflectance, absorptance, and responses.

The available summary quantities are both simple statistical summaries and response-weighted summaries. Simple derived quantities represent summaries of a given range of wavelengths, and can be expressed either in energy or photon based units. Derived biologically effective quantities are used to quantify the effect of radiation on different organisms or processes within organisms. These

effects can range from damage to perception of informational light signals. Additional features of spectra may be important and worthwhile annotating in plots. Of these, local maxima (peaks) and minima (valleys) present in spectral data can also be annotated with statistics made available by the 'ggspectra' package.

Package 'ggspectra' is useful solely for plotting spectral data as most functions depend on the x aesthetic being mapped to a variable containing wavelength values expressed in nanometres. It works well together with some other extensions to package 'ggplot2' such as packages 'ggrepel' and 'cowplot'.

This package is part of a suite of R packages for photobiological calculations described at the [r4photobiology](https://www.r4photobiology.info) web site.

Note

This package makes use of the new features of 'ggplot2' >= 2.0.0 that make writing this kind of extensions easy and is consequently not compatible with earlier versions of 'ggplot2'.

Author(s)

Maintainer: Pedro J. Aphalo <pedro.aphalo@helsinki.fi> ([ORCID](#))

Other contributors:

- Titta K. Kotilainen ([ORCID](#)) [contributor]

References

Aphalo, Pedro J. (2015) The r4photobiology suite. UV4Plants Bulletin, 2015:1, 21-29. doi:10.19232/uv4pb.2015.1.14.

ggplot2 web site at <https://ggplot2.tidyverse.org/>

ggplot2 source code at <https://github.com/tidyverse/ggplot2>

Function multiplot from <http://www.cookbook-r.com/>

See Also

Useful links:

- <https://docs.r4photobiology.info/ggspectra/>
- <https://github.com/aphalo/ggspectra/>
- Report bugs at <https://github.com/aphalo/ggspectra/issues/>

Examples

```
library(photobiologyWavebands)

ggplot(sun.spct) + geom_line() + stat_peaks(span = NULL)

ggplot(sun.spct, aes(w.length, s.e.irrad)) + geom_line() +
  stat_peaks(span = 21, geom = "point", colour = "red") +
  stat_peaks(span = 51, geom = "text", colour = "red", vjust = -0.3,
            label.fmt = "%3.0f nm")
```

```
ggplot(polyester.spct, range = UV()) + geom_line()

plot(sun.spct)

plot(polyester.spct, UV_bands(), range = UV(),
      annotations = c("=", "segments", "labels"))
```

Afr_label

Absorptance axis labels

Description

Generate cps axis labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
Afr_label(
  unit.exponent = ifelse(pc.out, -2, 0),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.Afr"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE)
)

Rfr_total_label(
  unit.exponent = ifelse(pc.out, -2, 0),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE)
)
```

Arguments

unit.exponent	integer
format	character string, "R", "R.expresion", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).

axis.symbols logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".

pc.out logical, if TRUE use percent as default instead of fraction of one.

Value

a character string or an R expression.

Examples

```
Afr_label()
Afr_label(format = "R.expression", axis.symbols = FALSE)
Afr_label(-2)
Afr_label(-3)
Afr_label(format = "R.expression")
Afr_label(format = "LaTeX")
Afr_label(-2, format = "LaTeX")
```

```
Rfr_total_label()
Rfr_total_label(axis.symbols = FALSE)
Rfr_total_label(-2)
Rfr_total_label(-3)
Rfr_total_label(format = "R.expression")
Rfr_total_label(format = "LaTeX")
Rfr_total_label(-3, format = "LaTeX")
```

autoplot.calibration_spct

Plot one or more irradiance-calibration spectra.

Description

These methods return a ggplot object with an annotated plot of the spectral data contained in a calibration_spct or a calibration_mspct object.

Usage

```
## S3 method for class 'calibration_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  unit.out = "ignored",
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
```

```

    label.qty = "mean",
    span = NULL,
    wls.target = "HM",
    annotations = NULL,
    geom = "line",
    time.format = "",
    tz = "UTC",
    norm = NULL,
    text.size = 2.5,
    idfactor = NULL,
    facets = FALSE,
    plot.data = "as.is",
    ylim = c(NA, NA),
    object.label = deparse(substitute(object)),
    na.rm = TRUE
  )

## S3 method for class 'calibration_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  unit.out = "ignored",
  norm = getOption("ggspectra.normalize", default = "skip"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  plot.data = "as.is",
  idfactor = TRUE,
  facets = FALSE,
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

```

Arguments

object	a calibration_spect object or a calibration_mspct object.
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.
range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
unit.out	character IGNORED.
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.

wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
text.size	numeric size of text in the plot decorations.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spct contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package 'ggplot2'. Package 'ggspectra' defines specializations for the different classes for storage of spectral data defined in package [photobiology](#).

Value

A ggplot object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or c("=", "") as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to ggplot2::ggtitle() as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title, subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

If idfactor = NULL, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default "spct.idx" is tried. The default for multiple spectra is to create a factor named "spct.idx", but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [calibration_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
# to be added
```

```
autoplot.cps_spct      Plot one or more detector-counts-per-second spectra.
```

Description

These methods return a ggplot object with an annotated plot of a cps_spct or a cps_mspct object.

Usage

```

## S3 method for class 'cps_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = "skip",
  unit.out = NULL,
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = "mean",
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = "line",
  time.format = "",
  tz = "UTC",
  text.size = 2.5,
  idfactor = NULL,
  facets = FALSE,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

## S3 method for class 'cps_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = "skip",
  unit.out = NULL,
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  idfactor = TRUE,
  facets = FALSE,
  plot.data = "as.is",
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

```

Arguments

object	a cps_spct object.
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.

range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
unit.out	character IGNORED.
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
text.size	numeric size of text in the plot decorations.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spct contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter `annotations`.

The generic of the `autoplot` method is defined in package `'ggplot2'`. Package `'ggspectra'` defines specializations for the different classes for storage of spectral data defined in package `photobiology`.

Value

A `ggplot` object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: `"summaries"`, `"peaks"`, `"peak.labels"`, `"valleys"`, `"valley.labels"`, `"wls"`, `"wls.labels"`, `"colour.guide"`, `"color.guide"`, `"boxes"`, `"segments"`, `"labels"`. In addition, `"+"` is interpreted as a request to add to the already present default annotations, `"-"` as request to remove annotations and `"="` or missing `"+"` and `"-"` as a request to reset annotations to those requested. If used, `"+"`, `"-"` or `"="` must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass `""` or `c("=", "")` as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding `"peak.labels"` replaces `"peaks"` if present.

Title Annotations

metadata retrieved from object `object` is passed to `ggplot2::ggtitle()` as arguments for `title`, `subtitle` and `caption`. The specification for the title is passed as argument to annotations, and consists in the keyword `title` with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to `title`, `subtitle` and `caption`. The recognized keywords are: `"objt"`, `"class"`, `"what"`, `"when"`, `"where"`, `"how"`, `"inst.name"`, `"inst.sn"`, `"comment"` and `"none"` are recognized as modifiers to `"title"`; `"none"` is a placeholder. Default is `"title:objt"` or no title depending on the context.

Note

If `idfactor = NULL`, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default `"spct.idx"` is tried. The default for multiple spectra is to create a factor named `"spct.idx"`, but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [cps_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other `autoplot` methods: [autoplot.calibration_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
autoplot(white_led.cps_spct)
autoplot(white_led.cps_spct, geom = "spct")
autoplot(white_led.cps_spct, norm = "max")
```

```

two_leds.mspct <-
  cps_mspct(list("LED 1" = white_led.cps_spct,
                "LED 2" = white_led.cps_spct / 2))
autoplot(two_leds.mspct)
autoplot(two_leds.mspct, idfactor = "Spectra")
autoplot(two_leds.mspct, plot.data = "mean")

```

autoplot.filter_spct *Plot one or more "filter" spectra.*

Description

These methods return a ggplot object of an annotated plot from spectral data contained in a `filter_spct` or a `filter_mspct` object. Data can be expressed as absorbance, absorptance or transmittance.

Usage

```

## S3 method for class 'filter_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "update"),
  plot.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = NULL,
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = "line",
  time.format = "",
  tz = "UTC",
  text.size = 2.5,
  chroma.type = "CMF",
  idfactor = NULL,
  facets = FALSE,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

## S3 method for class 'filter_mspct'
autoplot(

```

```

object,
...,
range = getOption("ggspectra.wlrange", default = NULL),
norm = getOption("ggspectra.norm", default = "update"),
plot.qty = getOption("photobiology.filter.qty", default = "transmittance"),
pc.out = getOption("ggspectra.pc.out", default = FALSE),
plot.data = "as.is",
idfactor = TRUE,
facets = FALSE,
object.label = deparse(substitute(object)),
na.rm = TRUE
)

```

Arguments

object	a filter_spct object or a filter_mspct object.
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.
range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
plot.qty	character string one of "transmittance" or "absorbance".
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
text.size	numeric size of text in the plot decorations.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.

<code>idfactor</code>	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
<code>facets</code>	logical or integer Indicating if facets are to be created for the levels of <code>idfactor</code> when <code>spect</code> contain multiple spectra in long form.
<code>plot.data</code>	character Data to plot. Default is <code>"as.is"</code> plotting one line per spectrum. When passing <code>"mean"</code> , <code>"median"</code> , <code>"sum"</code> , <code>"prod"</code> , <code>"var"</code> , <code>"sd"</code> , <code>"se"</code> as argument all the spectra must contain data at the same wavelength values.
<code>ylim</code>	numeric y axis limits,
<code>object.label</code>	character The name of the object being plotted.
<code>na.rm</code>	logical.

Details

The plot object returned is a `ggplot` (an object of class `"gg"`) and it can be added to or modified as any other `ggplot`. The axis labels are encoded as `plotmath` expressions as they contain superscripts and special characters. In `'ggplot2'`, `plotmath` expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package `'ggplot2'`. Package `'ggspectra'` defines specializations for the different classes for storage of spectral data defined in package `photobiology`.

Value

A `ggplot` object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: `"summaries"`, `"peaks"`, `"peak.labels"`, `"valleys"`, `"valley.labels"`, `"wls"`, `"wls.labels"`, `"colour.guide"`, `"color.guide"`, `"boxes"`, `"segments"`, `"labels"`. In addition, `"+"` is interpreted as a request to add to the already present default annotations, `"-"` as request to remove annotations and `"="` or missing `"+"` and `"-"` as a request to reset annotations to those requested. If used, `"+"`, `"-"` or `"="` must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass `""` or `c("=", "")` as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding `"peak.labels"` replaces `"peaks"` if present.

Title Annotations

metadata retrieved from object `object` is passed to `ggplot2::ggtitle()` as arguments for `title`, `subtitle` and `caption`. The specification for the title is passed as argument to annotations, and consists in the keyword `title` with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to `title`, `subtitle` and `caption`. The recognized keywords are: `"objt"`, `"class"`, `"what"`, `"when"`, `"where"`,

"how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

The plotting of absorbance is an exception to scale limits as the y-axis is not extended past 6 a.u. In the case of absorbance, values larger than 6 a.u. are rarely meaningful due to stray light during measurement. However, when transmittance values below the detection limit are rounded to zero, and later converted into absorbance, values Inf a.u. result, disrupting the plot. Scales are further expanded so as to make space for the annotations.

If `idfactor = NULL`, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default `"spct.idx"` is tried. The default for multiple spectra is to create a factor named `"spct.idx"`, but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [filter_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
# one spectrum
autoplot(yellow_gel.spct)
autoplot(yellow_gel.spct, geom = "spct")
autoplot(yellow_gel.spct, plot.qty = "transmittance")
autoplot(yellow_gel.spct, plot.qty = "absorptance")
autoplot(yellow_gel.spct, plot.qty = "absorbance")
autoplot(yellow_gel.spct, pc.out = TRUE)
autoplot(yellow_gel.spct, annotations = c("+", "wls"))

# spectra for two filters in long form
autoplot(two_filters.spct)
autoplot(two_filters.spct, idfactor = "Spectra")
autoplot(two_filters.spct, facets = TRUE)

# spectra for two filters as a collection
autoplot(two_filters.mspct)
autoplot(two_filters.mspct, idfactor = "Spectra")
autoplot(two_filters.mspct, facets = TRUE)
```

autoplot.object_spct *Plot one or more "object" spectra.*

Description

These methods return a ggplot object with an annotated plot of an object_spct or an object_mspct object. These objects contain spectral transmittance, reflectance and possibly absorbance data. As these quantities add up to one, only two are needed.

Usage

```
## S3 method for class 'object_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = "skip",
  plot.qty = "all",
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = NULL,
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = NULL,
  time.format = "",
  tz = "UTC",
  stacked = plot.qty == "all",
  text.size = 2.5,
  chroma.type = "CMF",
  idfactor = NULL,
  facets = NULL,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

## S3 method for class 'object_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = "skip",
  plot.qty = getOption("photobiology.filter.qty", default = "all"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
```

```

plot.data = "as.is",
idfactor = TRUE,
facets = plot.qty == "all",
object.label = deparse(substitute(object)),
na.rm = TRUE
)

```

Arguments

object	an object_spct object
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.
range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
plot.qty	character string, one of "all", "transmittance", "absorbance", "absorptance", or "reflectance".
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
stacked	logical Whether to use position_stack() or position_identity().
text.size	numeric size of text in the plot decorations.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.

facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spect contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package 'ggplot2'. Package 'ggspectra' defines specializations for the different classes for storage of spectral data defined in package [photobiology](#).

Value

A ggplot object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or `c("=", "")` as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to `ggplot2::ggtitle()` as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title, subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

In the case of multiple spectra contained in the argument to object plotting is for `plot.qty = "all"` is always done using facets. Other plot quantities are handled by the methods for `filter_spct` and `reflector_spct` objects after on-the-fly conversion and the use of facets is possible but not the default.

If `idfactor = NULL`, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default "spct.idx" is tried. The default for multiple spectra is to create a factor named "spct.idx", but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [object_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotatations_default\(\)](#)

Examples

```
low_res.spct <- thin_wl(Ler_leaf.spct,
                      max.wl.step = 20,
                      max.slope.delta = 0.01,
                      col.names = "Tfr")
autoplot(low_res.spct)
autoplot(low_res.spct, geom = "line")

two_leaves.mspct <-
  object_mspct(list("Arabidopsis leaf 1" = low_res.spct,
                   "Arabidopsis leaf 2" = low_res.spct))
autoplot(two_leaves.mspct, idfactor = "Spectra")
```

`autoplot.raw_spct` *Plot one or more raw-detector-counts spectra.*

Description

These methods construct a ggplot object with an annotated plot of a `raw_spct` or a `raw_mspct` object.

Usage

```
## S3 method for class 'raw_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA()),
```

```

    PhR()))),
  range = getOption("ggspectra.wlrange", default = NULL),
  unit.out = "counts",
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = "mean",
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = "line",
  time.format = "",
  tz = "UTC",
  norm = "skip",
  text.size = 2.5,
  idfactor = NULL,
  facets = FALSE,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

## S3 method for class 'raw_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "skip"),
  unit.out = "counts",
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  idfactor = TRUE,
  facets = FALSE,
  plot.data = "as.is",
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

```

Arguments

<code>object</code>	a <code>raw_spct</code> object.
<code>...</code>	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
<code>w.band</code>	a single waveband object or a list of waveband objects.
<code>range</code>	an R object on which <code>range()</code> returns a vector of length 2, with minimum and maximum wavelengths (nm).
<code>unit.out</code>	character IGNORED.
<code>pc.out</code>	logical, if TRUE use percent instead of fraction of one for normalized spectral data.

label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
text.size	numeric size of text in the plot decorations.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spct contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package 'ggplot2'. Package 'ggspectra' defines specializations for the different classes for storage of spectral data defined in package [photobiology](#).

Value

A ggplot object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or c("=", "") as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to ggplot2::ggtitle() as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title, subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

If idfactor = NULL, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default "spct.idx" is tried. The default for multiple spectra is to create a factor named "spct.idx", but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [raw_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
low_res.raw_spct <- thin_wl(white_led.raw_spct,
                          max.wl.step = 20,
                          max.slope.delta = 0.05,
                          col.names = "counts_3")

autoplot(low_res.raw_spct)
autoplot(low_res.raw_spct, annotations = "")

two_leds.mspct <-
  raw_mspct(list("LED 1" = low_res.raw_spct,
                "LED 2" = low_res.raw_spct))
autoplot(two_leds.mspct)
```

```
autoplot(two_leds.mspct, facets = 1) # one column
```

```
autoplot.reflector_spct
```

Plot one or more reflector spectra.

Description

These methods return a ggplot object for an annotated plot from spectral data stored in a `reflector_spct` or a `reflector_mspct` object.

Usage

```
## S3 method for class 'reflector_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "update"),
  plot.qty = getOption("photobiology.reflector.qty", default = "reflectance"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = NULL,
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = "line",
  time.format = "",
  tz = "UTC",
  text.size = 2.5,
  chroma.type = "CMF",
  idfactor = NULL,
  facets = FALSE,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)
```

```
## S3 method for class 'reflector_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.normalize", default = "update"),
```



```

plot.qty = getOption("photobiology.reflector.qty", default = "reflectance"),
pc.out = getOption("ggspectra.pc.out", default = FALSE),
plot.data = "as.is",
idfactor = TRUE,
facets = FALSE,
object.label = deparse(substitute(object)),
na.rm = TRUE
)

```

Arguments

object	a reflector_spct object or a reflector_mspct object.
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.
range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
plot.qty	character string (currently ignored).
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
text.size	numeric size of text in the plot decorations.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.

facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spect contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package 'ggplot2'. Package 'ggspectra' defines specializations for the different classes for storage of spectral data defined in package [photobiology](#).

Value

A ggplot object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or `c("=", "")` as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to `ggplot2::ggtitle()` as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title, subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

If `idfactor = NULL`, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default `"spct.idx"` is tried. The default for multiple spectra is to create a factor named `"spct.idx"`, but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [reflector_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
autoplot(Ler_leaf_rflt.spct)
autoplot(Ler_leaf_rflt.spct, geom = "spct")
autoplot(Ler_leaf_rflt.spct, annotations = c("+", "valleys"))

two_leaves.mspct <-
  reflector_mspct(list("Arabidopsis leaf 1" = Ler_leaf_rflt.spct,
                     "Arabidopsis leaf 2" = Ler_leaf_rflt.spct / 2))
autoplot(two_leaves.mspct)
autoplot(two_leaves.mspct, idfactor = "Spectra")
autoplot(two_leaves.mspct, facets = 2)
```

autoplot.response_spct

Plot one or more response spectra.

Description

These methods return a ggplot object with an annotated plot of the spectral data contained in a `response_spct` or a `response_mspct` object. Spectral responsivity can be expressed either on an energy basis or a photon or quantum basis.

Usage

```
## S3 method for class 'response_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default = list(UVC(), UVB(), UVA(),
    PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "update"),
```

```

unit.out = getOption("photobiology.radiation.unit", default = "energy"),
pc.out = getOption("ggspectra.pc.out", default = FALSE),
label.qty = NULL,
span = NULL,
wls.target = "HM",
annotations = NULL,
geom = "line",
time.format = "",
tz = "UTC",
text.size = 2.5,
idfactor = NULL,
facets = FALSE,
plot.data = "as.is",
ylim = c(NA, NA),
object.label = deparse(substitute(object)),
na.rm = TRUE
)

## S3 method for class 'response_mspct'
autoplot(
  object,
  ...,
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "update"),
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  plot.data = "as.is",
  facets = FALSE,
  idfactor = TRUE,
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

```

Arguments

<code>object</code>	a <code>response_spct</code> object or a <code>response_mspct</code> object.
<code>...</code>	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
<code>w.band</code>	a single waveband object or a list of waveband objects.
<code>range</code>	an R object on which <code>range()</code> returns a vector of length 2, with minimum and maximum wavelengths (nm).
<code>norm</code>	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
<code>unit.out</code>	character string indicating type of radiation units to use for plotting: "photon" or its synonym "quantum", or "energy".

pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
text.size	numeric size of text in the plot decorations.
idfactor	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
facets	logical or integer Indicating if facets are to be created for the levels of idfactor when spct contain multiple spectra in long form.
plot.data	character Data to plot. Default is "as.is" plotting one line per spectrum. When passing "mean", "median", "sum", "prod", "var", "sd", "se" as argument all the spectra must contain data at the same wavelength values.
ylim	numeric y axis limits,
object.label	character The name of the object being plotted.
na.rm	logical.

Details

The plot object returned is a ggplot (an object of class "gg") and it can be added to or modified as any other ggplot. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In 'ggplot2', plotmath expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package 'ggplot2'. Package 'ggspectra' defines specializations for the different classes for storage of spectral data defined in package [photobiology](#).

Value

A ggplot object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or c("=", "") as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to ggplot2::ggtitle() as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title, subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

If idfactor = NULL, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default "spct.idx" is tried. The default for multiple spectra is to create a factor named "spct.idx", but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [response_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.source_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotations_default\(\)](#)

Examples

```
autoplot(photodiode.spct)
autoplot(photodiode.spct, geom = "spct")
autoplot(photodiode.spct, unit.out = "photon")
autoplot(photodiode.spct, annotations = "")
autoplot(photodiode.spct, norm = "skip")
autoplot(photodiode.spct, norm = 400)

two_sensors.mspect <-
  response_mspect(list("Photodiode" = photodiode.spct,
                      "Coupled charge device" = ccd.spct))
autoplot(two_sensors.mspect, normalize = TRUE, unit.out = "photon")
```

```

autoplot(two_sensors.mspct, normalize = TRUE, idfactor = "Spectra")
autoplot(two_sensors.mspct, normalize = TRUE, facets = 2)
autoplot(two_sensors.mspct, normalize = TRUE, geom = "spct")

```

autoplot.source_spct *Plot one or more light-source spectra.*

Description

These methods return a ggplot object with an annotated plot of the spectral data contained in a source_spct or a source_mspct object.

Usage

```

## S3 method for class 'source_spct'
autoplot(
  object,
  ...,
  w.band = getOption("photobiology.plot.bands", default =
    list(photobiologyWavebands::UVC(), photobiologyWavebands::UVB(),
    photobiologyWavebands::UVA(), photobiologyWavebands::PhR())),
  range = getOption("ggspectra.wlrange", default = NULL),
  norm = getOption("ggspectra.norm", default = "update"),
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  label.qty = NULL,
  span = NULL,
  wls.target = "HM",
  annotations = NULL,
  geom = "line",
  time.format = "",
  tz = "UTC",
  text.size = 2.5,
  chroma.type = "CMF",
  idfactor = NULL,
  facets = FALSE,
  plot.data = "as.is",
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)

## S3 method for class 'source_mspct'
autoplot(
  object,
  ...,

```

```

range = getOption("ggspectra.wlrange", default = NULL),
norm = getOption("ggspectra.normalize", default = "update"),
unit.out = getOption("photobiology.radiation.unit", default = "energy"),
pc.out = getOption("ggspectra.pc.out", default = FALSE),
idfactor = TRUE,
facets = FALSE,
plot.data = "as.is",
object.label = deparse(substitute(object)),
na.rm = TRUE
)

```

Arguments

object	a source_spct or a source_mspct object.
...	in the case of collections of spectra, additional arguments passed to the plot methods for individual spectra, otherwise currently ignored.
w.band	a single waveband object or a list of waveband objects.
range	an R object on which range() returns a vector of length 2, with minimum and maximum wavelengths (nm).
norm	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength, "update" to update the normalization after modifying units of expression, quantity or range but respecting the previously used criterion, or "skip" to force return of object unchanged.
unit.out	character string indicating type of radiation units to use for plotting: "photon" or its synonym "quantum", or "energy".
pc.out	logical, if TRUE use percent instead of fraction of one for normalized spectral data.
label.qty	character string giving the type of summary quantity to use for labels, one of "mean", "total", "contribution", and "relative".
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centred at that element.
wls.target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
annotations	a character vector. For details please see sections Plot Annotations and Title Annotations .
geom	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
time.format	character Format as accepted by strptime .
tz	character Time zone to use for title and/or subtitle.
text.size	numeric size of text in the plot decorations.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.

<code>idfactor</code>	character Name of an index column in data holding a factor with each spectrum in a long-form multispectrum object corresponding to a distinct level of the factor.
<code>facets</code>	logical or integer Indicating if facets are to be created for the levels of <code>idfactor</code> when <code>spct</code> contain multiple spectra in long form.
<code>plot.data</code>	character Data to plot. Default is <code>"as.is"</code> plotting one line per spectrum. When passing <code>"mean"</code> , <code>"median"</code> , <code>"sum"</code> , <code>"prod"</code> , <code>"var"</code> , <code>"sd"</code> , <code>"se"</code> as argument all the spectra must contain data at the same wavelength values.
<code>ylim</code>	numeric y axis limits,
<code>object.label</code>	character The name of the object being plotted.
<code>na.rm</code>	logical.

Details

The plot object returned is a `ggplot` (an object of class `"gg"`) and it can be added to or modified as any other `ggplot`. The axis labels are encoded as *plotmath* expressions as they contain superscripts and special characters. In `'ggplot2'`, *plotmath* expressions do not obey theme settings related to text fonts, except for size.

Scale limits are expanded so as to make space for the annotations. If annotations are disabled, limits are not expanded unless `reserve.space` is passed to parameter annotations.

The generic of the `autoplot` method is defined in package `'ggplot2'`. Package `'ggspectra'` defines specializations for the different classes for storage of spectral data defined in package `photobiology`.

Value

A `ggplot` object with a number of layers that depends on the data and annotations.

Plot Annotations

The recognized annotation names are: `"summaries"`, `"peaks"`, `"peak.labels"`, `"valleys"`, `"valley.labels"`, `"wls"`, `"wls.labels"`, `"colour.guide"`, `"color.guide"`, `"boxes"`, `"segments"`, `"labels"`. In addition, `"+"` is interpreted as a request to add to the already present default annotations, `"-"` as request to remove annotations and `"="` or missing `"+"` and `"-"` as a request to reset annotations to those requested. If used, `"+"`, `"-"` or `"="` must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass `""` or `c("=", "")` as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding `"peak.labels"` replaces `"peaks"` if present.

Title Annotations

metadata retrieved from object `object` is passed to `ggplot2::ggtitle()` as arguments for `title`, `subtitle` and `caption`. The specification for the title is passed as argument to annotations, and consists in the keyword `title` with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to `title`, `subtitle` and `caption`. The recognized keywords are: `"objt"`, `"class"`, `"what"`, `"when"`, `"where"`,

"how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

If `idfactor = NULL`, the default for single spectra, the name of the factor is retrieved from metadata or if no metadata found, the default "spct.idx" is tried. The default for multiple spectra is to create a factor named "spct.idx", but if a different name is passed, it will be used instead, possibly renaming a pre-existing one.

See Also

[normalize](#), [source_spct](#), [waveband](#), [photobiologyWavebands-package](#) and [autoplot](#)

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.waveband\(\)](#), [set_annotatations_default\(\)](#)

Examples

```
autoplot(sun.spct)
autoplot(sun.spct, geom = "spct")
autoplot(sun.spct, unit.out = "photon")
autoplot(sun.spct, norm = "max")
autoplot(sun.spct, norm = "max", pc.out = TRUE)

# multiple spectra in long form
autoplot(sun_evening.spct)
autoplot(sun_evening.spct, facets = 1) # one column
autoplot(sun_evening.spct, facets = 2) # two columns
autoplot(sun_evening.spct, plot.data = "mean")
# needs 'photobiology' (> 0.11.2)
# autoplot(sun_evening.spct, idfactor = "Sequence")

# multiple spectra as a collection
autoplot(sun_evening.mspct)
autoplot(sun_evening.mspct, facets = 1) # one column
autoplot(sun_evening.mspct, facets = 2) # two columns
autoplot(sun_evening.mspct, plot.data = "mean")
autoplot(sun_evening.mspct, idfactor = "Time")
```

`autoplot.waveband`

Create a complete ggplot for a waveband descriptor.

Description

This function returns a ggplot object with an annotated plot of a waveband object.

Usage

```
## S3 method for class 'waveband'
autoplot(
  object,
  ...,
  w.length = NULL,
  range = c(280, 800),
  fill = 0,
  span = NULL,
  wls.target = "HM",
  unit.in = getOption("photobiology.radiation.unit", default = "energy"),
  annotations = NULL,
  geom = "line",
  wb.trim = TRUE,
  norm = NULL,
  text.size = 2.5,
  ylim = c(NA, NA),
  object.label = deparse(substitute(object)),
  na.rm = TRUE
)
```

Arguments

<code>object</code>	a waveband object.
<code>...</code>	currently ignored.
<code>w.length</code>	numeric vector of wavelengths (nm)
<code>range</code>	an R object on which <code>range()</code> returns a vector of length 2, with min and max wavelengths (nm).
<code>fill</code>	value to use as response for wavelengths outside the waveband range.
<code>span</code>	a peak is defined as an element in a sequence which is greater than all other elements within a window of width <code>span</code> centered at that element.
<code>wls.target</code>	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.
<code>unit.in</code>	the type of unit we assume as reference "energy" or "photon" based.
<code>annotations</code>	a character vector. For details please see section Plot Annotations.
<code>geom</code>	character The name of a ggplot geometry, currently only "area", "spct" and "line". The default NULL selects between them based on stacked.
<code>wb.trim</code>	logical.
<code>norm</code>	numeric normalization wavelength (nm) or character string "max" for normalization at the wavelength of highest peak.
<code>text.size</code>	numeric size of text in the plot decorations.
<code>ylim</code>	numeric y axis limits,
<code>object.label</code>	character The name of the object being plotted.
<code>na.rm</code>	logical.

Details

Note that scales are expanded so as to make space for the annotations. The object returned is a ggplot object, and can be further manipulated.

Value

a ggplot object.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or c("=", "") as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Note

Effectiveness spectra are plotted expressing the spectral effectiveness either as $1\text{mol}^{-1}\text{nm}$ photons of $1\text{J}^{-1}\text{nm}$ which can be selected through formal argument `unit.out`. The value of `unit.in` has no effect on the result when using BSWFs, as BSWFs are defined based on a certain base of expression, which is enforced. In contrast, for wavebands which only define a wavelength range, changing the assumed reference irradiance, changes the responsivity according to Planck's law.

This function creates a `response_spct` object from the `waveband` object and plots it. Unused arguments are passed along, which means that other plot aspects can be controlled by providing arguments for the plot method of the `response_spct` class.

See Also

[autoplot.response_spct](#), [waveband](#).

Other autoplot methods: [autoplot.calibration_spct\(\)](#), [autoplot.cps_spct\(\)](#), [autoplot.filter_spct\(\)](#), [autoplot.object_spct\(\)](#), [autoplot.raw_spct\(\)](#), [autoplot.reflector_spct\(\)](#), [autoplot.response_spct\(\)](#), [autoplot.source_spct\(\)](#), [set_annotations_default\(\)](#)

Examples

```
autoplot(waveband(c(400, 500)))
autoplot(waveband(c(400, 500)), geom = "spct")
```

autotitle	<i>Add title, subtitle and caption to a spectral plot</i>
-----------	---

Description

Add a title, subtitle and caption to a spectral plot based on automatically extracted metadata from an spectral object.

Usage

```
autotitle(  
  object,  
  object.label = deparse(substitute(object)),  
  annotations = "title",  
  time.format = NULL,  
  tz = "",  
  default.title = "title:objt"  
)
```

```
ggtitle_spect(  
  object,  
  object.label = deparse(substitute(object)),  
  annotations = "title",  
  time.format = NULL,  
  tz = "",  
  default.title = "title:objt"  
)
```

Arguments

<code>object</code>	generic_spect or generic_mspect The spectral object plotted.
<code>object.label</code>	character The name of the object being plotted.
<code>annotations</code>	character vector Annotations as described for <code>plot()</code> methods, values unrelated to title are ignored.
<code>time.format</code>	character Format as accepted by strptime .
<code>tz</code>	character time zone used in labels.
<code>default.title</code>	character vector The default used for <code>annotations = "title"</code> .

Value

The return value of `ggplot2::labs()`.

Title Annotations

metadata retrieved from object `object` is passed to `ggplot2::ggtitle()` as arguments for `title`, `subtitle` and `caption`. The specification for the title is passed as argument to `annotations`, and consists in the keyword `title` with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to `title`, `subtitle` and `caption`. The recognized keywords are: `"objt"`, `"class"`, `"what"`, `"when"`, `"where"`, `"how"`, `"inst.name"`, `"inst.sn"`, `"comment"` and `"none"` are recognized as modifiers to `"title"`; `"none"` is a placeholder. Default is `"title:objt"` or no title depending on the context.

Note

Method renamed as `autotitle()` to better reflect its function; `ggtitle_spct()` is deprecated but will remain available for backwards compatibility.

Examples

```
p <- ggplot(sun.spct) +
  geom_line()

p + autotitle(sun.spct)
p + autotitle(sun.spct, object.label = "The terrestrial solar spectrum")
p + autotitle(sun.spct, annotations = "title:objt:class")
p + autotitle(sun.spct, annotations = "title:where:when:how")

p <- ggplot(sun_evening.spct) +
  aes(linetype = spct.idx) +
  geom_line()

p + autotitle(sun_evening.spct, annotations = "title:objt:class")
p + autotitle(sun_evening.spct, annotations = "title:where:when:how")
p + autotitle(sun_evening.spct, annotations = "title:none:none:how")

p <- ggplot(sun_evening.mspect) +
  aes(linetype = spct.idx) +
  geom_line()

p + autotitle(sun_evening.mspect, annotations = "title:objt:class")
```

axis_labels_uk

Default text for axis labels

Description

Texts used by default for axis labels in plots are recalled from character vectors returned by these functions. The aim is that their default values can be easily changed or translated to other languages. They contain only the text part, but not symbols or units of expression.

Usage

```
axis_labels_uk(append = "", sep = "")

axis_labels_uk_comma()

axis_labels_none()

axis_labels()
```

Arguments

append character The string to be appended to each label,
sep character Passed to function paste as argument for parameter sep.

Details

By default `axis_labels()` contains a copy of `axis_labels_uk_comma()`. By assigning to this name a user function that returns a named character vector using the same names as those returned by these functions, it is possible to temporarily change the default texts.

Currently only UK English label texts are predefined and `axis_labels()` is a synonym of `axis_labels_uk()`.

Value

A character vector

Examples

```
axis_labels()[["w.length"]] # ending in a comma
axis_labels_uk()[["w.length"]] # no comma
axis_labels_none()[["w.length"]] # empty label
```

A_label

Absorbance axis labels

Description

Generate cps axis labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
A_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
```

```

    normalized = FALSE,
    axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
    Tfr.type
)

A_internal_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

A_total_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

```

Arguments

<code>unit.exponent</code>	integer
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .
<code>Tfr.type</code>	character, either "total" or "internal".

Value

a character string or an R expression.

Note

Default for `label.text` depends on the value passed as argument to `Tfr.type`.

Examples

```

A_label(Tfr.type = "internal")
A_label(Tfr.type = "total")
A_label(Tfr.type = "total", axis.symbols = FALSE)

```



```

A_internal_label()
A_internal_label(format = "R.expression", axis.symbols = FALSE)
A_internal_label(-3)
A_internal_label(format = "R.expression")
A_internal_label(format = "LaTeX")
A_internal_label(-3, format = "LaTeX")

```

```

A_total_label()
A_total_label(format = "R.expression", axis.symbols = FALSE)
A_total_label(-3)
A_total_label(format = "R.expression")
A_total_label(format = "LaTeX")
A_total_label(-3, format = "LaTeX")

```

black_or_white	<i>Chose black vs. white color based on weighted mean of RGB channels</i>
----------------	---

Description

Chose black or white color based on a color to be used as background. Usefull when using `geom_text` on top of tiles or bars, or `geom_label` with a variable fill.

Usage

```
black_or_white(colors, threshold = 0.45)
```

Arguments

colors	character A vector of color definitions.
threshold	numeric in range 0 to 1.

Examples

```

black_or_white("red")
black_or_white(colors()[1:10])

```

`color_chart`*Create a color checker chart*

Description

Color-checker-chart ggplot labelled with color names or with indexes of the colors in the vector passed as first argument.

Usage

```
color_chart(  
  colors = grDevices::colors(),  
  ncol = NULL,  
  use.names = NULL,  
  text.size = 2,  
  text.color = NULL,  
  grid.color = "white"  
)
```

Arguments

<code>colors</code>	character	A vector of color definitions.
<code>ncol</code>	integer	Number of column in the checker grid.
<code>use.names</code>	logical	Force use of names or indexes.
<code>text.size</code>	numeric	Size of the text labels drawn on each color tile.
<code>text.color</code>	character	Color definition, used for text on tiles.
<code>grid.color</code>	character	Color definition, used for grid lines between tiles.

Note

Default `text.color` uses `black_or_white()` to ensure enough contrast. Default for `use.names` depends on number of columns in the grid, indexes are used when columns are seven or more.

Examples

```
color_chart()  
color_chart(grep("dark", colors(), value = TRUE), text.size = 3.5)
```

counts_label	<i>Raw-counts axis labels</i>
--------------	-------------------------------

Description

Generate axis labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
counts_label(  
  unit.exponent = 3,  
  format = getOption("photobiology.math", default = "R.expression"),  
  label.text = axis_labels()[["counts"]],  
  scaled = FALSE,  
  normalized = FALSE,  
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)  
)
```

Arguments

unit.exponent	integer
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".

Value

a character string or an R expression.

Examples

```
counts_label()  
counts_label("R.expression")  
counts_label("LaTeX")
```

cps_label *Counts-per-second axis labels*

Description

Generate pixel response rate axis labels in cps units. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
cps_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["cps"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

Arguments

unit.exponent	integer
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".

Value

a character string or an R expression.

Examples

```
cps_label()
cps_label(3)
cps_label(format = "R.expression")
cps_label(format = "R.character")
cps_label(format = "LaTeX")
cps_label(3, format = "LaTeX")
```

exponent2prefix	<i>SI unit prefixes</i>
-----------------	-------------------------

Description

Convert SI unit prefixes into exponents of ten of multipliers and vice-versa.

Usage

```
exponent2prefix(
  exponent,
  char.set = getOption("photobiology.fancy.chars", default = "utf8")
)

exponent2factor(exponent = 0, if.zero.exponent = "1")

exponent2prefix_name(exponent)

prefix_name2exponent(name)

prefix2exponent(
  prefix,
  char.set = getOption("photobiology.fancy.chars", default = "utf8")
)

has_SI_prefix(exponent)

nearest_SI_exponent(exponent)
```

Arguments

exponent	numeric	The power of 10 of the unit multiplier.
char.set	character	How to encode Greek letters and other fancy characters in prefixes: "utf8", "ascii", "LaTeX". The difference between "utf8" and "ascii" is that the first uses UTF8 character "micro" (similar to Greek mu) and the second uses "u".
if.zero.exponent	character	string to return when exponent is equal to zero.
name	character	Long SI name of multiplier.
prefix	character	Unit prefix used for multiplier.

Note

To change the default `char.set`, set R option `"photobiology.fancy.chars"`. Implementation is based on a table of data and extensible to any alphabet supported by R character objects by expanding the table.

Examples

```
exponent2prefix(3)
exponent2prefix(0)
exponent2prefix(-6)
```

```
exponent2factor(3)
exponent2factor(0)
exponent2factor(0, NULL)
exponent2factor(0, "")
exponent2factor(-6)
```

 geom_spct

Spectral data plots.

Description

For each continuous x value, geom_spct displays a y interval. geom_spct is a special case of geom_area, where the minimum of the range is fixed to 0, but stacking is not enabled.

Usage

```
geom_spct(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A data frame. If specified, overrides the default data frame defined at the top level of the plot.
stat	The statistical transformation to use on the data for this layer, as a string.
position	Position adjustment, either as a string, or the result of a call to a position adjustment function.
na.rm	If FALSE (the default), removes missing values with a warning. If TRUE silently removes missing values.

<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Details

An spectrum plot is the analog of a line plot (see `geom_path`), and can be used to show how y varies over the range of x. The difference is that the area under the line is filled.

Aesthetics

See `geom_ribbon`

See Also

`geom_ribbon` for stacked areas, `geom_path` for lines (lines), `geom_point` for scatter plots.

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) + geom_spct()
```

ggplot

Create a new ggplot plot from spectral data.

Description

`ggplot()` initializes a `ggplot` object. It can be used to declare the input spectral object for a graphic and to optionally specify the set of plot aesthetics intended to be common throughout all subsequent layers unless specifically overridden.

Usage

```
## S3 method for class 'source_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  environment = parent.frame()
)
```

```
## S3 method for class 'response_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  environment = parent.frame()
)

## S3 method for class 'filter_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  plot.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  environment = parent.frame()
)

## S3 method for class 'reflector_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  plot.qty = NULL,
  environment = parent.frame()
)

## S3 method for class 'cps_spct'
ggplot(data, mapping = NULL, ..., range = NULL, environment = parent.frame())

## S3 method for class 'calibration_spct'
ggplot(data, mapping = NULL, ..., range = NULL, environment = parent.frame())

## S3 method for class 'raw_spct'
ggplot(data, mapping = NULL, ..., range = NULL, environment = parent.frame())

## S3 method for class 'object_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  plot.qty = getOption("photobiology.object.qty", default = "all"),
  environment = parent.frame()
)
```



```
)

## S3 method for class 'generic_spct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  spct_class,
  environment = parent.frame()
)

## S3 method for class 'generic_mspct'
ggplot(data, mapping = NULL, ..., range = NULL, environment = parent.frame())

## S3 method for class 'filter_mspct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  plot.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  environment = parent.frame()
)

## S3 method for class 'source_mspct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  environment = parent.frame()
)

## S3 method for class 'object_mspct'
ggplot(
  data,
  mapping = NULL,
  ...,
  range = NULL,
  plot.qty = getOption("photobiology.object.qty", default = ifelse(length(data) > 1L,
    "as.is", "all")),
  environment = parent.frame()
)
```

Arguments

<code>data</code>	Default spectrum dataset to use for plot. If not a spectrum, the methods used will be those defined in package <code>ggplot2</code> . See ggplot . If not specified, must be supplied in each layer added to the plot.
<code>mapping</code>	Default list of aesthetic mappings to use for plot. If not specified, in the case of spectral objects, a default mapping will be used.
<code>...</code>	Other arguments passed on to methods.
<code>range</code>	an R object on which <code>range()</code> returns a vector of length 2, with min and max wavelengths (nm).
<code>unit.out</code>	character string indicating type of units to use for plotting spectral irradiance or spectral response, "photon" or "energy".
<code>environment</code>	If a variable defined in the aesthetic mapping is not found in the data, <code>ggplot</code> will look for it in this environment. It defaults to using the environment in which <code>ggplot()</code> is called.
<code>plot.qty</code>	character string One of "transmittance", "absorptance" or "absorbance" for <code>filter_spct</code> objects, and in addition to these "reflectance", "all" or "as.is" for <code>object_spct</code> objects.
<code>spct_class</code>	character Class into which a <code>generic_spct</code> object will be converted before plotting. The column names in data should match those expected by the class constructor (see setGenericSpct); other arguments should be passed by name).

Details

`ggplot()` is typically used to construct a plot incrementally, using the `+` operator to add layers to the existing `ggplot` object. This is advantageous in that the code is explicit about which layers are added and the order in which they are added. For complex graphics with multiple layers, initialization with `ggplot` is recommended.

We show seven common ways to invoke `ggplot` for spectra and collections of spectra:

- `ggplot(spct)`
- `ggplot(spct, unit.out = <unit.to.use>)`
- `ggplot(spct, plot.qty = <quantity.to.plot>)`
- `ggplot(spct, range = <wavelength.range>)`
- `ggplot(spct) + aes(<other aesthetics>)`
- `ggplot(spct, aes(x, y, <other aesthetics>))`
- `ggplot(spct, aes())`

The first method is recommended if all layers use the same data and the same set of automatic default `x` and `y` aesthetics. The second, third and fourth use automatic default `x` and `y` aesthetics but first transform or trim the spectral data to be plotted. The fifth uses automatic default `x` and `y` aesthetics and adds mappings for other aesthetics. These patterns can be combined as needed. The sixth disables the use of a default automatic mapping, while the seventh delays the mapping of aesthetics and can be convenient when using different mappings for different geoms.

Object spectra

In the case of class `object_spct`, the arguments `"all"` and `"as.is"` if passed to `plot.qty`, indicate in the first case that the data are to be converted into long form, to allow stacking, while in the second case data is copied unchanged to the plot object. `"reflectance"` passed to `plot.qty` converts data into a `reflector_spct` object and `"absorbance"`, `"absorptance"` and `"reflectance"`, convert data into a `filter_spct`.

Collections of spectra

The method for collections of spectra accepts arguments for the same parameters as the corresponding methods for single spectra. Heterogeneous generic collections of spectra are not supported. When plotting collections of spectra the factor `spect.idx` contains as levels the names of the individual members of the collection, and can be mapped to aesthetics or used for faceting.

Note

Current implementation does not merge the default mapping with user supplied mapping. If user supplies a mapping, it is used as is, and variables should be present in the spectral object. In contrast, when using the default mapping, unit or quantity conversions are done on the fly when needed. To add to the default mapping, `aes()` can be used by itself to compose the `ggplot`. In all cases, except when an `object_spct` is converted into long form, the data member of the returned plot object retains its class and attributes.

`plot.qty` is ignored for reflectors.

Examples

```
ggplot(sun.spct) + geom_line()
ggplot(sun.spct, unit.out = "photon") + geom_line()

ggplot(yellow_gel.spct) + geom_line()
ggplot(yellow_gel.spct, plot.qty = "absorbance") + geom_line()

ggplot(Ler_leaf.spct) + facet_grid(~variable) + geom_line()
ggplot(Ler_leaf.spct) + aes(linetype = variable) + geom_line()
```

multipliers_label

Calibration multipliers axis labels

Description

Calibration multipliers axis labels. Output can be selected as character, expression (R default devices) or LaTeX (for `tikz` device).

Usage

```

multipliers_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["e.mult"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

```

Arguments

<code>unit.exponent</code>	integer
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .

Value

a character string or an R expression.

Examples

```

multipliers_label()
multipliers_label(3)
multipliers_label(format = "R.expression")
multipliers_label(format = "R.character")
multipliers_label(format = "LaTeX")
multipliers_label(3, format = "LaTeX")

```

multiplot

Multiple plot function

Description

Grid based; allows multiple plots arranged in a matrix and printed to any R device. ggplot objects can be passed in ..., or to plotlist (as a list of ggplot objects)

Usage

```
multiplot(
  ...,
  plotlist = NULL,
  ncol = 1,
  cols = ncol,
  layout = NULL,
  title = "",
  title.position = "left",
  title.fontsize = 12,
  title.fontfamily = "sans",
  title.fontface = "bold",
  title.colour = "black"
)
```

Arguments

<code>...</code>	one or more ggplot objects.
<code>plotlist</code>	list of ggplot objects.
<code>ncol, cols</code>	numerical Number of columns in layout.
<code>layout</code>	A numeric matrix specifying the layout. If present, 'cols' is ignored.
<code>title</code>	character vector Title of the composite plot.
<code>title.position</code>	numeric or character, the horizontal position of the title.
<code>title.fontsize</code>	numeric
<code>title.fontfamily</code>	character e.g. "sans", "serif", "mono".
<code>title.fontface</code>	character e.g. "plain", "bold", "italic", "bold.italic".
<code>title.colour</code>	character e.g. "black", "red".

Details

ggplot objects can be passed in `...`, or to `plotlist` (as a list of ggplot objects) If the layout is something like `matrix(c(1,2,3,3), nrow=2, byrow=TRUE)`, then plot 1 will go in the upper left, 2 will go in the upper right, and 3 will go all the way across the bottom.

Note

Modified from example by Winston Chang found in the Cookbook for R Licenced under CC BY-SA

References

<http://www.cookbook-r.com/>

Examples

```

multiplot(plot(sun.spct), plot(yellow_gel.spct), ncol = 1)
multiplot(plot(sun.spct), plot(yellow_gel.spct), ncol = 1,
          title = "The sun and a yellow filter")

```

plot.generic_spct *Deprecated plot methods*

Description

These plot() methods return a ggplot object with an annotated plot of an object of a class derived from generic_spct, of a class derived from generic_mspct or of an object of class waveband for which an autoplot() method exists. They are implemented as wrappers of autoplot(). The generic for plot() is defined by base R and specializations for objects of diverse classes are provided various packages and R itself. The generic for autoplot() is defined by package 'ggplot2'.

Usage

```

## S3 method for class 'generic_spct'
plot(x, ...)

## S3 method for class 'generic_mspct'
plot(x, ...)

## S3 method for class 'waveband'
plot(x, ...)

```

Arguments

x An R object derived from class generic_spct or derived from class generic_mspct.
... Named arguments passed to autoplot() methods.

Value

a ggplot object.

Deprecation warning!

These plot() specializations are provided for backwards compatibility, but all new or updated code should call autoplot() instead of plot() on objects of spectral and waveband classes defined in package 'photobiology'.

These methods add support for plot() specializations as these specializations were provided by package 'ggspectra' years ago, before 'ggplot2' had an autoplot() generic. As these methods return ggplots autoplot is a more suitable name for them.

See Also

[autoplot.calibration_spct](#), [autoplot.cps_spct](#), [autoplot.filter_spct](#), [autoplot.raw_spct](#), [autoplot.response_spct](#), [autoplot.source_spct](#) and [autoplot.waveband](#).

Examples

```
plot(sun.spct) # deprecated syntax, to be avoided
autoplot(sun.spct) # current syntax, to be used
```

Rfr_label

Reflectance axis labels

Description

Generate spectral reflectance labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
Rfr_label(
  unit.exponent = ifelse(pc.out, -2, 0),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  Rfr.type
)
```

```
Rfr_specular_label(
  unit.exponent = ifelse(pc.out, -2, 0),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE)
)
```

Arguments

```
unit.exponent  integer
format          character string, "R", "R.expression", "R.character", or "LaTeX".
label.text     character Textual portion of the labels.
```

scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in nanometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
pc.out	logical, if TRUE use percent as default instead of fraction of one.
Rfr.type	character, either "total" or "specular".

Value

a character string or an R expression.

Note

Default for label.text depends on the value passed as argument to Rfr.type.

Examples

```
Rfr_label(Rfr.type = "specular")
Rfr_label(Rfr.type = "total")

Rfr_specular_label()
Rfr_specular_label(axis.symbols = FALSE)
Rfr_specular_label(-2)
Rfr_specular_label(-3)
Rfr_specular_label(format = "R.expression")
Rfr_specular_label(format = "LaTeX")
Rfr_specular_label(-3, format = "LaTeX")
```

s.e.irrad_label *Spectral irradiance axis labels*

Description

Generate axis labels for spectral irradiance in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
s.e.irrad_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.irrad"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
```



```

)

s.q.irrad_label(
  unit.exponent = ifelse(normalized, 0, -6),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.irrad"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

```

Arguments

unit.exponent	integer.
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".

Value

a character string or an R expression.

Examples

```

str(s.e.irrad_label())
str(s.e.irrad_label(axis.symbols = FALSE))
str(s.e.irrad_label(format = "R.expression"))
str(s.e.irrad_label(format = "LaTeX"))

```

```

str(s.q.irrad_label())
str(s.q.irrad_label(axis.symbols = FALSE))
str(s.q.irrad_label(format = "R.expression"))
str(s.q.irrad_label(format = "LaTeX"))

```

s.e.response_label	<i>spectral response and action axis labels</i>
--------------------	---

Description

Generate axis labels for response or action spectra in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
s.e.response_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.response"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
s.q.response_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.response"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
s.e.action_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.action"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
s.q.action_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.action"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

Arguments

unit.exponent	integer
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".

Value

a character string or an R expression.

Examples

```
s.e.response_label()
s.e.response_label(format = "R.expression")
s.e.response_label(format = "R.character")
s.e.response_label(format = "LaTeX")
s.e.response_label(unit.exponent = 3, format = "R.character")
s.q.response_label(format = "R.character")
s.e.action_label(format = "R.character")
s.q.action_label(format = "R.character")
s.e.response_label(scaled = TRUE)
s.e.response_label(scaled = TRUE, format = "R.character")
s.e.response_label(scaled = TRUE, format = "LaTeX")
s.e.response_label(normalized = 300)
s.e.response_label(normalized = 300, format = "R.character")
s.e.response_label(normalized = 300, format = "LaTeX")
s.q.response_label(scaled = TRUE)
s.q.response_label(scaled = TRUE, format = "R.character")
s.q.response_label(scaled = TRUE, format = "LaTeX")
s.q.response_label(normalized = 300)
s.q.response_label(normalized = 300, format = "R.character")
s.q.response_label(normalized = 300, format = "LaTeX")
```

scale_x_energy_eV_continuous

Energy per photon x-scale

Description

Scale x continuous with defaults suitable for wavelengths expressed as energy per photon [eV] or [J].

Usage

```
scale_x_energy_eV_continuous(
  unit.exponent = 0,
  name = w_energy_eV_label(unit.exponent = unit.exponent, label.text = label.text,
    axis.symbols = axis.symbols),
  breaks = scales::pretty_breaks(n = 7),
  labels = SI_pl_format(exponent = unit.exponent),
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)
```

```

scale_x_energy_J_continuous(
  unit.exponent = -18,
  name = w_energy_J_label(unit.exponent = unit.exponent, label.text = label.text,
    axis.symbols = axis.symbols),
  breaks = scales::pretty_breaks(n = 7),
  labels = SI_pl_format(exponent = unit.exponent),
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>breaks</code>	The positions of ticks or a function to generate them.
<code>labels</code>	The tick labels or a function to generate them from the tick positions.
<code>label.text</code>	character Textual portion of the labels.
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .
<code>...</code>	other named arguments passed to <code>scale_y_continuous</code>

Details

This scale automates the generation of axis labels when the variable mapped to the x aesthetic contains numeric values for wavelengths expressed as energy per photon. This is **not** how spectral data are stored in all the packages of the R for Photobiology suite and can be used in plots built with `ggplot2()` with explicit mapping using a conversion function. If desired, a secondary axis can be added manually as described in [sec_axis](#).

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```

ggplot(sun.spct, aes(x = wl2energy(w.length, unit = "joule"), y = s.e.irrad)) +
  geom_line() +
  scale_x_energy_J_continuous()

ggplot(sun.spct, aes(x = wl2energy(w.length, unit = "joule"), y = s.e.irrad)) +
  geom_line() +
  scale_x_energy_J_continuous(unit.exponent = -19)

ggplot(sun.spct, aes(x = wl2energy(w.length, unit = "eV"), y = s.e.irrad)) +
  geom_line() +
  scale_x_energy_eV_continuous()

```

```
ggplot(sun.spct, aes(x = wl2energy(w.length, unit = "eV"), y = s.e.irrad)) +
  geom_line() +
  scale_x_energy_eV_continuous(unit.exponent = -3)
```

scale_x_frequency_continuous

Frequency x-scale

Description

Scale x continuous with defaults suitable for wavelengths expressed as frequencies [Hz].

Usage

```
scale_x_frequency_continuous(
  unit.exponent = 12,
  name = w_frequency_label(unit.exponent = unit.exponent, label.text = label.text,
    axis.symbols = axis.symbols),
  breaks = scales::pretty_breaks(n = 7),
  labels = SI_pl_format(exponent = unit.exponent),
  label.text = axis_labels()[["freq"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)
```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
breaks	The positions of ticks or a function to generate them.
labels	The tick labels or a function to generate them from the tick positions.
label.text	character Textual portion of the labels.
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
...	other named arguments passed to scale_y_continuous

Details

This scale automates the generation of axis labels when the variable mapped to the x aesthetic contains numeric values for wavelengths expressed as frequency. This is **not** how spectral data are stored in the packages of the R for Photobiology suite and can be only used in plots built with `ggplot2()` with explicit mapping using a conversion function. If desired, a secondary axis can be added manually as described in [sec_axis](#).

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```
ggplot(sun.spct, aes(x = wl2frequency(w.length), y = s.e.irrad)) +
  geom_line() +
  scale_x_frequency_continuous()
```

```
ggplot(sun.spct, aes(x = wl2frequency(w.length), y = s.e.irrad)) +
  geom_line() +
  scale_x_frequency_continuous(14)
```

scale_x_wavenumber_continuous

Wavenumber x-scale

Description

Scale x continuous with defaults suitable for wavelengths expressed as wavenumbers [m^{-2}].

Usage

```
scale_x_wavenumber_continuous(
  unit.exponent = -6,
  name = w_number_label(unit.exponent = unit.exponent, label.text = label.text,
    axis.symbols = axis.symbols),
  breaks = scales::pretty_breaks(n = 7),
  labels = SI_pl_format(exponent = -unit.exponent),
  label.text = axis_labels()[["w.number"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)
```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
breaks	The positions of ticks or a function to generate them.
labels	The tick labels or a function to generate them from the tick positions.
label.text	character Textual portion of the labels.
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
...	other named arguments passed to scale_y_continuous

Details

This scale automates the generation of axis labels when the variable mapped to the x aesthetic contains numeric values for wavelengths expressed wavenumbers. This is **not** how spectral data are stored in all the packages of the R for Photobiology suite and can be used in plots built with `ggplot2()` with explicit mapping using a conversion function. If desired, a secondary axis can be added manually as described in [sec_axis](#).

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```
ggplot(sun.spct, aes(x = wl2wavenumber(w.length), y = s.e.irrad)) +
  geom_line() +
  scale_x_wavenumber_continuous()

ggplot(sun.spct, aes(x = wl2wavenumber(w.length), y = s.e.irrad)) +
  geom_line() +
  scale_x_wavenumber_continuous(unit.exponent = -5)
```

scale_x_wl_continuous *Wavelength x-scale*

Description

Scale x continuous with defaults suitable for wavelengths in nanometres.

Usage

```
scale_x_wl_continuous(
  unit.exponent = -9,
  name = w_length_label(unit.exponent = unit.exponent, label.text = label.text,
    axis.symbols = axis.symbols),
  breaks = scales::pretty_breaks(n = 7),
  labels = SI_pl_format(exponent = unit.exponent + 9),
  label.text = axis_labels()[["w.length"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)
```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>breaks</code>	The positions of ticks or a function to generate them.

labels	The tick labels or a function to generate them from the tick positions.
label.text	character Textual portion of the labels.
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
...	other named arguments passed to scale_y_continuous

Details

This scale automates the generation of axis labels when the variable mapped to the x aesthetic contains numeric values for wavelengths expressed in nanometres. This is how spectral data are stored in all the packages of the R for Photobiology suite, including the the expected data by the autoplot() methods defined in 'ggspectra'.

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous()

ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(unit.exponent = -6)

ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(label.text = "Longitud de onda,")

autoplot(sun.spct) +
  scale_x_wl_continuous(label.text = "Longitud de onda,",
                        unit.exponent = -6)
```

scale_y_Afr_continuous

Absorptance y-scale

Description

Scale y continuous with defaults suitable for spectral absorbance.

Usage

```

scale_y_Afr_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Afr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.Afr"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  ...
)

```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
labels	The tick labels or a function to generate them.
limits	One of NULL for default based on data range, a numeric vector of length two (NA allowed) or a function that accepts the data-based limits as argument and returns new limits.
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
pc.out	logical, if TRUE use percent as default instead of fraction of one.
...	other named arguments passed to scale_y_continuous

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```

Afr_as_default()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Afr_continuous() +
  scale_x_wl_continuous()

```

```

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Afr_continuous(unit.exponent = -2) +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Afr_continuous(unit.exponent = -3) +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Afr_continuous(axis.symbols = FALSE) +
  scale_x_wl_continuous(axis.symbols = FALSE)

unset_filter_qty_default()

```

scale_y_A_continuous *Absorbance y-scale*

Description

Scale y continuous with defaults suitable for spectral absorbance.

Usage

```

scale_y_A_continuous(
  unit.exponent = 0,
  name = A_label(unit.exponent = unit.exponent, format = format, label.text = label.text,
    scaled = scaled, normalized = round(normalized, 1), axis.symbols = axis.symbols,
    Tfr.type = Tfr.type),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  Tfr.type,
  ...
)

scale_y_A_internal_continuous(
  unit.exponent = 0,
  name = A_label(unit.exponent = unit.exponent, format = format, label.text = label.text,
    scaled = scaled, normalized = round(normalized, 1), axis.symbols = axis.symbols,
    Tfr.type = "internal"),

```

```

    labels = SI_pl_format(exponent = unit.exponent),
    format = getOption("photobiology.math", default = "R.expression"),
    label.text = NULL,
    scaled = FALSE,
    normalized = FALSE,
    axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
    ...
)

scale_y_A_total_continuous(
  unit.exponent = 0,
  name = A_label(unit.exponent = unit.exponent, format = format, label.text = label.text,
    scaled = scaled, normalized = round(normalized, 1), axis.symbols = axis.symbols,
    Tfr.type = "total"),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>labels</code>	The tick labels or a function to generate them.
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .
<code>Tfr.type</code>	character, either "total" or "internal".
<code>...</code>	other named arguments passed to <code>scale_y_continuous</code>

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```

ggplot(yellow_gel.spct, plot.qty = "absorbance") +
  geom_line() +
  scale_y_A_continuous(Tfr.type = getTfrType(yellow_gel.spct)) +
  scale_x_wl_continuous()

```

```

ggplot(yellow_gel.spct, plot.qty = "absorbance") +
  geom_line() +
  scale_y_A_internal_continuous() +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct, plot.qty = "absorbance") +
  geom_line() +
  scale_y_A_total_continuous() +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct, plot.qty = "absorbance") +
  geom_line() +
  scale_y_A_total_continuous(axis.symbols = FALSE) +
  scale_x_wl_continuous(axis.symbols = FALSE)

```

scale_y_counts_continuous

Raw-counts y-scale

Description

Scale y continuous with defaults suitable for raw detector counts.

Usage

```

scale_y_counts_continuous(
  unit.exponent = ifelse(normalized, 0, 3),
  name = counts_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["counts"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

scale_y_counts_tg_continuous(
  unit.exponent = ifelse(normalized, 0, 3),
  name = counts_label(unit.exponent = 0, format = format, label.text = label.text, scaled
    = scaled, normalized = round(normalized, 1), axis.symbols = axis.symbols),
  labels = SI_tg_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["counts"]],

```

```

    scaled = FALSE,
    normalized = FALSE,
    axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
    ...
  )

```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>labels</code>	The tick labels or a function to generate them.
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .
<code>...</code>	other named arguments passed to <code>scale_y_continuous</code>

Note

This function only alters default arguments values for `name` and `labels`, please, see documentation for [scale_continuous](#) for other parameters.

Examples

```

ggplot(white_led.raw_spct) +
  geom_line() +
  scale_y_counts_continuous() +
  scale_x_wl_continuous()

ggplot(white_led.raw_spct) +
  geom_line() +
  scale_y_counts_continuous(unit.exponent = 0) +
  scale_x_wl_continuous()

ggplot(white_led.raw_spct) +
  geom_line() +
  scale_y_counts_tg_continuous() +
  scale_x_wl_continuous()

ggplot(white_led.raw_spct) +
  geom_line() +
  scale_y_counts_tg_continuous(unit.exponent = 0) +
  scale_x_wl_continuous()

norm_led.raw_spct <- normalize(white_led.raw_spct[, 1:2], norm = "max")

ggplot(norm_led.raw_spct) +

```

```

geom_line() +
scale_y_counts_continuous(normalized = getNormalized(norm_led.raw_spct)) +
scale_x_wl_continuous()

ggplot(norm_led.raw_spct) +
geom_line() +
scale_y_counts_tg_continuous(normalized = getNormalized(norm_led.raw_spct)) +
scale_x_wl_continuous()

```

scale_y_cps_continuous

Counts-per-second y-scale

Description

Scale y continuous with defaults suitable for raw detector counts.

Usage

```

scale_y_cps_continuous(
  unit.exponent = 0,
  name = cps_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["cps"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
labels	The tick labels or a function to generate them.
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
...	other named arguments passed to scale_y_continuous

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```
ggplot(white_led.cps_spct) +
  geom_line() +
  scale_y_cps_continuous() +
  scale_x_wl_continuous()

ggplot(white_led.cps_spct) +
  geom_line() +
  scale_y_cps_continuous(3) +
  scale_x_wl_continuous()

ggplot(white_led.cps_spct * 1e-4) +
  geom_line() +
  scale_y_cps_continuous(scaled = TRUE) +
  scale_x_wl_continuous()

norm_led.cps_spct <- normalize(white_led.cps_spct, norm = "max")

ggplot(norm_led.cps_spct) +
  geom_line() +
  scale_y_cps_continuous(normalized = getNormalized(norm_led.cps_spct)) +
  scale_x_wl_continuous()
```

scale_y_multipliers_continuous
Calibration multipliers y-scale

Description

Scale y continuous with defaults suitable for raw the calibration multipliers used to convert pixel response rate (counts per second) into energy irradiance units.

Usage

```
scale_y_multipliers_continuous(
  unit.exponent = 0,
  name = multipliers_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["e.mult"]],
  scaled = FALSE,
```

```

normalized = FALSE,
axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
...
)

```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>labels</code>	The tick labels or a function to generate them.
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .
<code>...</code>	other named arguments passed to <code>scale_y_continuous</code>

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

scale_y_Rfr_continuous

Reflectance y-scale

Description

Scale y continuous with defaults suitable for spectral reflectance.

Usage

```

scale_y_Rfr_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Rfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Rfr.type = Rfr.type),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),

```



```

    Rfr.type,
    ...
)

scale_y_Rfr_specular_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Rfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Rfr.type = "specular"),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  ...
)

scale_y_Rfr_total_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Rfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Rfr.type = "total"),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  ...
)

```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
labels	The tick labels or a function to generate them.
limits	One of NULL for default based on data range, a numeric vector of length two (NA allowed) or a function that accepts the data-based limits as argument and returns new limits.
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.

normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
pc.out	logical, if TRUE use percent as default instead of fraction of one.
Rfr.type	character, either "total" or "spcular".
...	other named arguments passed to scale_y_continuous

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```
ggplot(Ler_leaf_rflt.spct) +
  geom_line() +
  scale_y_Rfr_continuous(Rfr.type = getRfrType(Ler_leaf_rflt.spct)) +
  scale_x_wl_continuous()

ggplot(Ler_leaf_rflt.spct) +
  geom_line() +
  scale_y_Rfr_continuous(unit.exponent = -2,
                        Rfr.type = getRfrType(Ler_leaf_rflt.spct)) +
  scale_x_wl_continuous()

ggplot(Ler_leaf_rflt.spct) +
  geom_line() +
  scale_y_Rfr_continuous(unit.exponent = -3,
                        Rfr.type = getRfrType(Ler_leaf_rflt.spct)) +
  scale_x_wl_continuous()

ggplot(Ler_leaf_rflt.spct) +
  geom_line() +
  scale_y_Rfr_specular_continuous() +
  scale_x_wl_continuous()

ggplot(Ler_leaf_rflt.spct) +
  geom_line() +
  scale_y_Rfr_specular_continuous(axis.symbols = FALSE) +
  scale_x_wl_continuous(axis.symbols = FALSE)
```

scale_y_s.e.irrad_continuous

Spectral irradiance y-scale

Description

Scale y continuous with defaults suitable for raw detector counts.

Usage

```

scale_y_s.e.irrad_continuous(
  unit.exponent = 0,
  name = s.e.irrad_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.irrad"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

```

scale_y_s.q.irrad_continuous(
  unit.exponent = ifelse(normalized, 0, -6),
  name = s.q.irrad_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.irrad"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

```

scale_y_s.e.irrad_log10(
  unit.exponent = 0,
  name = s.e.irrad_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.irrad"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

```

scale_y_s.q.irrad_log10(
  unit.exponent = ifelse(normalized, 0, -6),
  name = s.q.irrad_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),

```

```

labels = SI_pl_format(exponent = unit.exponent),
format = getOption("photobiology.math", default = "R.expression"),
label.text = axis_labels()[["s.q.irrad"]],
scaled = FALSE,
normalized = FALSE,
axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
...
)

```

Arguments

<code>unit.exponent</code>	integer
<code>name</code>	The name of the scale, used for the axis-label.
<code>labels</code>	The tick labels or a function to generate them.
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>scaled</code>	logical If TRUE relative units are assumed.
<code>normalized</code>	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the default name.
<code>...</code>	other named arguments passed to <code>scale_y_continuous</code>

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```

ggplot(sun.spct) +
  geom_line() +
  scale_y_s.e.irrad_continuous() +
  scale_x_wl_continuous()

ggplot(sun.spct) +
  geom_line() +
  scale_y_s.e.irrad_continuous(label.text = "") +
  scale_x_wl_continuous()

ggplot(sun.spct) +
  geom_line() +
  scale_y_s.e.irrad_continuous(label.text = "Irradiancia spectral,") +
  scale_x_wl_continuous(label.text = "Longitud de onda,")

ggplot(sun.spct) +
  geom_line() +
  scale_y_s.e.irrad_continuous(unit.exponent = -1) +
  scale_x_wl_continuous()

ggplot(sun.spct, unit.out = "photon") +
  geom_line() +

```

```

scale_y_s.q.irrad_continuous() +
scale_x_wl_continuous()

ggplot(clip_wl(sun.spct, c(295, NA))) +
  geom_line() +
  scale_y_s.e.irrad_log10() +
  scale_x_wl_continuous()

ggplot(clip_wl(sun.spct, c(295, NA)),
  unit.out = "photon") +
  geom_line(na.rm = TRUE) +
  scale_y_s.q.irrad_log10() +
  scale_x_wl_continuous()

photon_as_default()
normalized_sun.spct <- normalize(sun.spct)
ggplot(normalized_sun.spct) +
  geom_line(na.rm = TRUE) +
  scale_y_s.q.irrad_continuous(normalized =
                                getNormalized(normalized_sun.spct)) +
  scale_x_wl_continuous()

unset_radiation_unit_default()

```

scale_y_s.e.response_continuous

Spectral response and action y-scales

Description

Scale y continuous with defaults suitable for response and action spectra.

Usage

```

scale_y_s.e.response_continuous(
  unit.exponent = 0,
  name = s.e.response_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = -unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.response"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

```

scale_y_s.q.response_continuous(
  unit.exponent = 0,
  name = s.q.response_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = -unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.response"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

scale_y_s.e.action_continuous(
  unit.exponent = 0,
  name = s.e.action_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = -unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.e.action"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

scale_y_s.q.action_continuous(
  unit.exponent = 0,
  name = s.q.action_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols),
  labels = SI_pl_format(exponent = -unit.exponent),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["s.q.action"]],
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  ...
)

```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
labels	The tick labels or a function to generate them.
format	character string, "R", "R.expression", "R.character", or "LaTeX".

label.text	character	Textual portion of the labels.
scaled	logical	If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric	Normalization wavelength in manometers (nm).
axis.symbols	logical	If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
...		other named arguments passed to scale_y_continuous

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#).

Examples

```

ggplot(ccd.spct) +
  geom_line() +
  scale_y_s.e.action_continuous() + # per joule
  scale_x_wl_continuous()

ggplot(ccd.spct) +
  geom_line() +
  scale_y_s.e.response_continuous() + # per joule
  scale_x_wl_continuous()

ggplot(ccd.spct) +
  geom_line() +
  scale_y_s.e.response_continuous(unit.exponent = 6) + # per mega joule
  scale_x_wl_continuous()

ggplot(ccd.spct, unit.out = "photon") +
  geom_line() +
  scale_y_s.q.response_continuous() + # per mol
  scale_x_wl_continuous()

ggplot(ccd.spct, unit.out = "photon") +
  geom_line() +
  scale_y_s.q.response_continuous(unit.exponent = 3) + # per 1000 moles
  scale_x_wl_continuous()

norm_ccd.spct <- normalize(ccd.spct, norm = "max")
ggplot(norm_ccd.spct) +
  geom_line() +
  scale_y_s.e.response_continuous(normalized = getNormalized(norm_ccd.spct)) +
  scale_x_wl_continuous()

photon_as_default()

norm_ccd.spct <- normalize(ccd.spct, norm = "max")
ggplot(norm_ccd.spct) +
  geom_line() +
  scale_y_s.q.response_continuous(normalized = getNormalized(norm_ccd.spct)) +
  scale_x_wl_continuous()

```

```

ggplot(norm_ccd.spct) +
  geom_line() +
  scale_y_s.q.response_continuous(unit.exponent = 2,
                                normalized = getNormalized(norm_ccd.spct)) +
  scale_x_wl_continuous()

unset_radiation_unit_default()

```

scale_y_Tfr_continuous

Transmittance y-scale

Description

Scale y continuous with defaults suitable for spectral transmittance.

Usage

```

scale_y_Tfr_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Tfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Tfr.type = Tfr.type),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  Tfr.type,
  ...
)

scale_y_Tfr_internal_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Tfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Tfr.type = "internal"),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,

```



```

axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
pc.out = getOption("ggspectra.pc.out", default = FALSE),
...
)

scale_y_Tfr_total_continuous(
  unit.exponent = ifelse(pc.out, -2, 0),
  name = Tfr_label(unit.exponent = unit.exponent, format = format, label.text =
    label.text, scaled = scaled, normalized = round(normalized, 1), axis.symbols =
    axis.symbols, Tfr.type = "total"),
  labels = SI_pl_format(exponent = unit.exponent),
  limits = c(0, 1),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  ...
)

```

Arguments

unit.exponent	integer
name	The name of the scale, used for the axis-label.
labels	The tick labels or a function to generate them.
limits	One of NULL for default based on data range, a numeric vector of length two (NA allowed) or a function that accepts the data-based limits as argument and returns new limits.
format	character string, "R", "R.expression", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).
axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
pc.out	logical, if TRUE use percent as default instead of fraction of one.
Tfr.type	character, either "total" or "internal".
...	other named arguments passed to scale_y_continuous

Note

This function only alters two default arguments, please, see documentation for [scale_continuous](#)

Examples

```

Tfr_as_default()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Tfr_continuous(Tfr.type = getTfrType(yellow_gel.spct)) +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Tfr_continuous(unit.exponent = -2,
                        Tfr.type = getTfrType(yellow_gel.spct)) +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Tfr_continuous(unit.exponent = -3,
                        Tfr.type = getTfrType(yellow_gel.spct)) +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Tfr_total_continuous() +
  scale_x_wl_continuous()

ggplot(yellow_gel.spct) +
  geom_line() +
  scale_y_Tfr_total_continuous(axis.symbols = FALSE) +
  scale_x_wl_continuous(axis.symbols = FALSE)

unset_filter_qty_default()

```

sec_axis_w_number *Secondary axes for wavelengths*

Description

Secondary axes for wavelength data in nanometres. With suitable scaling and name (axis label) for frequency, wave number, photon energy and wavelength.

Usage

```

sec_axis_w_number(
  unit.exponent = -6,
  label.text = axis_labels()[["w.number"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

```

```

sec_axis_w_frequency(
  unit.exponent = 12,
  label.text = axis_labels()[["freq"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

sec_axis_energy_eV(
  unit.exponent = 0,
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

sec_axis_energy_J(
  unit.exponent = -18,
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

sec_axis_wl(
  unit.exponent = -9,
  label.text = axis_labels()[["w.length"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

```

Arguments

<code>unit.exponent</code>	integer The exponent on base 10 of the scale multiplier used for the axis labels, e.g., 3 for 10^3 or k .
<code>label.text</code>	character Textual portion of the labels.
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .

Details

These secondary axis functions can be used only when the x aesthetic is mapped to a numerical variable containing wavelength values expressed in nanometres. They can be used to add a secondary x axis to plots created using `ggplot()` or `autoplot()`.

See Also

the default text used for quantity names are most easily changed by resetting all the defaults once as explained in [axis_labels_uk](#), even if it is possible to override them also in each call.

Examples

```

ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(sec.axis = sec_axis_w_number())

```

```

# Secondary axes can be added to plots built with autoplot() methods
autoplot(sun.spct) +
  scale_x_wl_continuous(sec.axis = sec_axis_w_number())

# Using 'ggplot2' scale
ggplot(sun.spct) +
  geom_line() +
  scale_x_continuous(name = w_length_label(),
                    sec.axis = sec_axis_w_number())

# change scale multipliers, SI defined
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(-6, sec.axis = sec_axis_w_number(-3))

# change scale multipliers, not SI defined (best avoided)
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(-8, sec.axis = sec_axis_w_number(-4))

# Change quantity name to Spanish
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(label.text = "Longitud de onda,",
                      sec.axis = sec_axis_w_frequency(label.text = "Frecuencia,"))

# Frequency in secondary axis
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(sec.axis = sec_axis_w_frequency())

# Energy (per photon) in atto joules
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(sec.axis = sec_axis_energy_J())

# Energy (per photon) in electron volts
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(sec.axis = sec_axis_energy_eV())

# Secondary axis with wavelength using a different scale factor
ggplot(sun.spct) +
  geom_line() +
  scale_x_wl_continuous(sec.axis = sec_axis_wl(-6))

# Secondary axes can be added to plots built with autoplot() methods
autoplot(sun.spct) +
  scale_x_wl_continuous(sec.axis = sec_axis_wl(-6))

```

`set_annotatations_default`*Set defaults for autoplot annotations*

Description

Set R options used when plotting spectra. Option "photobiology.plot.annotations" is used as default argument to formal parameter annotations and option "photobiology.plot.bands" is used as default argument to formal parameter w.band in all the autoplot() methods exported from package 'ggspectra'. These convenience functions make it easier to edit these two option which are stored as a vector of characters strings and a list of waveband objects, respectively.

Usage

```
set_annotatations_default(annotations = NULL)
```

```
set_w.band_default(w.band = NULL)
```

Arguments

annotations	character vector Annotations to add or remove from defaults used by the autoplot() methods defined in this package..
w.band	a single waveband object or a list of waveband objects.

Value

Previous value of option "photobiology.plot.annotations", returned invisibly.

Plot Annotations

The recognized annotation names are: "summaries", "peaks", "peak.labels", "valleys", "valley.labels", "wls", "wls.labels", "colour.guide", "color.guide", "boxes", "segments", "labels". In addition, "+" is interpreted as a request to add to the already present default annotations, "-" as request to remove annotations and "=" or missing "+" and "-" as a request to reset annotations to those requested. If used, "+", "-" or "=" must be the first member of a character vector, and followed by one or more of the names given above. To simultaneously add and remove annotations one can pass a list containing character vectors each assembled as described. The vectors are applied in the order they appear in the list. To disable all annotations pass "" or c("=", "") as argument. Adding a variation of an annotation already present, replaces the existing one automatically: e.g., adding "peak.labels" replaces "peaks" if present.

Title Annotations

metadata retrieved from object object is passed to ggplot2::ggtitle() as arguments for title, subtitle and caption. The specification for the title is passed as argument to annotations, and consists in the keyword title with optional modifiers selecting the kind of metadata to use, separated by colons. Up to three keywords separated by colons are accepted, and correspond to title,

subtitle and caption. The recognized keywords are: "objt", "class", "what", "when", "where", "how", "inst.name", "inst.sn", "comment" and "none" are recognized as modifiers to "title"; "none" is a placeholder. Default is "title:objt" or no title depending on the context.

Note

The syntax used and behaviour are the same as for the annotations parameter of the `autoplot()` methods for spectra, but instead of affecting a single plot, `set_annotations_default()` changes the default used for subsequent calls to `autoplot()`.

See Also

Other autoplot methods: `autoplot.calibration_spct()`, `autoplot.cps_spct()`, `autoplot.filter_spct()`, `autoplot.object_spct()`, `autoplot.raw_spct()`, `autoplot.reflector_spct()`, `autoplot.response_spct()`, `autoplot.source_spct()`, `autoplot.waveband()`

SI_pl_format

Formatter for plain labels discounting for SI multipliers

Description

The labels generated represent numbers rescaled to compensate for a change in unit's by a factor of ten or by a power of ten.

Usage

```
SI_pl_format(exponent = 0, digits = 3, ...)
```

```
SI_plain(x, exponent = 0, digits = 3, ...)
```

Arguments

exponent	numeric Power of 10 to use as multiplier
digits	number of significant digits to show
...	other arguments passed on to <code>format</code>
x	a numeric vector to format

Value

a function with single parameter x, a numeric vector, that returns a character vector

Examples

```
SI_pl_format()(1:10)
SI_pl_format()(runif(10))
SI_pl_format(exponent = 2)(runif(10))
SI_plain(1:10)
SI_plain(runif(10))
SI_plain(runif(10), digits = 2)
```

SI_tg_format	<i>Formatter for tagged labels using SI multipliers</i>
--------------	---

Description

The labels generated represent the same numbers, but with trailing zeros removed/added and compensated by attaching to each label an SI multiplier "prefix".

Usage

```
SI_tg_format(exponent = 0, digits = 3, ...)
```

```
SI_tagged(x, exponent = 0, digits = 3, ...)
```

Arguments

exponent	numeric Power of 10 to use as multiplier
digits	number of significant digits to show
...	other arguments passed on to format
x	a numeric vector to format

Value

a function with single parameter x, a numeric vector, that returns a character vector

Note

If the exponent passed has no SI prefix defined, the exponent will be adjusted to match one.

Examples

```
SI_tg_format()(1:10)
SI_tg_format()(runif(10))
SI_tg_format(exponent = 2)(runif(10))
SI_tagged(1:10)
SI_tagged(runif(10))
SI_tagged(runif(10), digits = 2)
```

stat_color

Calculate colours from wavelength.

Description

stat_color computes color definitions according to human vision.

Usage

```
stat_color(
  mapping = NULL,
  data = NULL,
  geom = "point",
  chroma.type = "CMF",
  position = "identity",
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

The original data frame with a variable with color definitions added.

Computed variable

wl.color color corresponding to x-value giving wavelength in nanometres.

Default aesthetics

Set by the statistic and available to geoms.

color ..wl.color..

fill ..wl.color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

See Also

`color_of`, which is used internally.

Other stats functions: `stat_find_qtys()`, `stat_find_wls()`, `stat_label_peaks()`, `stat_peaks()`, `stat_spikes()`, `stat_wb_box()`, `stat_wb_column()`, `stat_wb_contribution()`, `stat_wb_hbar()`, `stat_wb_irrad()`, `stat_wb_label()`, `stat_wb_mean()`, `stat_wb_relative()`, `stat_wb_sirrad()`, `stat_wb_total()`, `stat_wl_strip()`, `stat_wl_summary()`

Examples

```
ggplot(sun.spct) + geom_line() +
  stat_color() + scale_color_identity()
```

stat_find_qtys	<i>Find quantity value for target wavelength value.</i>
----------------	---

Description

`stat_find_qtys` finds at which y positions values equal to an x target are located.

Usage

```
stat_find_qtys(
  mapping = NULL,
  data = NULL,
  geom = "point",
  target = "half.maximum",
  interpolate = TRUE,
  chroma.type = "CMF",
```

```

  label.fmt = "%.3g",
  x.label.fmt = label.fmt,
  y.label.fmt = label.fmt,
  position = "identity",
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
target	numeric value indicating the spectral quantity value for which wavelengths are to be searched and interpolated if need. The character string "half.maximum" is also accepted as argument.
interpolate	logical Indicating whether the nearest wavelength value in x should be returned or a value calculated by linear interpolation between wavelength values straddling the target.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for converting values into character strings by means of function sprintf .
x.label.fmt	character string giving a format definition for converting x -values into character strings by means of function sprintf .
y.label.fmt	character string giving a format definition for converting y -values into character strings by means of function sprintf .
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Details

These stats use `geom_point` by default as it is the geom most likely to work well in almost any situation without need of tweaking. The default aesthetics set by these stats allow their direct use with `geom_text`, `geom_label`, `geom_line`, `geom_rug`, `geom_hline` and `geom_vline`. The formatting of the labels returned can be controlled by the user.

Value

A data frame with one row for each match to the target subset from the data or interpolated. As spectra are monotonic in wavelength, this statistic will never return more than one row when used with spectra.

Computed variables

x x-value at or nearest to the match to the target as numeric

y target value or y-value nearest to the target as numeric

x.label x-value at or nearest to the match formatted as character

y.label target value or y-value nearest to the target formatted as character

color color definition calculated by assuming that x-values are wavelengths expressed in nanometres.

Default aesthetics

Set by the statistic and available to geoms.

label ..x.label..

xintercept ..x..

yintercept ..y..

fill ..color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

These stats work nicely together with geoms `geom_text_repel` and `geom_label_repel` from package [ggrepel](#) to solve the problem of overlapping labels by displacing them. To discard overlapping labels use `check_overlap = TRUE` as argument to `geom_text`. By default the labels are character values suitable to be plotted as is, but with a suitable `label.fmt` labels suitable for parsing by the geoms (e.g. into expressions containing greek letters or super or subscripts) can be also easily obtained.

See Also

[find_peaks](#).

Other stats functions: [stat_color\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(yellow_gel.spct) + geom_line() +
  stat_find_qtys(target = "half.range")
ggplot(yellow_gel.spct) + geom_line() +
  stat_find_qtys(target = c(490, 500, 510))
ggplot(yellow_gel.spct) + geom_line() +
  stat_find_qtys(target = 500, geom = "point", colour = "red") +
  stat_find_qtys(target = 500, geom = "text", colour = "red",
    hjust = 1.1, label.fmt = "Tfr = %1.2f")
```

stat_find_wls

Find wavelength for target quantity value.

Description

stat_find_wls finds at which x positions values equal to a target are located.

Usage

```
stat_find_wls(
  mapping = NULL,
  data = NULL,
  geom = "point",
  target = "half.maximum",
  interpolate = TRUE,
  chroma.type = "CMF",
  label.fmt = "%.3g",
  x.label.fmt = label.fmt,
  y.label.fmt = label.fmt,
  position = "identity",
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
target	numeric vector indicating the spectral quantity values for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments. A list with numeric and/or character values is also accepted.

<code>interpolate</code>	logical Indicating whether the nearest wavelength value in <code>x</code> should be returned or a value calculated by linear interpolation between wavelength values straddling the target.
<code>chroma.type</code>	character one of "CMF" (color matching function) or "CC" (color coordinates) or a <code>chroma_spct</code> object.
<code>label.fmt</code>	character string giving a format definition for converting values into character strings by means of function <code>sprintf</code> .
<code>x.label.fmt</code>	character string giving a format definition for converting <code>\$x\$</code> -values into character strings by means of function <code>sprintf</code> .
<code>y.label.fmt</code>	character string giving a format definition for converting <code>\$y\$</code> -values into character strings by means of function <code>sprintf</code> .
<code>position</code>	The position adjustment to use for overlapping points on this layer
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Details

These stats use `geom_point` by default as it is the geom most likely to work well in almost any situation without need of tweaking. The default aesthetics set by these stats allow their direct use with `geom_text`, `geom_label`, `geom_line`, `geom_rug`, `geom_hline` and `geom_vline`. The formatting of the labels returned can be controlled by the user.

Value

A data frame with one row for each match to target found in the data.

Computed variables

- x** x-value at or nearest to the match to the target as numeric
- y** target value or y-value nearest to the target as numeric
- x.label** x-value at or nearest to the match formatted as character
- y.label** target value or y-value nearest to the target formatted as character
- wl.color** color definition calculated by assuming that x-values are wavelengths expressed in nanometres.

Default aesthetics

Set by the statistic and available to geoms.

label ..x.label..

xintercept ..x..

yintercept ..y..

fill ..wl.color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

These stats work nicely together with geoms `geom_text_repel` and `geom_label_repel` from package `ggrepel` to solve the problem of overlapping labels by displacing them. To discard overlapping labels use `check_overlap = TRUE` as argument to `geom_text`. By default the labels are character values suitable to be plotted as is, but with a suitable `label.fmt` labels suitable for parsing by the geoms (e.g. into expressions containing greek letters or super or subscripts) can be also easily obtained.

See Also

[find_peaks](#).

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(yellow_gel.spct) + geom_line() +
  stat_find_wls(target = c(0.25, 0.5, 0.75))
ggplot(yellow_gel.spct) + geom_line() +
  stat_find_wls(target = "half.maximum", geom = "point", colour = "red") +
  stat_find_wls(target = "half.maximum", geom = "text", colour = "red",
    hjust = 1.1, label.fmt = "%3.0f nm")
```

stat_label_peaks	<i>Label peaks and valleys.</i>
------------------	---------------------------------

Description

stat_labels_peaks finds at which x positions local maxima are located, and adds labels and colors to the data without subsetting. To find local minima, you can use stat_labels_valleys instead.

Usage

```
stat_label_peaks(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  position = "identity",  
  ...,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  x.label.fmt = label.fmt,  
  y.label.fmt = label.fmt,  
  label.fill = "",  
  na.rm = TRUE,  
  show.legend = FALSE,  
  inherit.aes = TRUE  
)
```

```
stat_label_valleys(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  position = "identity",  
  ...,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  x.label.fmt = label.fmt,  
  y.label.fmt = label.fmt,  
  label.fill = "",  
  na.rm = TRUE,  
  show.legend = FALSE,  
  inherit.aes = TRUE  
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
position	The position adjustment to use for overlapping points on this layer
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.
span	a peak is defined as an element in a sequence which is greater than all other elements within a window of width span centered at that element. The default value is 5, meaning that a peak is bigger than two consecutive neighbors on each side. Default: 5.
ignore_threshold	numeric value between 0.0 and 1.0 indicating the size threshold below which peaks will be ignored.
strict	logical flag: if TRUE, an element must be strictly greater than all other values in its window to be considered a peak. Default: FALSE.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for converting values into character strings by means of function sprintf .
x.label.fmt	character string giving a format definition for converting x -values into character strings by means of function sprintf .
y.label.fmt	character string giving a format definition for converting y -values into character strings by means of function sprintf .
label.fill	character string ot use for labels not at peaks or valleys being highlighted.
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .

Details

These stats use `geom_text` by default as it is the geom most likely to work well in almost any situation without need of tweaking. These statistics work best with `geom_text_repel` and `geom_label_repel` from package 'ggrepel' as they are designed so that peak or valley labels will not overlapT any observation in the whole data set. Default aesthetics set by these stats allow their direct use with `geom_text`, `geom_label`, `geom_line`, `geom_rug`, `geom_hline` and `geom_vline`. The formatting of the labels returned can be controlled by the user.

Value

The original data with additional computed variables added.

Computed variables

x.label x-value at a peak (or valley) formatted as character or otherwise the value passed to `label.fill` which defaults to an empty string ("").

y.label y-value at the peak (or valley) formatted as character or otherwise the value passed to `label.fill` which defaults to an empty string ("").

wl.color At peaks and valleys, color definition calculated by assuming that x-values are wavelengths expressed in nanometres, otherwise, `rgb(1, 1, 1, 0)` (transparent white).

Default aesthetics

Set by the statistic and available to geoms.

label `..x.label..`

xintercept `..x..`

yintercept `..y..`

color `black_or_white(..wl.color..)`

fill `..wl.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

These stats work nicely together with geoms `geom_text_repel` and `geom_label_repel` from package [ggrepel](#) to solve the problem of overlapping labels by displacing them. To discard overlapping labels use `check_overlap = TRUE` as argument to `geom_text`. By default the labels are character values suitable to be plotted as is, but with a suitable `label.fmt` labels suitable for parsing by the geoms (e.g. into expressions containing greek letters or super or subscripts) can be also easily obtained.

See Also

[stat_peaks](#), [stat_valleys](#) and [find_peaks](#), which is used internally.

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```

# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) + geom_line() +
  stat_label_peaks(hjust = "left", span = 31, angle = 90, color = "red")
ggplot(sun.spct) + geom_line() +
  stat_label_valleys(hjust = "right", span = 21, angle = 90, color = "blue")

ggplot(sun.spct) + geom_line() +
  stat_peaks(span = 41, shape = 21, size = 3) +
  stat_label_peaks(span = 41, geom = "label", label.fmt = "%3.0f nm") +
  scale_fill_identity() +
  scale_color_identity() +
  expand_limits(y = c(NA, 1))

# using 'ggrepel' to avoid overlaps
# too slow for CRAN checks
## Not run:
library(ggrepel)

ggplot(sun.spct) + geom_line() +
  stat_peaks(span = 41, shape = 21, size = 3) +
  stat_label_peaks(span = 41, geom = "label_repel", segment.colour = "red",
    nudge_y = 0.12, label.fmt = "%3.0f nm", vjust = 1) +
  scale_fill_identity() +
  scale_color_identity() +
  expand_limits(y = c(NA, 1))

## End(Not run)

```

stat_peaks

Find peaks and valleys.

Description

stat_peaks finds at which x positions local maxima are located. If you want find local minima, you can use stat_valleys instead.

Usage

```

stat_peaks(
  mapping = NULL,
  data = NULL,
  geom = "point",
  position = "identity",
  ...,
  span = 5,
  ignore_threshold = 0.01,
  strict = is.null(span),

```

```

    refine.wl = FALSE,
    method = "spline",
    chroma.type = "CMF",
    label.fmt = "%.3g",
    x.label.fmt = label.fmt,
    y.label.fmt = label.fmt,
    na.rm = FALSE,
    show.legend = FALSE,
    inherit.aes = TRUE
  )

stat_valleys(
  mapping = NULL,
  data = NULL,
  geom = "point",
  position = "identity",
  ...,
  span = 5,
  ignore_threshold = -0.01,
  strict = is.null(span),
  refine.wl = FALSE,
  method = "spline",
  chroma.type = "CMF",
  label.fmt = "%.3g",
  x.label.fmt = label.fmt,
  y.label.fmt = label.fmt,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
position	The position adjustment to use for overlapping points on this layer
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.
span	integer A peak is defined as an element in a sequence which is greater than all other elements within a window of width span centered at that element. Use NULL for the global peak. Valleys are the reverse.
ignore_threshold	numeric For peaks, value between 0.0 and 1.0 indicating the relative size of peaks compared to tallest peak threshold below which peaks will be ignored, while negative values between 0.0 and -1.0 set a threshold so that the tallest

	peaks are ignored, instead of the shortest. For valleys, value between 0.0 and 1.0 indicating the relative depth of valleys below which valleys will be ignored, while negative values between 0.0 and -1.0 set a threshold so that the deeper valleys are ignored, instead of the shallower ones.
<code>strict</code>	logical If TRUE, an element must be strictly greater than all other values in its window to be considered a peak.
<code>refine.wl</code>	logical Flag indicating if peak or valleys locations should be refined by fitting a function.
<code>method</code>	character String with the name of a method used for peak fitting. Currently only spline interpolation is implemented.
<code>chroma.type</code>	character one of "CMF" (color matching function) or "CC" (color coordinates) or a <code>chroma_spct</code> object.
<code>label.fmt</code>	character string giving a format definition for converting values into character strings by means of function <code>sprintf</code> .
<code>x.label.fmt</code>	character string giving a format definition for converting <code>\$x\$</code> -values into character strings by means of function <code>sprintf</code> .
<code>y.label.fmt</code>	character string giving a format definition for converting <code>\$y\$</code> -values into character strings by means of function <code>sprintf</code> .
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .

Details

These stats use `geom_point` by default as it is the geom most likely to work well in almost any situation without need of tweaking. The default aesthetics set by these stats allow their direct use with `geom_text`, `geom_label`, `geom_line`, `geom_rug`, `geom_hline` and `geom_vline`. The formatting of the labels returned can be controlled by the user.

Value

A data frame with one row for each peak (or valley) found in the data.

Computed variables

x x-value at the peak (or valley) as numeric

y y-value at the peak (or valley) as numeric

x.label x-value at the peak (or valley) formatted as character

y.label y-value at the peak (or valley) formatted as character

wl.color color definition calculated by assuming that x-values are wavelengths expressed in nanometres.

BW.color color definition, either "black" or "white", as needed to ensure high contrast to `wl.color`.

Default aesthetics

Set by the statistic and available to geoms.

label stat(x.label)

xintercept stat(x)

yintercept stat(y)

fill stat(wl.color)

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

These stats work nicely together with geoms `geom_text_repel` and `geom_label_repel` from package [ggrepel](#) to solve the problem of overlapping labels by displacing them. To discard overlapping labels use `check_overlap = TRUE` as argument to `geom_text`. By default the labels are character values suitable to be plotted as is, but with a suitable `label.fmt` labels suitable for parsing by the geoms (e.g. into expressions containing greek letters or super or subscripts) can be also easily obtained.

See Also

[find_peaks](#), which is used internally.

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  geom_line() +
  stat_peaks()

ggplot(sun.spct) +
  geom_line() +
  stat_valleys()

ggplot(sun.spct) +
  geom_line() +
  stat_peaks(span = 51, geom = "point", colour = "red") +
  stat_peaks(span = 51, geom = "text", colour = "red",
            vjust = -0.4, label.fmt = "%3.2f nm")
```

```

ggplot(sun.spct) +
  geom_line() +
  stat_peaks(span = 51, geom = "point", colour = "red", refine.wl = TRUE) +
  stat_peaks(span = 51, geom = "text", colour = "red",
            vjust = -0.4, label.fmt = "%3.2f nm",
            refine.wl = TRUE)

ggplot(sun.spct) +
  geom_line() +
  stat_peaks(span = 51, geom = "point", colour = "red", refine.wl = TRUE) +
  stat_peaks(mapping = aes(fill = after_stat(wl.colour), color = after_stat(BW.colour)),
            span = 51, geom = "label",
            size = 3, vjust = -0.2, label.fmt = "%.3g nm",
            refine.wl = TRUE) +
  stat_valleys(span = 71, geom = "point", colour = "blue", refine.wl = TRUE) +
  stat_valleys(mapping = aes(fill = after_stat(wl.colour), color = after_stat(BW.colour)),
            span = 71, geom = "label",
            size = 3, vjust = 1.2, label.fmt = "%.3g nm",
            refine.wl = TRUE) +
  expand_limits(y = 0.85) + # make room for label
  scale_fill_identity() +
  scale_color_identity()

```

stat_spikes

Find spikes

Description

stat_spikes finds at which x positions spikes are located. Spikes can be either upwards or downwards from the baseline.

Usage

```

stat_spikes(
  mapping = NULL,
  data = NULL,
  geom = "point",
  position = "identity",
  ...,
  z.threshold = 9,
  max.spike.width = 8,
  chroma.type = "CMF",
  label.fmt = "%.3g",
  x.label.fmt = label.fmt,
  y.label.fmt = label.fmt,
  na.rm = FALSE,
  show.legend = FALSE,
  inherit.aes = TRUE
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
position	The position adjustment to use for overlapping points on this layer
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.
z.threshold	numeric Modified Z values larger than <code>z.threshold</code> are considered to be spikes.
max.spike.width	integer Wider regions with high Z values are not detected as spikes.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spect object.
label.fmt	character string giving a format definition for converting values into character strings by means of function sprintf .
x.label.fmt	character string giving a format definition for converting <code>\$x\$</code> -values into character strings by means of function sprintf .
y.label.fmt	character string giving a format definition for converting <code>\$y\$</code> -values into character strings by means of function sprintf .
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .

Details

This stat uses `geom_point` by default as it is the geom most likely to work well in almost any situation without need of tweaking. The default aesthetics set by this stat allows its direct use with `geom_text`, `geom_label`, `geom_line`, `geom_rug`, `geom_hline` and `geom_vline`. The formatting of the labels returned can be controlled by the user.

Value

A data frame with one row for each peak (or valley) found in the data.

Computed variables

- x** x-value at the peak (or valley) as numeric
- y** y-value at the peak (or valley) as numeric
- x.label** x-value at the peak (or valley) formatted as character
- y.label** y-value at the peak (or valley) formatted as character

wl.color color definition calculated by assuming that x-values are wavelengths expressed in nanometres.

BW.color color definition that either "black" or "white", to ensure high contrast to `wl.color`.

Default aesthetics

Set by the statistic and available to geoms.

label `stat(x.label)`

xintercept `stat(x)`

yintercept `stat(y)`

fill `stat(wl.color)`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

This stat works nicely together with geoms `geom_text_repel` and `geom_label_repel` from package `ggrepel` to solve the problem of overlapping labels by displacing them. To discard overlapping labels use `check_overlap = TRUE` as argument to `geom_text`. By default the labels are character values suitable to be plotted as is, but with a suitable `label.fmt` labels suitable for parsing by the geoms (e.g. into expressions containing greek letters or super or subscripts) can be also easily obtained.

See Also

[find_spikes](#), which is used internally, for a description of the algorithm used.

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
```

```
# two spurious(?) spikes
ggplot(sun.spct) +
  geom_line() +
  stat_spikes(colour = "red", alpha = 0.3)
```

```
# no spikes detected
ggplot(sun.spct) +
  geom_line() +
```



```
stat_spikes(colour = "red", alpha = 0.3,
            max.spike.width = 3,
            z.threshold = 12)

# small noise spikes detected
ggplot(white_led.raw_spct) +
  geom_line() +
  stat_spikes(colour = "red", alpha = 0.3)

ggplot(white_led.raw_spct) +
  geom_line() +
  stat_spikes(colour = "red", alpha = 0.3) +
  stat_spikes(geom = "text", colour = "red", check_overlap = TRUE,
             vjust = -0.5, label.fmt = "%3.0f nm")

ggplot(white_led.raw_spct, aes(w.length, counts_2)) +
  geom_line() +
  stat_spikes(colour = "red", alpha = 0.3,
             max.spike.width = 3,
             z.threshold = 12)
```

stat_wb_box

Draw colour boxes for wavebands

Description

stat_wb_box plots boxes corresponding to wavebands, by default located slightly above the peak of the spectrum. Sets suitable default aesthetics for "rect" geom.

Usage

```
stat_wb_box(
  mapping = NULL,
  data = NULL,
  geom = "rect",
  w.band = NULL,
  chroma.type = "CMF",
  ypos.mult = 1.07,
  ypos.fixed = NULL,
  box.height = 0.06,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
ypos.mult	numeric Multiplier constant used to compute returned y values. This is numerically similar to using npc units, but values larger than one expand the plotting area.
ypos.fixed	numeric If not NULL used a constant value returned in y.
box.height	numeric The height of the box as a fraction of the range of \$y\$. This is similar to using npc units.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row for each waveband object in the argument to w.band. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named integral below is the result of applying `integral.fun` to the data, with default `integrate_xy`.

x w.band-midpoint

wb.xmin w.band minimum

wb.xmax w.band maximum

wb.ymin data\$y minimum

wb.ymax data\$y maximum

ymin box bottom

ymax box top

y ypos.fixed or top of data, adjusted by ypos.mult
wb.color color of the w.band
wb.name label of w.band
BW.color black_or_white(wb.color)

Default aesthetics

Set by the statistic and available to geoms.

xmin stat(wb.xmin)
xmax stat(wb.xmax)
ymin stat(ymin)
ymax stat(ymax)
fill ..wb.color..

Required aesthetics

Required by the statistic and need to be set with aes().

x numeric, wavelength in nanometres
y numeric, a spectral quantity

Note

This stat uses a panel function and ignores grouping as it is meant to be used for annotations. The value returned as default value for y is based on the y-range of spectral values for the whole data set.

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```

library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  stat_wb_box(w.band = VIS_bands()) +
  geom_line() +
  scale_fill_identity()
ggplot(sun.spct) +
  stat_wb_box(w.band = VIS_bands(), color = "white") +
  geom_line() +
  scale_fill_identity()
  
```

stat_wb_column	<i>Integrate ranges under curve.</i>
----------------	--------------------------------------

Description

stat_wb_column computes means under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for "rect" geom.

Usage

```
stat_wb_column(
  mapping = NULL,
  data = NULL,
  geom = "rect",
  w.band = NULL,
  integral.fun = integrate_xy,
  chroma.type = "CMF",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
integral.fun	function on x and y .
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun`, with default `integrate_xy`.

x `w.band`-midpoint
wb.xmin `w.band` minimum
wb.xmax `w.band` maximum
wb.ymin `data$y` minimum
wb.ymax `data$y` maximum
wb.ymean `yint` divided by `wl_expance(w.band)`
y `wb.ymean`
wb.color color of the `w.band`
wb.name label of `w.band`
BW.color `black_or_white(wb.color)`

Default aesthetics

Set by the statistic and available to geoms.

xmin `..wb.xmin..`
xmax `..wb.xmax..`
ymin `0`
ymax `..wb.ymean..`
fill `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres
y numeric, a spectral quantity

Note

If the argument passed to `w.band` is a BSWF it is silently converted to a wavelength range and the average of spectral values without weighting is returned as default value for `ymax` while the default value for `ymin` is zero.

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```

library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands()) +
  geom_line() +
  scale_fill_identity()

ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands(), alpha = 0.5) +
  geom_line() +
  scale_fill_identity()

```

stat_wb_contribution *Integrate ranges under spectral curve.*

Description

stat_wb_contribution computes means under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for "rect", "hline", "vline", "text" and "label" geoms displaying "contributions" per waveband to the total of the spectral integral.

Usage

```

stat_wb_contribution(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  integral.fun = integrate_xy,
  label.mult = 1,
  chroma.type = "CMF",
  label.fmt = "%1.2f",
  ypos.mult = 1.07,
  ypos.fixed = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping The aesthetic mapping, usually constructed with [aes](#) or [aes_](#). Only needs to be set at the layer level if you are overriding the plot defaults.

<code>data</code>	A layer specific dataset - only needed if you want to override the plot defaults.
<code>geom</code>	The geometric object to use display the data
<code>w.band</code>	a waveband object or a list of waveband objects or numeric vector of at least length two.
<code>integral.fun</code>	function on <code>\$x\$</code> and <code>\$y\$</code> .
<code>label.mult</code>	numeric Scaling factor applied to y-integral values before conversion into character strings.
<code>chroma.type</code>	character one of "CMF" (color matching function) or "CC" (color coordinates) or a <code>chroma_spct</code> object.
<code>label.fmt</code>	character string giving a format definition for converting y-integral values into character strings by means of function <code>sprintf</code> .
<code>ypos.mult</code>	numeric Multiplier constant used to scale returned y values.
<code>ypos.fixed</code>	numeric If not NULL used a constant value returned in y.
<code>position</code>	The position adjustment to use for overlapping points on this layer
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun` to the data, with default `integrate_xy`.

y.label `yint` multiplied by `label.mult` and formatted according to `label.fmt`

x `w.band-midpoint`

xmin `w.band` minimum

xmax `w.band` maximum

ymin `data$y` minimum

ymax `data$y` maximum

yint `data$y` integral for `w.band` / `data$y` integral for whole range of `data$x`

xmean `yint` divided by `wl_expans(w.band)`

y `ypos.fixed` or top of data, adjusted by `ypos.mult`

wb.color color of the `w.band`

wb.name label of `w.band`

Default aesthetics

Set by the statistic and available to geoms.

label `..y.label..`

x `..x..`

xmin `..xmin..`

xmax `..xmax..`

ymin `..y.. - (..ymax.. - ..ymin..) * 0.03`

ymax `..y.. + (..ymax.. - ..ymin..) * 0.03`

yintercept `..ymean..`

fill `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.

# Using defaults
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS()) +
  stat_wb_contribution(w.band = VIS()) +
  scale_fill_identity() + scale_color_identity()

# Setting position and angle of the text
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS_bands()) +
  stat_wb_contribution(w.band = VIS_bands(), angle = 90, size = 2.5) +
  scale_fill_identity() + scale_color_identity()

# Showing percentages, i.e., using a different format for numbers
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS_bands()) +
```



```

stat_wb_contribution(w.band = VIS_bands(), size = 2.5,
                    label.mult = 100, label.fmt = "%3.0f%%") +
scale_fill_identity() + scale_color_identity()

# Including the name of the waveband, i.e., changing the mapping for label
ggplot(sun.spct, range = c(NA, 410)) +
  geom_line() +
  stat_wb_box(w.band = UV_bands(), color = "white") +
  stat_wb_contribution(w.band = UV_bands(), size = 2.5,
                    label.mult = 100, label.fmt = "%3.0f%",
                    mapping = aes(label = after_stat(paste(wb.name, y.label)))) +
  scale_fill_identity() + scale_color_identity()

```

stat_wb_hbar

Integrate ranges under curve.

Description

stat_wb_hbar computes means under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for geoms "errorbarh" and "hline" from 'ggplot', and "linrangeh", and "errorbarh" from 'ggstance'.

Usage

```

stat_wb_hbar(
  mapping = NULL,
  data = NULL,
  geom = "errorbarh",
  w.band = NULL,
  integral.fun = integrate_xy,
  chroma.type = "CMF",
  ypos.fixed = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with <code>aes</code> or <code>aes_</code> . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data

<code>w.band</code>	a waveband object or a list of waveband objects or numeric vector of at least length two.
<code>integral.fun</code>	function on x and y .
<code>chroma.type</code>	character one of "CMF" (color matching function) or "CC" (color coordinates) or a <code>chroma_spct</code> object.
<code>ypos.fixed</code>	numeric If not NULL used a constant value returned in y .
<code>position</code>	The position adjustment to use for overlapping points on this layer
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun`, with default `integrate_xy`.

x `w.band-midpoint`
xmin `w.band` minimum
xmax `w.band` maximum
ymin `data$y` minimum
ymax `data$y` maximum
yint `data$y` integral for the range of `w.band`
ymean `yint` divided by `wl_expance(w.band)`
y `ypos.fixed` or mean of data
wb.color color of the `w.band`
wb.name label of `w.band`

Default aesthetics

Set by the statistic and available to geoms.

xmin `..xmin..`
xmax `..xmax..`
yintercept `..ymean..`
height `(..ymax.. - ..ymin..) * 2e-2`
color `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

Note

If the argument passed to `w.band` is a BSWF it is silently converted to a wavelength range and the average of spectral values without any weighting is returned as default value for `y`.

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = VIS_bands(), size = 1) +
  scale_color_identity() +
  theme_bw()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = PAR(), size = 1) +
  scale_color_identity() +
  theme_bw()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = PAR(), size = 1, ypos.fixed = 0) +
  scale_color_identity() +
  theme_bw()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = CIE(), size = 1) +
  scale_color_identity() +
  theme_bw()
```

stat_wb_irrad	<i>Integrate irradiance for wavebands.</i>
---------------	--

Description

stat_wb_irrad computes areas under a curve.

Usage

```
stat_wb_irrad(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  w.band = NULL,  
  time.unit,  
  unit.in,  
  label.qty = "total",  
  label.mult = 1,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  ypos.mult = 1.07,  
  ypos.fixed = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  inherit.aes = TRUE,  
  ...  
)
```

```
stat_wb_e_irrad(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  w.band = NULL,  
  time.unit = "second",  
  unit.in = "energy",  
  label.qty = "total",  
  label.mult = 1,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  ypos.mult = 1.07,  
  ypos.fixed = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  inherit.aes = TRUE,  
  ...  
)
```

```

)

stat_wb_q_irrad(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  time.unit = "second",
  unit.in = "photon",
  label.qty = "total",
  label.mult = 1,
  chroma.type = "CMF",
  label.fmt = "%.3g",
  ypos.mult = 1.07,
  ypos.fixed = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
time.unit	character or lubridate::duration
unit.in	character One of "photon","quantum" or "energy"
label.qty	character
label.mult	numeric Scaling factor applied to y-integral values before conversion into character strings.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
ypos.mult	numeric Multiplier constant used to scale returned y values.
ypos.fixed	numeric If not NULL used a constant value returned in y.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.

<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named integral below is the result of applying `irrad`, `e_irrad` or `q_irrad` to the data.

y.label `yeff` multiplied by `label.mult` and formatted according to `label.fmt`

x `w.band-midpoint`

wb.xmin `w.band` minimum

wb.xmax `w.band` maximum

wb.ymin `data$y` minimum

wb.ymax `data$y` maximum

wb.yeff weighted irradiance if `w.band` describes a BSWF

wb.yint not weighted irradiance for the range of `w.band`

wb.xmean `yint` divided by `wl_expance(w.band)`

y `ypos.fixed` or top of data, adjusted by `ypos.mult`

wb.color color of the `w.band`

wb.name label of `w.band`

BW.color `black_or_white(wb.color)`

Default aesthetics

Set by the statistic and available to geoms.

label `..y.label..`

x `..x..`

xmin `..wb.xmin..`

xmax `..wb.xmax..`

ymin `..y.. - (..wb.ymax.. - ..wb.ymin..) * 0.03`

ymax `..y.. + (..wb.ymax.. - ..wb.ymin..) * 0.03`

yintercept `..wb.ymean..`

fill `..wb.color..`


```

geom_line() +
scale_fill_identity() + scale_color_identity() +
theme_bw()
sep = ""))))) +

```

stat_wb_label	<i>Label ranges under spectral curve.</i>
---------------	---

Description

stat_wb_label computes the center of a waveband. Sets suitable default aesthetics for "text" and "label" geoms displaying "boundaries" and "names" of wavebands.

Usage

```

stat_wb_label(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  chroma.type = "CMF",
  label.fmt = "%s",
  ypos.fixed = 0,
  position = "identity",
  na.rm = TRUE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for formatting the name of the waveband. sprintf .
ypos.fixed	numeric If not NULL used a constant value returned in y.
position	The position adjustment to use for overlapping points on this layer

<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

x w.band-midpoint
wb.xmin w.band minimum
wb.xmax w.band maximum
y ypos.fixed or zero
wb.color color of the w.band
wb.name label of w.band
wb.label formatted wb.name

Default aesthetics

Set by the statistic and available to geoms.

label ..wb.label..
x ..x..
xmin ..wb.xmin..
xmax ..wb.xmax..
fill ..wb.color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

Note

This stat uses a panel function and ignores grouping as it is meant to be used for annotations.

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS(), ymin = -0.04, ymax = 0,
             color = "black", fill = "white") +
  stat_wb_label(w.band = VIS(), ypos.fixed = -0.02, color = "black")

ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = PAR(), ypos.fixed = 0, size = 1) +
  stat_wb_label(aes(color = ..wb.color..),
               w.band = PAR(), ypos.fixed = +0.025) +
  scale_color_identity()
```

stat_wb_mean

Integrate ranges under curve.

Description

stat_wb_mean computes means under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for "rect", "hline", "vline", "text" and "label" geoms.

Usage

```
stat_wb_mean(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  integral.fun = integrate_xy,
  label.mult = 1,
  chroma.type = "CMF",
  label.fmt = "%.3g",
  ypos.mult = 1.07,
  xpos.fixed = NULL,
  ypos.fixed = NULL,
  position = "identity",
```

```

    na.rm = FALSE,
    show.legend = NA,
    inherit.aes = TRUE,
    ...
  )

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
integral.fun	function on $\$x\$$ and $\$y\$$.
label.mult	numeric Scaling factor applied to y-integral values before conversion into character strings.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spect object.
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
ypos.mult	numeric Multiplier constant used to scale returned y values.
xpos.fixed, ypos.fixed	numeric If not NULL used as constant value returned in x or y.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun`, with default `integrate_xy`.

y.label `y`mean multiplied by `label.mult` and formatted according to `label.fmt`

x w.band-midpoint
wb.xmin w.band minimum
wb.xmax w.band maximum
wb.ymin data\$y minimum
wb.ymax data\$y maximum
wb.yint data\$y integral for the range of w.band
wb.xmean yint divided by wl_expanse(w.band)
y ypos.fixed or top of data, adjusted by ypos.mult
wb.color color of the w.band
wb.name label of w.band
BW.color black_or_white(wb.color)

Default aesthetics

Set by the statistic and available to geoms.

label ..y.label..
x ..x..
xmin ..wb.xmin..
xmax ..wb.xmax..
ymin 0
ymax ..wb.ymean..
yintercept ..wb.ymean..
fill ..wb.color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres
y numeric, a spectral quantity

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```

library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.

# Using defaults
ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands()) +
  stat_wb_mean(w.band = VIS_bands(),
              color = "black") +
  scale_fill_identity() + scale_color_identity()

# Setting format for numbers, position, angle, and color
ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands(), alpha = 0.5) +
  stat_wb_mean(w.band = VIS_bands(),
              label.fmt = "%.2f",
              angle = 90, color = "black", ypos.fixed = 0.1) +
  geom_line() +
  scale_fill_identity() + scale_color_identity() +
  theme_bw()

# Changing label mapping
ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands(), alpha = 0.5) +
  stat_wb_mean(w.band = VIS_bands(),
              label.fmt = "%.2f",
              angle = 90, color = "black", ypos.fixed = 0.1,
              hjust = "left", size = 3,
              mapping = aes(label = after_stat(paste(wb.name, ": ", y.label, sep = "")))) +
  geom_line() +
  scale_fill_identity() + scale_color_identity() +
  theme_bw()

# example using repulsion
library(ggrepel)
ggplot(sun.spct) +
  geom_line() +
  stat_wb_hbar(w.band = VIS_bands(), size = 1.5) +
  stat_wb_mean(w.band = VIS_bands(),
              geom = "label_repel", nudge_y = +0.04, size = 3,
              segment.colour = NA, label.size = NA) +
  expand_limits(y = 0.9) +
  scale_fill_identity() + scale_color_identity() +
  theme_bw()

```

Description

stat_wb_relative computes means under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for "rect", "hline", "vline", "text" and "label" geoms displaying values per waveband "relative" to the sum of the wavebands.

Usage

```
stat_wb_relative(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  integral.fun = integrate_xy,
  label.mult = 1,
  chroma.type = "CMF",
  label.fmt = "%1.2f",
  ypos.mult = 1.07,
  ypos.fixed = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
integral.fun	function on x and y .
label.mult	numeric Scaling factor applied to y-integral values before conversion into character strings.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
ypos.mult	numeric Multiplier constant used to scale returned y values.
ypos.fixed	numeric If not NULL used a constant value returned in y.
position	The position adjustment to use for overlapping points on this layer

<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
<code>...</code>	other arguments passed on to <code>layer</code> . This can include aesthetics whose values you want to set, not map. See <code>layer</code> for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun` to the data, with default `integrate_xy`.

y.label `yint` multiplied by `label.mult` and formatted according to `label.fmt`

x `w.band`-midpoint

wb.xmin `w.band` minimum

wb.xmax `w.band` maximum

wb.ymin `data$y` minimum

wb.ymax `data$y` maximum

wb.yint `data$y` integral for each member of `w.band` / sum of `data$y` integrals for all wavebands in `w.band`

wb.xmean `yint` divided by `wl_expance(w.band)`

y `ypos.fixed` or top of data, adjusted by `ypos.mult`

wb.color color of the `w.band`

wb.name label of `w.band`

BW.color `black_or_white(wb.color)`

Default aesthetics

Set by the statistic and available to geoms.

label `..y.label..`

x `..x..`

xmin `..wb.xmin..`

xmax `..wb.xmax..`

ymin `..y.. - (..wb.ymax.. - ..wb.ymin..) * 0.03`

ymax `..y.. + (..wb.ymax.. - ..wb.ymin..) * 0.03`

yintercept `..wb.ymean..`

fill `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

See Also

Other stats functions: `stat_color()`, `stat_find_qtys()`, `stat_find_wls()`, `stat_label_peaks()`, `stat_peaks()`, `stat_spikes()`, `stat_wb_box()`, `stat_wb_column()`, `stat_wb_contribution()`, `stat_wb_hbar()`, `stat_wb_irrad()`, `stat_wb_label()`, `stat_wb_mean()`, `stat_wb_sirrad()`, `stat_wb_total()`, `stat_wl_strip()`, `stat_wl_summary()`

Examples

```
library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS()) +
  stat_wb_relative(w.band = VIS()) +
  scale_fill_identity() + scale_color_identity()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS_bands()) +
  stat_wb_relative(w.band = VIS_bands(), angle = 90, size = 2.5) +
  scale_fill_identity() + scale_color_identity()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS_bands()) +
  stat_wb_relative(w.band = VIS_bands(), angle = 90, size = 2.5,
                  label.mult = 100, label.fmt = "%3.0f%") +
  scale_fill_identity() + scale_color_identity()
```

stat_wb_sirrad

Integrate spectral irradiance for wavebands.

Description

`stat_wb_sirrad` computes areas under a curve.

Usage

```
stat_wb_sirrad(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  w.band = NULL,  
  time.unit,  
  unit.in,  
  label.qty = "mean",  
  label.mult = 1,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  ypos.mult = 0.55,  
  xpos.fixed = NULL,  
  ypos.fixed = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  inherit.aes = TRUE,  
  ...  
)
```

```
stat_wb_e_sirrad(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  w.band = NULL,  
  time.unit = "second",  
  unit.in = "energy",  
  label.qty = "mean",  
  label.mult = 1,  
  chroma.type = "CMF",  
  label.fmt = "%.3g",  
  ypos.mult = 0.55,  
  xpos.fixed = NULL,  
  ypos.fixed = NULL,  
  position = "identity",  
  na.rm = FALSE,  
  show.legend = NA,  
  inherit.aes = TRUE,  
  ...  
)
```

```
stat_wb_q_sirrad(  
  mapping = NULL,  
  data = NULL,  
  geom = "text",  
  w.band = NULL,
```

```

time.unit = "second",
unit.in = "photon",
label.qty = "mean",
label.mult = 1,
chroma.type = "CMF",
label.fmt = "%.3g",
ypos.mult = 1.07,
xpos.fixed = NULL,
ypos.fixed = NULL,
position = "identity",
na.rm = FALSE,
show.legend = NA,
inherit.aes = TRUE,
...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
time.unit	character or lubridate::duration
unit.in	character One of "photon","quantum" or "energy"
label.qty	character
label.mult	numeric Scaling factor applied to y-integral values before conversion into character strings.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spect object.
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
ypos.mult	numeric Multiplier constant used to scale returned y values.
xpos.fixed, ypos.fixed	numeric If not NULL used a constant value returned in x or y.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Wavebands outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named integral below is the result of applying `irrad`, `e_irrad` or `q_irrad` to the data.

y.label `yeff` multiplied by `label.mult` and formatted according to `label.fmt`

x `w.band`-midpoint

wb.xmin `w.band` minimum

wb.xmax `w.band` maximum

wb.ymin `data$y` minimum

wb.ymax `data$y` maximum

wb.yeff weighted irradiance if `w.band` describes a BSWF

wb.yint not weighted irradiance for the range of `w.band`

wb.xmean `yint` divided by `wl_expance(w.band)`

y `ypos.fixed` or top of data, adjusted by `ypos.mult`

wb.color color of the `w.band`

wb.name label of `w.band`

BW.color `black_or_white(wb.color)`

Default aesthetics

Set by the statistic and available to geoms.

label `..y.label..`

x `..x..`

xmin `..wb.xmin..`

xmax `..wb.xmax..`

ymin 0

ymax `..wb.ymean..`

yintercept `..wb.ymean..`

fill `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

y numeric, a spectral quantity

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```
library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  stat_wb_column(w.band = VIS_bands()) +
  stat_wb_e_sirrad(w.band = VIS_bands(), angle = 90, size = 4,
                  label.fmt = "%1.2f", ypos.fixed = 0.1) +
  geom_line() +
  scale_fill_identity() + scale_color_identity()

ggplot(sun.spct, unit.out = "photon") +
  geom_line() +
  stat_wb_hbar(w.band = PAR(), size = 1) +
  stat_wb_q_sirrad(aes(color = ..wb.color..),
                  w.band = PAR(), label.fmt = "mean = %.3g",
                  ypos.mult = 1, xpos.fixed = 390, hjust = 1) +
  scale_color_identity()
```

stat_wb_total

Integrate ranges under spectral curve.

Description

stat_wb_total computes integral under a curve. It first integrates the area under a spectral curve and also the mean expressed per nanometre of wavelength for each waveband in the input. Sets suitable default aesthetics for "rect", "hline", "vline", "text" and "label" geoms displaying "totals" per waveband.

Usage

```
stat_wb_total(
  mapping = NULL,
  data = NULL,
  geom = "text",
  w.band = NULL,
  integral.fun = integrate_xy,
  label.mult = 1,
  chroma.type = "CMF",
  label.fmt = "%.3g",
  ypos.mult = 1.07,
```

```

  ypos.fixed = NULL,
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	a waveband object or a list of waveband objects or numeric vector of at least length two.
integral.fun	function on $\$x\$$ and $\$y\$$.
label.mult	numeric Scaling factor applied to y-integral values before conversion into character strings.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
ypos.mult	numeric Multiplier constant used to scale returned y values.
ypos.fixed	numeric If not NULL used a constant value returned in y.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row for each waveband object in the argument to `w.band`. Waveband outside the range of the spectral data are trimmed or discarded.

Computed variables

What it is named `integral` below is the result of applying `integral.fun`, with default `integrate_xy`.

y.label `y.mean` multiplied by `label.mult` and formatted according to `label.fmt`
x `w.band`-midpoint
wb.xmin `w.band` minimum
wb.xmax `w.band` maximum
wb.ymin `data$y` minimum
wb.ymax `data$y` maximum
wb.yint `data$y` integral for the range of `w.band`
wb.xmean `yint` divided by `wl_expance(w.band)`
y `ypos.fixed` or top of data, adjusted by `ypos.mult`
wb.color color of the `w.band`
wb.name label of `w.band`
BW.color `black_or_white(wb.color)`

Default aesthetics

Set by the statistic and available to geoms.

label `..y.label..`
x `..x..`
xmin `..wb.xmin..`
xmax `..wb.xmax..`
ymin `..y.. - (..wb.ymax.. - ..wb.ymin..) * 0.03`
ymax `..y.. + (..wb.ymax.. - ..wb.ymin..) * 0.03`
yintercept `..wb.ymean..`
fill `..wb.color..`

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres
y numeric, a spectral quantity

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wl_strip\(\)](#), [stat_wl_summary\(\)](#)

Examples

```

library(photobiologyWavebands)
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = VIS()) +
  stat_wb_total(w.band = VIS()) +
  scale_fill_identity() + scale_color_identity()

ggplot(sun.spct) +
  geom_line() +
  stat_wb_box(w.band = UV_bands(), color = "white") +
  stat_wb_total(w.band = UV_bands()) +
  scale_fill_identity() + scale_color_identity()

```

stat_wl_strip

Calculate colours from wavelength.

Description

stat_wl_strip computes color definitions according to human vision.

Usage

```

stat_wl_strip(
  mapping = NULL,
  data = NULL,
  geom = "rect",
  w.band = NULL,
  length.out = 150,
  chroma.type = "CMF",
  position = "identity",
  na.rm = TRUE,
  show.legend = FALSE,
  inherit.aes = TRUE,
  ...
)

wl_guide(
  mapping = NULL,
  data = NULL,
  chroma.type = "CMF",
  w.band = NULL,
  length.out = 150,
  ymin = -Inf,
  ymax = Inf,
  position = "identity",

```

```

na.rm = FALSE,
show.legend = FALSE,
inherit.aes = TRUE,
...
)

```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
w.band	waveband object or a list of such objects or NULL.
length.out	The number of steps to use to simulate a continuous range of colours when w.band == NULL.
chroma.type	character one of "CMF" (color matching function) or "CC" (color coordinates) or a chroma_spct object.
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.
ymin, ymax	numeric used as aesthetics for plotting the guide.

Value

generic_spect object with new x values plus other computed variables described below.

Computed variables

x $(w.low + wl.high) / 2$
wl.low boundary of waveband
wl.high boundary of waveband
wl.color color corresponding to wavelength
wb.color color corresponding to waveband
wb.name label of w.band

Default aesthetics

Set by the statistic and available to geoms.

x ..x..

label as.character(..wb.f..)

xmin ..wl.low..

xmax ..wl.high..

fill ..wb.color..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres

Note

This stat uses a panel function and ignores grouping as it is meant to be used for annotations.

See Also

`color_of`, which is used internally.

Other stats functions: `stat_color()`, `stat_find_qtys()`, `stat_find_wls()`, `stat_label_peaks()`, `stat_peaks()`, `stat_spikes()`, `stat_wb_box()`, `stat_wb_column()`, `stat_wb_contribution()`, `stat_wb_hbar()`, `stat_wb_irrad()`, `stat_wb_label()`, `stat_wb_mean()`, `stat_wb_relative()`, `stat_wb_sirrad()`, `stat_wb_total()`, `stat_wl_summary()`

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) + geom_line() +
  stat_wl_strip(ymax = -0.02, ymin = -0.04) +
  scale_fill_identity()
```

```
# on some graphic devices the output may show spurious vertical lines
ggplot(sun.spct) + wl_guide(alpha = 0.33, color = NA) + geom_line()
```

stat_wl_summary

Average area under curve for regions.

Description

`stat_wl_summary` computes the area under a curve.

Usage

```
stat_wl_summary(
  mapping = NULL,
  data = NULL,
  geom = "text",
  range = NULL,
  integral.fun = integrate_xy,
  label.fmt = "%.3g",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	The aesthetic mapping, usually constructed with aes or aes_ . Only needs to be set at the layer level if you are overriding the plot defaults.
data	A layer specific dataset - only needed if you want to override the plot defaults.
geom	The geometric object to use display the data
range	a numeric vector of at least length two.
integral.fun	function on x and y .
label.fmt	character string giving a format definition for converting y-integral values into character strings by means of function sprintf .
position	The position adjustment to use for overlapping points on this layer
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders .
...	other arguments passed on to layer . This can include aesthetics whose values you want to set, not map. See layer for more details.

Value

A data frame with one row.

Computed variables

What it is named `integral` below is the result of applying `integral.fun`, with default `integrate_xy`.

y.label y formatted according to `label.fmt`

x range-midpoint

wb.xmin range minimum
wb.xmax range maximum
y data\$y integral for the range by the expanse of the range

Default aesthetics

Set by the statistic and available to geoms.

label ..label..
x ..x..
xmin ..wb.xmin..
xmax ..wb.xmax..
y ..y..
ymin 0
ymax ..y..
yintercept ..y..

Required aesthetics

Required by the statistic and need to be set with `aes()`.

x numeric, wavelength in nanometres
y numeric, a spectral quantity

See Also

Other stats functions: [stat_color\(\)](#), [stat_find_qtys\(\)](#), [stat_find_wls\(\)](#), [stat_label_peaks\(\)](#), [stat_peaks\(\)](#), [stat_spikes\(\)](#), [stat_wb_box\(\)](#), [stat_wb_column\(\)](#), [stat_wb_contribution\(\)](#), [stat_wb_hbar\(\)](#), [stat_wb_irrad\(\)](#), [stat_wb_label\(\)](#), [stat_wb_mean\(\)](#), [stat_wb_relative\(\)](#), [stat_wb_sirrad\(\)](#), [stat_wb_total\(\)](#), [stat_wl_strip\(\)](#)

Examples

```
# ggplot() methods for spectral objects set a default mapping for x and y.
ggplot(sun.spct) + geom_line() +
  stat_wl_summary(geom = "hline")
ggplot(sun.spct) + geom_line() +
  stat_wl_summary(label.fmt = "mean = %.3f", color = "red", vjust = -0.3) +
  stat_wl_summary(geom = "hline", color = "red")
```

Tfr_label *Transmittance axis labels*

Description

Generate cps axis labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
Tfr_label(
  unit.exponent = ifelse(pc.out, -2, 0),
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE),
  pc.out = getOption("ggspectra.pc.out", default = FALSE),
  Tfr.type
)

Tfr_internal_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)

Tfr_total_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = NULL,
  scaled = FALSE,
  normalized = FALSE,
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

Arguments

unit.exponent	integer
format	character string, "R", "R.expresion", "R.character", or "LaTeX".
label.text	character Textual portion of the labels.
scaled	logical If TRUE relative units are assumed.
normalized	logical (FALSE) or numeric Normalization wavelength in manometers (nm).

axis.symbols	logical If TRUE symbols of the quantities are added to the name. Supported only by format = "R.expression".
pc.out	logical, if TRUE use percent as default instead of fraction of one.
Tfr.type	character, either "total" or "internal".

Value

a character string or an R expression.

Note

Default for label.text depends on the value passed as argument to Tfr.type.

Examples

```
Tfr_label(Tfr.type = "internal")
Tfr_label(Tfr.type = "total")
Tfr_label(Tfr.type = "internal", axis.symbols = FALSE)

Tfr_internal_label()
Tfr_internal_label(format = "R.expression", axis.symbols = FALSE)
Tfr_internal_label(-2)
Tfr_internal_label(-3)
Tfr_internal_label(format = "R.expression")
Tfr_internal_label(format = "LaTeX")
Tfr_internal_label(-3, format = "LaTeX")

Tfr_total_label()
Tfr_total_label(format = "R.expression", axis.symbols = FALSE)
Tfr_total_label(-2)
Tfr_total_label(-3)
Tfr_total_label(format = "R.expression")
Tfr_total_label(format = "LaTeX")
Tfr_total_label(-3, format = "LaTeX")
```

w_length_label

Wave- axis labels

Description

Generate wavelength, wavenumber, wave frequency, and energy per photon axis labels in SI units, using SI scale factors. Output can be selected as character, expression (R default devices) or LaTeX (for tikz device).

Usage

```
w_length_label(
  unit.exponent = -9,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["w.length"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
w_number_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["w.number"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
w_frequency_label(
  unit.exponent = 9,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["freq"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
w_energy_eV_label(
  unit.exponent = 0,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

```
w_energy_J_label(
  unit.exponent = -18,
  format = getOption("photobiology.math", default = "R.expression"),
  label.text = axis_labels()[["energy"]],
  axis.symbols = getOption("ggspectra.axis.symbols", default = TRUE)
)
```

Arguments

<code>unit.exponent</code>	integer The exponent in base 10 of the scale multiplier to use.
<code>format</code>	character string, "R", "R.expression", "R.character", or "LaTeX".
<code>label.text</code>	character Textual portion of the labels.
<code>axis.symbols</code>	logical If TRUE symbols of the quantities are added to the name. Supported only by <code>format = "R.expression"</code> .

Details

By default labels consist in a textual name for the quantity, a symbol separated by a comma and units with scale factor in parenthesis. The textual names are by default in English but this default can be

overridden for example with translations to a different language. To change or translate the default texts please see [axis_labels_uk](#). The markup language used for the labels can be selected through a parameter argument, with character strings ready to be parsed into R expressions as default.

Wavelengths are assumed to be expressed in nanometres in the data. The `unit.exponent` corresponds to that desired for the tick labels with the corresponding axis label automatically set to an SI scale factor if possible, and otherwise shown as a power of 10.

These functions are used internally by *x* scales; see [sec_axis_w_number](#) and [scale_x_wl_continuous](#). The scales and secondary axis functions should be used except when defining new scale functions.

Value

a character string or an R expression.

Examples

```
w_length_label()
w_length_label(axis.symbols = FALSE)
w_length_label(format = "R.expression")
w_length_label(format = "LaTeX")
w_number_label()
w_number_label(format = "R.expression")
w_frequency_label()
w_frequency_label(format = "R.expression")
w_energy_J_label()
w_energy_eV_label()
```

w_number

Deprecated functions

Description

To convert wavelength into wavenumber or into frequency, please, use the conversion functions from package 'photobiology' in place of the deprecated functions `w_number()` and `w_frequency()` from this package.

Usage

```
w_number(w.length, unit.exponent = 0)
```

```
w_frequency(w.length, unit.exponent = 0)
```

Arguments

`w.length` numeric wavelength (nm)
`unit.exponent` integer Exponent of the scale multiplier implicit in result, e.g., use 3 for kJ.

Deprecated

These functions will be removed from package 'ggpmisc' in the near future.

See Also

See [w12wavenumber](#) for the functions to be used in all new code.

Examples

```
library(photobiology)
```

```
w12wavenumber(600)
```

```
w12frequency(600)
```


Index

- * **autoplot functions**
 - plot.generic_spct, 54
- * **autoplot methods**
 - autoplot.calibration_spct, 6
 - autoplot.cps_spct, 9
 - autoplot.filter_spct, 13
 - autoplot.object_spct, 17
 - autoplot.raw_spct, 20
 - autoplot.reflector_spct, 24
 - autoplot.response_spct, 27
 - autoplot.source_spct, 31
 - autoplot.waveband, 34
 - set_annotations_default, 85
- * **hplot**
 - autoplot.waveband, 34
- * **stats functions**
 - stat_color, 88
 - stat_find_qtys, 89
 - stat_find_wls, 92
 - stat_label_peaks, 95
 - stat_peaks, 98
 - stat_spikes, 102
 - stat_wb_box, 105
 - stat_wb_column, 108
 - stat_wb_contribution, 110
 - stat_wb_hbar, 113
 - stat_wb_irrad, 116
 - stat_wb_label, 120
 - stat_wb_mean, 122
 - stat_wb_relative, 125
 - stat_wb_sirrad, 128
 - stat_wb_total, 132
 - stat_wl_strip, 135
 - stat_wl_summary, 137
- A_internal_label (A_label), 39
- A_label, 39
- A_total_label (A_label), 39
- aes, 46, 88, 90, 92, 96, 99, 103, 106, 108, 110, 113, 117, 120, 123, 126, 130, 133, 136, 138
- aes_, 46, 88, 90, 92, 96, 99, 103, 106, 108, 110, 113, 117, 120, 123, 126, 130, 133, 136, 138
- Afr_label, 5
- autoplot, 8, 9, 12, 15, 16, 19, 20, 22, 23, 26, 27, 29, 30, 33, 34
- autoplot.calibration_mspct
 - (autoplot.calibration_spct), 6
- autoplot.calibration_spct, 6, 12, 16, 20, 23, 27, 30, 34, 36, 55, 86
- autoplot.cps_mspct (autoplot.cps_spct), 9
- autoplot.cps_spct, 9, 9, 16, 20, 23, 27, 30, 34, 36, 55, 86
- autoplot.filter_mspct
 - (autoplot.filter_spct), 13
- autoplot.filter_spct, 9, 12, 13, 20, 23, 27, 30, 34, 36, 55, 86
- autoplot.object_mspct
 - (autoplot.object_spct), 17
- autoplot.object_spct, 9, 12, 16, 17, 23, 27, 30, 34, 36, 86
- autoplot.raw_mspct (autoplot.raw_spct), 20
- autoplot.raw_spct, 9, 12, 16, 20, 20, 27, 30, 34, 36, 55, 86
- autoplot.reflector_mspct
 - (autoplot.reflector_spct), 24
- autoplot.reflector_spct, 9, 12, 16, 20, 23, 24, 30, 34, 36, 86
- autoplot.response_mspct
 - (autoplot.response_spct), 27
- autoplot.response_spct, 9, 12, 16, 20, 23, 27, 27, 34, 36, 55, 86
- autoplot.source_mspct
 - (autoplot.source_spct), 31
- autoplot.source_spct, 9, 12, 16, 20, 23, 27, 30, 31, 36, 55, 86

- autoplot.waveband, [9](#), [12](#), [16](#), [20](#), [23](#), [27](#), [30](#), [34](#), [34](#), [55](#), [86](#)
- autotitle, [37](#)
- axis_labels (axis_labels_uk), [38](#)
- axis_labels_none (axis_labels_uk), [38](#)
- axis_labels_uk, [38](#), [83](#), [143](#)
- axis_labels_uk_comma (axis_labels_uk), [38](#)

- black_or_white, [41](#)
- borders, [47](#), [88](#), [90](#), [93](#), [96](#), [100](#), [103](#), [106](#), [108](#), [111](#), [114](#), [118](#), [121](#), [123](#), [127](#), [130](#), [133](#), [136](#), [138](#)

- calibration_spct, [9](#)
- chroma_spct, [14](#), [18](#), [25](#), [32](#), [88](#), [90](#), [93](#), [96](#), [100](#), [103](#), [106](#), [108](#), [111](#), [114](#), [117](#), [120](#), [123](#), [126](#), [130](#), [133](#), [136](#)
- color_chart, [42](#)
- color_of, [89](#), [137](#)
- counts_label, [43](#)
- cps_label, [44](#)
- cps_spct, [12](#)

- exponent2factor (exponent2prefix), [45](#)
- exponent2prefix, [45](#)
- exponent2prefix_name (exponent2prefix), [45](#)

- filter_spct, [16](#)
- find_peaks, [91](#), [94](#), [97](#), [101](#)
- find_spikes, [104](#)
- format, [86](#), [87](#)

- geom_path, [47](#)
- geom_point, [47](#)
- geom_ribbon, [47](#)
- geom_spct, [46](#)
- ggplot, [47](#), [50](#)
- ggrepel, [91](#), [94](#), [97](#), [101](#), [104](#)
- ggspectra (ggspectra-package), [3](#)
- ggspectra-package, [3](#)
- ggtitle_spct (autotitle), [37](#)

- has_SI_prefix (exponent2prefix), [45](#)

- layer, [47](#), [88](#), [90](#), [93](#), [96](#), [99](#), [103](#), [106](#), [108](#), [111](#), [114](#), [118](#), [121](#), [123](#), [127](#), [130](#), [133](#), [136](#), [138](#)

- multipliers_label, [51](#)
- multiplot, [52](#)

- nearest_SI_exponent (exponent2prefix), [45](#)
- normalize, [9](#), [12](#), [16](#), [20](#), [23](#), [27](#), [30](#), [34](#)

- object_spct, [20](#)

- photobiology, [8](#), [12](#), [15](#), [19](#), [22](#), [26](#), [29](#), [33](#)
- plot.generic_mspct (plot.generic_spct), [54](#)
- plot.generic_spct, [54](#)
- plot.waveband (plot.generic_spct), [54](#)
- prefix2exponent (exponent2prefix), [45](#)
- prefix_name2exponent (exponent2prefix), [45](#)

- raw_spct, [23](#)
- reflector_spct, [27](#)
- response_spct, [30](#)
- Rfr_label, [55](#)
- Rfr_specular_label (Rfr_label), [55](#)
- Rfr_total_label (Afr_label), [5](#)

- s.e.action_label (s.e.response_label), [57](#)
- s.e.irrad_label, [56](#)
- s.e.response_label, [57](#)
- s.q.action_label (s.e.response_label), [57](#)
- s.q.irrad_label (s.e.irrad_label), [56](#)
- s.q.response_label (s.e.response_label), [57](#)
- scale_continuous, [60](#), [62–65](#), [67](#), [69](#), [71](#), [72](#), [74](#), [76](#), [79](#), [81](#)
- scale_x_energy_eV_continuous, [59](#)
- scale_x_energy_J_continuous (scale_x_energy_eV_continuous), [59](#)
- scale_x_frequency_continuous, [61](#)
- scale_x_wavenumber_continuous, [62](#)
- scale_x_wl_continuous, [63](#), [143](#)
- scale_y_A_continuous, [66](#)
- scale_y_A_internal_continuous (scale_y_A_continuous), [66](#)
- scale_y_A_total_continuous (scale_y_A_continuous), [66](#)
- scale_y_Afr_continuous, [64](#)

- scale_y_counts_continuous, 68
- scale_y_counts_tg_continuous
 - (scale_y_counts_continuous), 68
- scale_y_cps_continuous, 70
- scale_y_multipliers_continuous, 71
- scale_y_Rfr_continuous, 72
- scale_y_Rfr_specular_continuous
 - (scale_y_Rfr_continuous), 72
- scale_y_Rfr_total_continuous
 - (scale_y_Rfr_continuous), 72
- scale_y_s.e.action_continuous
 - (scale_y_s.e.response_continuous), 77
- scale_y_s.e.irrad_continuous, 74
- scale_y_s.e.irrad_log10
 - (scale_y_s.e.irrad_continuous), 74
- scale_y_s.e.response_continuous, 77
- scale_y_s.q.action_continuous
 - (scale_y_s.e.response_continuous), 77
- scale_y_s.q.irrad_continuous
 - (scale_y_s.e.irrad_continuous), 74
- scale_y_s.q.irrad_log10
 - (scale_y_s.e.irrad_continuous), 74
- scale_y_s.q.response_continuous
 - (scale_y_s.e.response_continuous), 77
- scale_y_Tfr_continuous, 80
- scale_y_Tfr_internal_continuous
 - (scale_y_Tfr_continuous), 80
- scale_y_Tfr_total_continuous
 - (scale_y_Tfr_continuous), 80
- sec_axis, 60, 61, 63
- sec_axis_energy_eV (sec_axis_w_number), 82
- sec_axis_energy_J (sec_axis_w_number), 82
- sec_axis_w_frequency
 - (sec_axis_w_number), 82
- sec_axis_w_number, 82, 143
- sec_axis_wl (sec_axis_w_number), 82
- set_annotations_default, 9, 12, 16, 20, 23, 27, 30, 34, 36, 85
- set_w.band_default
 - (set_annotations_default), 85
- setGenericSpct, 50
- SI_pl_format, 86
- SI_plain (SI_pl_format), 86
- SI_tagged (SI_tg_format), 87
- SI_tg_format, 87
- source_spct, 34
- sprintf, 90, 93, 96, 100, 103, 111, 117, 120, 123, 126, 130, 133, 138
- stat_color, 88, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_find_qtys, 89, 89, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_find_wls, 89, 91, 92, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_label_peaks, 89, 91, 94, 95, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_label_valleys (stat_label_peaks), 95
- stat_peaks, 89, 91, 94, 97, 98, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_spikes, 89, 91, 94, 97, 101, 102, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_valleys, 97
- stat_valleys (stat_peaks), 98
- stat_wb_box, 89, 91, 94, 97, 101, 104, 105, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_wb_column, 89, 91, 94, 97, 101, 104, 107, 108, 112, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_wb_contribution, 89, 91, 94, 97, 101, 104, 107, 109, 110, 115, 119, 122, 124, 128, 132, 134, 137, 139
- stat_wb_e_irrad (stat_wb_irrad), 116
- stat_wb_e_sirrad (stat_wb_sirrad), 128
- stat_wb_hbar, 89, 91, 94, 97, 101, 104, 107, 109, 112, 113, 119, 122, 124, 128, 132, 134, 137, 139
- stat_wb_irrad, 89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 116, 122, 124, 128, 132, 134, 137, 139
- stat_wb_label, 89, 91, 94, 97, 101, 104, 107,

109, 112, 115, 119, 120, 124, 128, 132, 134, 137, 139
 stat_wb_mean, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 122, 128, 132, 134, 137, 139*
 stat_wb_q_irrad (stat_wb_irrad), *116*
 stat_wb_q_sirrad (stat_wb_sirrad), *128*
 stat_wb_relative, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 125, 132, 134, 137, 139*
 stat_wb_sirrad, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 128, 134, 137, 139*
 stat_wb_total, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 132, 137, 139*
 stat_wl_strip, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 135, 139*
 stat_wl_summary, *89, 91, 94, 97, 101, 104, 107, 109, 112, 115, 119, 122, 124, 128, 132, 134, 137, 137*
 strptime, *8, 11, 14, 18, 22, 25, 29, 32, 37*

 Tfr_internal_label (Tfr_label), *140*
 Tfr_label, *140*
 Tfr_total_label (Tfr_label), *140*

 w_energy_eV_label (w_length_label), *141*
 w_energy_J_label (w_length_label), *141*
 w_frequency (w_number), *143*
 w_frequency_label (w_length_label), *141*
 w_length_label, *141*
 w_number, *143*
 w_number_label (w_length_label), *141*
 waveband, *9, 12, 16, 20, 23, 27, 30, 34, 36*
 wl2wavenumber, *144*
 wl_guide (stat_wl_strip), *135*